

## Barton 'K' Cam Range

### #70100, 70200, 70300

Manufactured from Dupont Kevlar/Zytal, K Cams are available in 3 sizes to accept lines up to 14mm (9/16") in diameter. This advanced material offers performance advantages over carbon fibre and conventional glass-reinforced resins.

'K' cams are very strong, lightweight and have excellent wear-resistance. A progressive tooth design ensures maximum holding power on all types of line, whilst maintaining minimum wear to both cam and line.

'K' Cam bases feature a stainless steel wear bar for prolonged life.

The cams utilise stainless steel leaf springs which give a smooth but positive action and a longer life span than conventional wire springs.

'K' cam cleats come with a range of accessories to include: Pillar fairleads, Wire fairleads and Top fairleads

#### #70100 - 'K' Cam Mini

Holding power 190kg (420lbs), maximum line 10mm (3/8"), hole centres 30mm (1 3/16), weight 17g (0.6oz)

#### #70200 - 'K' Cam Midi

Holding power 230kg (508lbs), maximum line 12mm(1/2") line, hole centres 40mm (1 9/16"), weight 34g (1.2oz)

#### #70300 - 'K' Cam Maxi

Holding power 260kg (570lbs), maximum line 14mm (9/16"), hole centres 50mm(2") , weight 50g (1.8oz)

