

Thank you for choosing Barton Marine Equipment.

Please read these instructions carefully before use and retain them for future referral. This sling is recommended for motors up to 15hp.

Box contents: 1 x 50mm Main Strap with D ring, 1 x 25mm Clamp Strap and 2 x Lateral Straps, pre-attached to the Main Strap.

Step One.

Attach the Clamp Strap to the clamp bracket of the motor, ensuring it's attached above the toggle clamps. This needs to be securely fastened and is engineered to be left on the motor. Ensure that the D rings are on either side of the bracket.



Step Two.

Pass the Main Strap around aft of the motor cover and position it so that it aligns with the shaft. Slide the buckle down so the strap fits snugly against the motor body.



Step Three.

Attach the Lateral Straps to the D rings on the Clamp Strap and then tighten the buckles on both sides until they are tight against the motor body.



Final Set Up.

It's important to check the balance of your motor in the Sling and it's recommended that you do this with two people. The motor needs to hang in the sling with the Main Strap in line with the shaft and centrally balanced. If it rocks backwards or forwards to find the centre of balance adjust the length of the Lateral Straps and the point at which the motor sits in the Main Strap until you find the correct point of balance.

When you are happy that the motor sits correctly in the Sling you can lift with davits or blocks, Barton's Skylock Block, part numbers N09411 and N09421, are a good choice for this as when you let go of the line it is locked in place and there is no chance of dropping the motor.

To remove the Sling simply disconnect the Main Strap from the Clamp Strap, which can be left in place.



Barton SkyLock 400/800

N09411 & N09421 Product Information

Can be used in conjunction with 88000 Outboard Motor Sling

Barton SkyLock 400/800

The Barton SkyLock is an integral part of the SkyDock lifting system. Two models are available, one lifting up to 400kg and a heavier version for lifting up to 800kg.

The clever design and positioning of the locking cams means the control line will never slip even when accidentally released.

Manufactured in our factory using 316 stainless steel side plates, glass reinforced nylon cover plates and aluminium cam plates to ensure a long service life with minimal maintenance.

Can be used to lift dinghy outboards, provisions and equipment on board, especially useful when short-handed. Around the home, SkyLock can be used for hoisting individual items such as bicycles and toys into unused roof space.

Maximum lifting load up to 400/800kg

Maximum line: 5mm/12mm
Length: 110mm/152mm
Height: 28mm/38mm
Width: 90mm/110mm
Weight: 181/450 grams

N09411 400kg



N09421 800kg

