







Welcome to the 56th edition of the Barton Catalogue.

For more than seventy-five years, Barton Marine has set the benchmark for high quality marine deck hardware.

Our products are made in the UK at our purpose-built factory in Whitstable on the North Kent Coast, with a nautical range of more than 2,000 specialist products.

Barton's range of performance deck equipment continues to set the bar for quality construction that is trusted globally by cruising sailors, racing enthusiasts, sailing schools and seasoned mariners.

Our Victory Wooden Block Range is still the only known supply of highperformance ball-bearing blocks offered for classic yachts and their passionate crews.

And now the revival of our Tufnol Block Range – 'TUPHblox' – complements classic rigging worldwide.

Our sleek new traveller cars and track systems are pushing our designs ahead with boat builders, sliding system designers and end users. And our nautical accessories are used in sailboats and power yachts alike.

Beyond marine applications, our equipment is certified by diverse industrial sectors that require top grade raw materials, design engineering, skilled workmanship and reliable lead times that our UK production team delivers.

We remain committed to investing in manufacturing in the UK. Our products are researched, designed, manufactured and assembled at our headquarters in England and delivered worldwide by our dynamic network of distributors and dealers who are passionate supporters of the Barton brand.

Barton believes in clean innovation and remains dedicated to sustainable ways of protecting our environment and supporting the communities where we produce and sell our products.

Thank you for your support. Our Barton Team members are here to offer technical and sales advice for all the sectors we serve.

Suzanne Blaustone CEO



British made since 1948

# **Contents**

Product guide	4	Deck Mounted Hardware	
Heart of the Barton Block	5		
Boat size guide – blocks	6	Barton DO 550 Clutches	78
Boat size guide – traveller systems	7	Rope Clutches & Mast Base Organisers	79
Block system diagrams	8	Deck Organisers	80
Dlasks		Barton Composite Winches	81
Blocks		The Barton Wincher Winch Handles & Accessories	82 83
20mm Size 0 blocks	10	Winch Handles & Accessories	03
30mm Size 1 blocks	12	Sail Handling Kits	
35mm Size 2 blocks	14	San Harianing Kits	
45mm Size 3 blocks	16	Stanchion Lead Blocks & Accessories	84
58mm Size 4 & 54mm Size 5 blocks	18	Continuous Line Furler	86
64mm Size 6 blocks	20	Single Line Furler	87
70mm Size 7 blocks	22	Lazy Jack Kits & Mast Step	88
Fiddle Blocks	24	Reefing Kits & Hooks	89
Barton Ball Bearing Ratchet Blocks	26	Boom Outhaul Traveller Kits	89
		Boom Vang Systems (Handy Billies)	90
Wooden Blocks – Victory Collection		Boomstrut	
Classic Wooden Blocks with Torlon Needle Bearings	29	boomstrut	
Classic Wooden Blocks – Victory Collection	30	Barton Boomstrut	92
TUPHblox		Dinghy Accessories & Kits	
T. facil Diagraphic Decis Diagraphic	22	Discolar Kita	0.4
Tufnol Pheonolic Resin Blocks	32	Dinghy Kits Land Sailing Kits	94 95
Specialist blocks		Aluminium Tiller Extensions	96
Specialist blocks		Carbon Tiller Extensions	97
Wire Rope Blocks	38	Flexible Tiller Joints	97
High Load & Foot Blocks	40	Dinghy & Dayboat fittings	98
Snatch Blocks	41	Dinghy Mast Support	99
SkyLock Block	41	Windicator	100
Low Friction Rings	42	Dinghy Support Parts	101
		Deck Hardware	102
Industrial projects		Ancillary Equipment	103
Bulkhead Pipe Glands	45	Rope Handling	
Industrial Blocks	46		
Block on a Strop	46	Kevlar Cam Cleats	104
Custom Design & Build	47	Cleats	106
		Wingnuts	107
Track & Traveller Systems		Clevis Pins, Split Rings & Springs	108
	40	Shackles, 'S' Hooks & Swivels	109
Recirculating Ball Traveller Systems	48	Deck Playes & Eyes	110
Mainsheet Preassembled Kits	49	Sheaves	111
Removable Mainsheet System Kits Recirculating Ball Mainsheet Systems	50 52	Accessories & Safety	
End Fittings & Accessories	54	Accessories & Salety	
Ball Bearing Traveller Spare Kits	56	Wear Pads & Line Tamers	112
Recirculating Ball Towable Genoa Car Systems	58	Fuel Whistle & EasySplice	113
Recirculating Ball 16mm Track	59	ClamSeal	114
Barton Genoa Car Range	60	SkyDock	115
T Track Systems	61	Inspection Covers	115
20mm T Track, Cars & Accessories	62	Outboard Motor Sling	116
25mm T Track, Cars & Accessories	64		
32mm T Track, Cars & Accessories	66	Index	
T Track Spinnaker Pole Parts & Systems	68		
19mm I Beam Track, Cars & Accessories	70	Alphabetical index of content	117
24mm I Beam Track, Cars & Accessories	71	Alphabetical index of part numbers	118
28mm I Beam Track, Cars & Accessories	72		
Track Systems			
Sliding Roof, Seat & Furniture Track	74		
Sliding System Modules	76		
Locking Modules	77		







"Seven decades of UK manufacturing defines the Barton legacy...it's amazing.

To be part of this proud British heritage is great.

The design work, engineering and production we do at Barton produces equipment that will still be in use for decades to come. The feedback we hear at boat shows and trade events worldwide along with the support we provide ensures that Barton products are strong, robust and durable."

**Jeff Webber** Chief Commercial Officer Barton Marine

# Product guide

To ensure your safety, your yacht's performance and to make certain that you get best value and quality, we provide guides to clarify your deck gear choices.

The diagrams on p8-9 explain how to achieve many tasks from increasing the purchase on your kicker system to ensuring your halyards are lead back into the cockpit correctly.

Our suggested boat size table on p6-7 is designed to help you correctly identify the right size of product for your application. From picking the correct size of blocks for your mainsheet system to ensuring you have the right size and type of blocks for your mast base, we provide some simple rules to consider when choosing a product.

Our team of experienced sailors are always available to assist you when making choices. Please contact us by phone or email at any time.

## Some tips when selecting and fitting blocks...

- Ensure the block is strong enough for the job required (rope capacity does not denote strength).
- Plain bearing versus ball bearing sheave ball bearing sheaves do not hold the same load as plain sheaves – see p5 for advice.
- Check line capacity is sufficient. A tight fit will increase friction, and cause wear to the block and line.
- Always ensure a fair lead. Blocks are designed to have the load running directly through the central axis.
- Never load one sheave only on a double block. It will cause the block to tilt.
- When fitting blocks always ensure that there is sufficient articulation.
- When fitting cam cleat blocks, ensure that the cam cleat is set at the correct angle to allow easy release.
- Foot blocks and cheek blocks should always be throughbolted for maximum strength.

#### Care of blocks and deck fittings...

- Regularly rinse blocks and deck fittings with fresh water to remove salt.
- Ensure that sheaves run freely.
- Check all blocks on a regular basis.
- Check shackles and pad eyes for signs of strain or overload.
- Inspect cam cleats for excessive wear.

#### **AVAILABLE FIXTURES SIZE 0 TO 7 BLOCKS**



#### **FIXED EYE**

A plain attachment eye.



#### **SNAP SHACKLE**

A cast stainless steel swivelling snap shackle - ideal for quick release downhauls or vangs.



#### **BECKET**

All the appropriate blocks are available with or without becket.



#### **SWIVEL**

Range of 316L stainless steel high load performance swivel shackles.



#### **DOUBLE TANG**

For use with the Barton mast base organiser.



#### **REVERSE SHACKLE**

Allows the shackle to be fixed but at any 90° angle to the sheave.



## **TUPHBLOX EYE**

Allows a shackle to be fitted by passing the bow through the elongated slot or onto the pin.



**Foot Blocks:** Fastenings of the minimum diameter suggested should be used to gain full load capacity. Ensure that suitable mounting pads are provided under deck. Stacking blocks to achieve doubles will reduce working loads quoted.

**Boat Sizes:** Suggested boat sizes are given as guidance only and assume a monohull with boom end sheeting, loaded vertically to the traveller. Mid-boom sheeting, severe angled take offs and curved tracks can impose greater loads and suitable allowances should be made for this. If at all unsure of your choice it is important to seek further advice. If you are close to the maximum boat size suggested, we would advise upgrading to a Torlon package, long car or the next size up.

**Mast Steps:** Mast steps should always be used in conjunction with a Bosun's chair or harness. Always have a crew member at hand to control the halyard. Do not go aloft barefoot and always put safety first.

# Heart of the Barton Block

# The sheave

#### BARTON PLAIN BEARING BLOCKS

All Barton plain bearing blocks have a precision moulded Acetal sheave running on a large diameter brass bearing, ensuring free running under the highest of loads.



# THE BARTON BALL BEARING OPTION

All Barton blocks from series 0 to size 7 offer the option of a high performance, low friction ball bearing sheave. The balls are made from Delrin.





Mast base organiser 81550 (see p79)

## PLAIN BEARING VERSUS BALL BEARING SHEAVES

Use a plain bearing sheave for a high static load; for example mast base, (main and Genoa) mast head and kicker or when the sheave will be under a high load and the sheave will turn infrequently.

Use a ball bearing sheave where fast, constant adjustment is required, for example mainsheets or spinnaker sheets.

Barton ball bearing sheaves in independent tests conducted by UK and European sailing magazines concluded Barton is the "best buy" choice among the competition.

## AN EXPLANATION

Our design features twin rows of Delrin balls running on a large diameter centre boss. This enables the load bearing surface to be maximised over the greatest number of bearings, giving higher performance in all directions.

Barton's unique design and material choices bring you the possibility of upgrading your block systems at a realistic cost.



**BARTON ROLLER SHEAVE** 



**COMPETITOR ROLLER SHEAVE** 

More ball bearings used result in increased capability and less rolling resistance

Friction is reduced by 23% when using a Barton ball bearing sheave compared to a plain sheave.



# **Boat size guide**

# Important note: boat sizes

Suggested boat sizes are given as a guidance only and assume a monohull with boom end sheeting, loaded vertically to the traveller.

Mid-boom sheeting, severely angled take offs and curved tracks can impose greater loads and suitable allowances should be made for this. If at all unsure of your choice, it is important to seek further advice. If you are close to the maximum boat size suggested, we would advise upgrading to a Torlon package, long car or the next size up.

## **BLOCKS**

#### MAINSHEET BLOCKS END BOOM SHEETING

Boat Size	5.5m 18ft	7m 23ft	10m 23ft	11.5m 38ft	13m 42ft	14m 46ft
Size 1 - 30mm sheave						
Size 2 - 35mm sheave						
Size 3 - 45mm sheave						
Size 4/5 - 58/54 mm sheave						
Size 6 - 64mm sheave						
Size 7 - 70mm sheave						

#### **MAST BASE / HALYARD BLOCKS**

N 5 15	6m	9m	10m	11.5m	13m	14m
Boat Size	20ft	29ft	33ft	38ft	42ft	46ft
Size 0 - 20mm sheave						
Size 1 - 30mm sheave						
Size 2 - 35mm sheave						
Size 3 - 45mm sheave						
Size 4/5 - 58/54 mm sheave						
Size 6 - 64mm sheave						
Size 7 - 70mm sheave						

## **SPINNAKER SHEET / GUY BLOCKS**

- Read Since	5.5m	5m	7m	10m	11.5m	13m	14m
Boat Size	18ft	20ft	23ft	33ft	38ft	42ft	46ft
Size 0 - 20mm sheave							
Size 1 - 30mm sheave							
Size 2 - 35mm sheave							
Size 3 - 45mm sheave							
Size 4/5 - 58/54 mm sheave							
Size 6 - 64mm sheave							
Size 7 - 70mm sheave							

## **KICKER BLOCKS**

Boat Size	6m	7m	8m	8.5m	11m	11.5m	13m	14m
	23ft	26ft	28ft	33ft	36ft	38ft	42ft	46ft
Size 0 - 20mm sheave								
Size 1 - 30mm sheave								
Size 2 - 35mm sheave								
Size 3 - 45mm sheave								
Size 4/5 - 58/54 mm sheave								
Size 6 - 64mm sheave								
Size 7 - 70mm sheave								

#### **METRIC TO IMPERIAL CONVERSION GUIDE**

#### **MILLIMETRE TO INCHES**

1.6mm <sup>1</sup> / <sub>16</sub> "	19mm 3/4"
3.2mm 1/8"	21mm 13/ <sub>16</sub> "
4.8mm <sup>3</sup> / <sub>16</sub> "	22mm 7/8"
6.4mm 1/4"	24mm 15/ <sub>16</sub> "
7.9mm <sup>5</sup> / <sub>16</sub> "	25.4mm 1"
9.5mm 3/8"	51mm 2"
11mm <sup>7</sup> / <sub>16</sub>	76mm 3"
13mm1/2"	102mm 4"
14mm <sup>9</sup> / <sub>16</sub> "	127mm 5"
16mm 5/8"	152mm 6"
17mm	

#### **GRAMS TO POUNDS & OUNCES**

113g 4oz	1814g 4lbs
227g 8oz	2268g 5lbs
340g 12oz	2722g 6lbs
454g 1lbs	3175g 7lbs
680g 11bs 8oz	3629g 8lbs
907g 2lbs	4082g 9lbs
1360g 3lbs	4536g 10lbs

# **TRAVELLER SYSTEMS**

## TRACK SYSTEMS

# **MAINSHEET TRAVELLER SYSTEMS**

Boat Size	5.5m	8.5m	11m	14m
	18ft	28ft	36ft	46ft
Size 0 - 16mm				
Size 1 - 20mm				
Size 2 - 26mm		_		
Size 3 - 30mm				

# **RECIRCULATING GENOA**

Boat Size	8.5m	11m	13m
	26ft	36ft	42ft
Size 0 - 16mm			
Size 1 - 26mm			
Size 3 - 30mm			

## **PIN STOP GENOA**

Boat Size	7m	8.5m	11.5m	14.5m
	23ft	28ft	38ft	48ft
20mm (13/16") T track				
25mm (1') T track				
32mm (1 1/4") T track		_		
32mm (1 1/4") T track HIGH LOAD				

# **WINCH & CLUTCH**

## **PRIMARY GENOA WINCH**

N 5 15	7m	8m	9.5m	10m	11.5m
Boat Size	23ft	26ft	31ft	33ft	38ft
Single speed 8:1					
Twin speed 16:1					
Twin speed 23:1					

## **SECONDARY HALYARD WINCH**

. —————————————————————————————————————					
Boat Size	7m	8m	9.5m	10m	11.5m
	23ft	26ft	31ft	33ft	38ft
Single speed 8:1					
Twin speed 16:1					
Twin speed 23:1					

## **ROPE CLUTCHES**


B	8m	9.5m	10m	11m	12m
Boat Size	26ft	31st	33ft	36ft	39ft
DO 550 rope clutch					
Standard clutch					


# METRIC TO IMPERIAL CONVERSION GUIDE

# GRAMS TO KILOGRAMS TO POUNDS

	INIEGGIAMIS IG I GOITE	-5
1000g 1kg	10kg	200kg 440lbs
	20kg 44lbs	300kg660lbs
	30kg 66lbs	400kg880lbs
	40kg 88lbs	500kg 1100lbs
	50kg 110lbs	600kg 1320lbs
	60kg 132lbs	700kg 1540lbs
	70kg 154lbs	800kg 1760lbs
	80kg 176lbs	900kg 1980lbs
	90kg 198lbs	1000kg2200lbs
	100kg 220lbs	2000kg 4400lbs

# Block system diagrams





# 20mm Size 0 blocks

The 20mm sheave Size 0 block range is available in plain and ball bearing assembly. Engineered for dinghy sailors and small craft enthusiasts, the series defines high strength, good performance and lightweight design for racing and day boats. Also ideal for lead blocks, flag pennants and small line systems on larger yachts.



N00191

N00211

20

0.7

0.9

N10191

N10211

18

36

0.6

1.3

53

2 1/16

2 1/2

9

10 11

Double – fixed eye + becket block

Single – swivel + becket (without shackle) block

#### **TECHNICAL DETAILS**

Cheeks - Glass Reinforced Nylon Sheaves - Acetal Straps & Fittings – 316 Stainless Steel Plain Bearing – Brass Ball Bearings – Delrin



Sheave size 20mm x 8mm (25/32" x 5/16")



**PLAIN BEARING** WLL 275kg (606lbs) Break load 550kg (1210lbs)



N00311

**BALL BEARING** Max rolling load 130kg (286lbs) Break load 550kg (1210lbs)



14



N00250

Max rope diameter 6mm (1/4")

















N00330











N00511



16





























N00932









РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	ММ	INCH
12	Double – swivel block	N00230	46	1.6	N10230	41	1.4	68	2 11/16
13	Double – swivel + becket block	N00231	50		N10231	46	1.6		
14	Double – stand up block	N00250	28	1	N10250	24	0.8	30	3 1/16
15	Triple - fixed eye block	N00310	53		N10310	46	1.6	50	1 15/16
16	Triple – fixed eye + becket block	N00311	57	1.9	N10311	50	1.8	62	2 7/16
17	Triple – swivel block	N00330	64		N10330	57	2		
18	Triple – swivel + becket block	N00331	66	2.3	N10331	61	2.2	82	3 1/4
19	Triple – fixed eye + becket + cam block	N00511	112		N10511	106	3.7	73	2 7/8
20	Triple – swivel + cam block	N00930	118	4	N10930	112	4	96	3 3/4
21	Triple – swivel + becket + cam block	N00931	123	4 3/16	N10931	117	4.1	96	3 3/4
22	Triple – swivel + becket + cam at 90° block	N00932	119	4.2	N10932	118	4.2	96	3 3/4

# 30mm Size 1 blocks

The 30mm sheave Size 1 block range is designed with an internal stainless steel frame for high strength and durability. Available in plain and ball bearing sheave options, the lightweight modern design is available in variations that allow for a multitude of uses on every size craft. See p8-9 for rigging specifications.



		Barten barton marine.com			<b>bart</b> ®r				
PHOTO NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	ММ	INCH
1	Single – double tang block	N01090	47	1.7	N11090	45	1.6	65	2 <sup>9</sup> / <sub>16</sub>
	Single – double tang + becket block	N01091	57	2.0	N11091	53	1.9	81	3 3/16
2	Single – fixed eye block	N01110	35	1.2	N11110	33	1.2	55	2 3/16
3	Single – fixed eye + becket block	N01111	45	1.6	N11111	43	1.5	71	2 13/16
4	Single – swivel block	N01130	43	1.5	N11130	41	1.4	72	2 13/16
5	Single – swivel + becket block	N01131	53	1.9	N11131	52	1.8	87	3 7/16
6	Single – upright block	N01150	63	2.2	N11150	62	2.2	53	2 1/16
7	Single – upright with fairlead block	N01151	69	2.4	N11151	69	2.4	63	2 1/16
8	Lightweight cheek block	N01160	21	0.7	N11160	20	0.7	55	2 3/16
9	Single – stand up block	N01170	42	1.5	N11170	40	1.4	67	2 5/8
10	Single – spinnaker lead block	N01180	57	2.0	N11180	56	2.0	105	4 1/8

## **TECHNICAL DETAILS**

Cheeks - Glass Reinforced Nylon Sheaves - Acetal Straps & Fittings – 316 Stainless Steel Plain Bearing – Brass Ball Bearings – Delrin



(5/16")

Sheave size 30mm x 12mm (1 3/16" x 15/32")


Max rope diameter 8mm



PLAIN BEARING WLL 355kg (782lbs) Break load 710kg (1565lbs)



BALL BEARING
Max rolling load 245kg (540lbs)
Break load 550kg (1210lbs)






# Barten bortomerine com

РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
11	Lightweight lead block	N01190	19	0.7	N11190	18	0.6	44	1 3/4
12	Double – fixed eye block	N01210	64	2.3	N11210	61	2.2	63	2 1/2
13	Double – fixed eye + becket block	N01211	74	2.6	N11211	69	2.4	77	3 1/16
14	Double – swivel block	N01230		2.8	N11230	74	2.6	78	3 1/16
15	Double – swivel + becket block	N01231	88	3.1	N11231	82	2.9	94	3 11/16
16	Double – upright block	N01250	87	3.1	N11250	84	3.0	53	2 1/16
17	Back-to-back swivel block	N01280	66	2.3	N11280	63	2.2	90	3 9/16
18	Triple – fixed eye block	N01310		3.0	N11310	81	2.9	56	2 3/16
19	Triple – fixed eye + becket block	N01311	96	3.4	N11311	91	3.2	73	2 7/8
20	Triple – swivel block	N01330		3.3	N11330	89	3.1	73	2 7/8
21	Triple – swivel + becket block	N01331	104	3.7	N11331	98	3.5	88	3 7/16

# 35mm Size 2 blocks


The 35mm sheave Size 2 block range provides high performance and load values in a variety of assemblies. The range has an internal stainless steel frame and precision components with plain or ball bearing sheave options. The lightweight design makes this range perfect for a multitude of uses on every yacht. See p8-9 for rigging specifications.



		bartonmarine.com							
PHOTO NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
1	Single – double tang block	N02090	52	1.8	N12090	51	1.8	75	2 15/16
2	Single – double tang + becket block	N02091	63	2.2	N12091	63	2.2	90	3 %16
3	Single – fixed eye block	N02110	40	1.4	N12110	40	1.4	68	2 11/16
4	Single – fixed eye + becket block	N02111	53	1.9	N12111	52	1.8	85	3 3/8
5	Single – swivel block	N02130	49	1.7	N12130	47	1.7	80	3 1/8
6	Single – swivel + becket block	N02131	59	2.1	N12131	59	2.1	95	3 3/4
7	Single – snap shackle block	N02140	84	3	N12140	83	2.9	92	3 5/8
8	Single – snap shackle + becket block	N02141	95	3.4	N12141	95	3.4	108	4 1/4
9	Single – upright block	N02150	78	2.8	N12150	78	2.8	63	2 1/2
10	Single – upright with fairlead block	N02151	86	3	N12151	87	3.1	75	2 15/16
11	Single – cheek block with back plate block	N02160	72	2.5	N12160	72	2.5	80	3 1/8
12	Curved backing plate (for cheek block)	N02161	14	0.5	-	-	_	80	3 1/8
13	Single – stand up block + soft plastic spring	N02170	126	4.4	N12170	126	4.4	100	3 15/16
14	Single – stand up + becket block + plastic spring	N02171	139	4.9	N12171	140	4.9	115	4 1/2
15	Single – spinnaker lead block	N02180	62	2.2	N12180	62	2.2	115	4 1/2

# TECHNICAL DETAILS

Cheeks - Glass Reinforced Nylon Sheaves - Acetal Straps & Fittings – 316 Stainless Steel Plain Bearing – Brass Ball Bearings – Delrin









**BALL BEARING**Max rolling load 260kg (573lbs)
Break load 740kg (1630lbs)



## i VIEW SIZE 2 FIDDLE BLOCKS ON p24

SQTE®N DQTE®N RACE bartonmarine.com		barten RACE bartonmarine.com
-------------------------------------	--	------------------------------

			bartonmarine.com			bartonmarine.com			
РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
16	Double – fixed eye block	N02210	73	2.6	N12210	72	2.5	70	2 12/16
17	Double – fixed eye + becket block	N02211	85	3.0	N12211	85	3.0	88	3 7/16
18	Double – swivel block	N02230	87	3.1	N12230	86	3.0	88	3 7/16
19	Double – swivel and becket block	N02231	99	3.5	N12231	98	3.5	105	4 2/16
20	Double – upright block	N02250	110	3.9	N12250	108	3.8	63	2 8/16
21	Double cheek block	N02260	104	3.7	N12260	102	3.6	80	3 2/16
22	Back-to-back swivel block	N02280	77	2.7	N12280	75	2.6	163	6 7/16
23	Triple – fixed eye block	N02310	100	3.5	N12310	99	3.5	70	2 12/16
24	Triple – fixed eye + becket block	N02311	111	3.9	N12311	111	3.9	88	3 7/16
25	Triple – swivel block	N02330	106	3.7	N12330	105	3.7	80	3 2/16
26	Triple – swivel + becket block	N02331	118	4.2	N12331	117	4.1	95	3 12/16
27	Single – swivel + becket + cam block	N02531	109	3.8	N12531	109	3.8	98	3 14/16
28	Single – snap shackle + becket + cam block	N02541	145	5.1	N12541	145	5.1	108	4 4/16
29	Single – stand up + becket + cam block	N02571	187	6.6	N12571	190	6.7	115	4 8/16
30	Triple – Swivel + becket + cam block	N02931	182	6.4	N12931	182	6.4	100	3 15/16

# 45mm Size 3 blocks

The 45mm sheave Size 3 block range incorporates modern design with stainless steel frames and the latest advanced materials, using 30% fibre glass filled nylon and Acetal sheaves to maximise their strength whilst keeping weight to a minimum. Suitable for use as mainsheet, vangs, lead blocks or wherever a powerful and compact purchase system is required on dinghies, dayboats and smaller yachts. See p8-9 for rigging specifications.




		bartonmarine.com		bartonmarine.com					
РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
1	Single – double tang block	N03090	74	2.6	N13090	77	2.7	87	3 7/16
2	Single – double tang + becket block	N03091	86	3.0	N13091	85	3	103	4 1/16
3	Single – fixed eye block	N03110	63	2.2	N13110	65	2.3	81	3 3/16
4	Single – fixed eye + becket block	N03111	75	2.6	N13111	74	2.6	97	3 13/16
5	Single – swivel block	N03130	78	2.8	N13130	82	2.9	98	3 7/8
6	Single – swivel + becket block	N03131	91	3.2	N13131	91	3.2	114	4 1/2
7	Single – snap shackle block	N03140	106	3.7	N13140	108	3.8	108	4 1/4
8	Single – snap shackle + becket block	N03141	115	4.1	N13141	118	4.2	124	4 7/8
9	Single – upright block	N03150	120	4.2	N13150	124	4.4	73	2 7/8
10	Single – upright with fairlead block	N03151	129	4.6	N13151	133	4.7	93	3 11/16
11	Single – cheek block with back plate block	N03160	106	3.7	N13160	109	3.8	93	3 11/16
12	Curved backing plate (for cheek block) Fits N03160 N13610	N03161	19	0.7	-	-	-	93	3 11/16
13	Single – stand up block + soft plastic spring	N03170	145	5.1	N13170	151	5.3	112	4 7/16
14	Single – stand up + becket block + plastic spring	N03171	157	5.5	N13171	158	5.6	126	4 15/16

# TECHNICAL DETAILS

Cheeks - Glass Reinforced Nylon Sheaves - Acetal Straps & Fittings – 316 Stainless Steel Plain Bearing – Brass Ball Bearings - Delrin

N03230





**PLAIN BEARING** WLL 400kg (881lbs) Break load 800kg (1763lbs)



N03250

N03331

**BALL BEARING** Max rolling load 270kg (595lbs) Break load 740kg (1630lbs)



Max rope diameter 10mm (3/8")







N03330



N03231





20





N03541

N03810

N03310







N03571



N03531











i VIEW SIZE 3 FIDDLE BLOCKS ON p24

arten rtonmarine.com	barten RACE barton marine.com

РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
15	Double – fixed eye block	N03210	109	3.8	N13210	116	4.1	80	3 1/8
16	Double – fixed eye + becket block	N03211	121	4.3	N13211	129	4.6	95	
17	Double – swivel block	N03230	131	4.6	N13230	138	4.9	104	4 1/8
18	Double – swivel + becket block	N03231	143		N13231	152	5.4	118	
19	Double – upright block	N03250	168	5.9	N13250	176	6.2	74	2 15/16
20	Triple – fixed eye block	N03310	151	5.3	N13310	161	5.7	79	
21	Triple – fixed eye + becket block	N03311	160	5.6	N13311	170	6.0	95	3 3/4
22	Triple – swivel block	N03330	166	5.9	N13330	179	6.3	96	
23	Triple – swivel + becket block	N03331	179	6.3	N13331	191	6.7	112	4 7/16
24	Single – snap shackle + becket + cam block	N03541	200	7.1	N13541	200	7.1	124	4 7/8
25	Single – swivel + becket + cam block	N03511	174	6.1	N13511	179	6.3	114	4 1/2
26	Single – stand up + becket + cam block	N03571	242	8.5	N13571	242	8.5	127	
27	Triple – swivel + becket + cam block	N03531	267	9.4	N13531	280	9.9	115	4 1/2
28	Quad with fixed eye block	N03810	350		N13810	330	11.6	85	
29	Quad with fixed eye + becket block	N03811	370	13.1	N13811	350	12.3	100	3 15/16

# 58mm Size 4 & 54mm Size 5 blocks

N04150

## **TECHNICAL DETAILS**

N04160

Cheeks - Glass Reinforced Nylon Sheaves - Acetal Straps & Fittings – 316 Stainless Steel Plain Bearing – Brass Ball Bearings – Delrin

N04250

Size 4 Blocks have a sheave size of 58mm for selected upright and cheek block designs. Size 5 Blocks have a sheave size of 54mm and are through-bolted and riveted for added strength and security. Both sizes feature marine grade moulded side plates. All load-carrying components and interior frames are constructed from 316 stainless steel. Both sizes are available in plain sheave or ball bearing sheave assemblies. These versatile sleek designs are engineered for use on larger cruising and racing yachts and are compatible with our ball bearing mainsheet traveller system.

N04151



Sheave size 58mm x 17mm (2 1/4" x 5/8")

Max rope diameters

Max rope diameter 12mm (1/2")



PLAIN BEARING WLL 630kg (1157lbs) Break load 1260kg (2770lbs)

Max rolling load 440kg (968bs)

Break load 1260kg (277

BALL BEARING

Sheave size 54mm x 17mm (2 1/8" x 5/8")

Max rope diameter 12mm (1/2") PLAIN BEARING
WLL 750kg (1157l

WLL 750kg (1157lbs) Break load 800kg (1763lbs)

BALL BEARING

Max rolling load 525kg (1157lbs) Break load 1500kg (3300lbs)



PHOTO NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
SIZE 5		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	OZ	ММ	INCH
5	Single – double tang block	N05090	162	5.7	N15090	147	5.2	114	4 1/2
6	Single – double tang + becket block	N05091	185	6.5	N15091	170	6.0		5 3/8
7	Single – fixed eye block	N05110	154	5.4	N15110	138	4.9	115	4 1/2
8	Single – fixed eye + becket block	N05111	178	6.3	N15111	163	5.7		5 <sup>5</sup> / <sub>16</sub>
9	Single – reverse shackle block	N05120	177	6.2	N15120	161	5.7	130	5 1/8
10	Single – reverse shackle + becket block	N05121	201	7.1	N15121	185	6.5		5 7/8
11	Single – swivel block	N05130	195	6.9	N15130	180	6.3	130	5 1/8
12	Single – swivel + becket block	N05131	220	7.8	N15131	205	7.2	153	6
13	Single – snap shackle block	N05140	259	9.1	N15140	242	8.5	145	5 11/16
14	Single – snap shackle + becket block	N05141	283	10	N15141	265	9.3	168	6 5/8
15	Single – stand up block + soft plastic spring	N05170	338	11.9	N15170	318	11.2	140	5 1/2
16	Single – stand up + becket block + plastic spring	N05171	370	13.1	N15171	354	12.5	163	6 7/16
17	Double – fixed eye block	N05210	252	8.9	N15210	220	7.8	112	4 7/16
18	Double – fixed eye + becket block	N05211	279	9.8	N15211	247	8.7	133	5 1/4
19	Double – reverse shackle block	N05220	273	9.6	N15220	242	8.5	125	4 15/16
20	Double – reverse shackle + becket block	N05221	298	10.5	N15221	265	9.3	150	5 7/8
21	Double – swivel block	N05230	294	10.4	N15230	263	9.3	130	5 1/8
22	Double – swivel + becket block	N05231	312	11	N15231	286	10.1	156	6 1/8
23	Triple – reverse shackle block	N05320	374	13.2	N15320	331	11.7	130	5 1/8
24	Triple – reverse shackle + becket block	N05321	400	14.1	N15321	355	12.5	150	5 7/8
25	Triple – swivel block	N05330	385	13.6	N15330	342	12.1	130	5 1/8
26	Triple – swivel + becket block	N05331	414	14.6	N15331	375	13.2	150	5 7/8
27	Single – swivel + becket + cam block	N05531	395	13.9	N15531	384	13.5	150	5 7/8
28	Single – snap shackle + becket + cam block	N05541	459	16.2	N15541	445	15.7	165	6 1/2
29	Single – stand up + becket + cam block	N05571	521	18.4	N15571	505	17.8	163	6 7/16
30	Triple – swivel + cam block	N05930	592	20.9	N15930	542	19.1	125	4 15/16
31	Triple – swivel + becket + cam block	N05931	610	21.5	N15931	567	20	154	6 1/16

# 64mm Size 6 blocks

The 64mm sheave Size 6 high load cruiser block range is of rugged construction, featuring high grade injection moulded side plates, with all load carrying components from 316 grade stainless steel. Side plates are through-bolted and riveted for added strength and security. This robust and versatile range is designed for use on larger cruising and racing yachts. All of these blocks are compatible with our main sheet systems.



# Barten bartonmarine.com

РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	ММ	INCH
1	Single – double tang block	N06090	186	6.6	N16090	180	6.3	126	4 15/16
2	Single – fixed eye block	N06110			N16110	173	6.1		4 5/8
3	Single – fixed eye + becket block	N06111	205	7.2	N16111	200	7.1	147	5 13/16
4	Single – reverse shackle block	N06120			N16120	193			5 1/2
5	Single – reverse shackle + becket block	N06121	229	8.1	N16121	220	7.8	165	6 1/2
6	Single – swivel block	N06130	219		N16130	216	7.6	142	5 %16
7	Single – swivel + becket block	N06131	247	8.7	N16131	242	8.5	167	6 9/16
8	Single – snap shackle block	N06140	280		N16140	275	9.7		6 1/8
9	Single – snap shackle + becket block	N06141	310	10.9	N16141	305	10.8	184	7 /4
10	Single – stand up block + soft plastic spring	N06170	360		N16170	361			6 1/8
11	Single – stand up + becket block + plastic spring	N06171	397	14	N16171	391	13.8	180	7 1/16
12	Double – fixed eye block	N06210	298	10.5	N16210	290	10.2	120	4 3/4
13	Double – fixed eye + becket block	N06211	325	11.5	N16211	315	11.1	154	6 1/16
14	Double – reverse shackle block	N06220	319	11.3	N16220	304	10.7	135	5 <sup>5</sup> / <sub>16</sub>


## **TECHNICAL DETAILS**

Cheeks - Glass Reinforced Nylon Sheaves - Acetal Straps & Fittings – 316 Stainless Steel Plain Bearing – Brass Ball Bearings – Delrin





Max rope diameter 14mm (9/16")





**BALL BEARING** 

Max rolling load 700kg (1543lbs) Break load 2000kg (4400lbs)



() VIE	W SIZE 6 FIDDLE BLOCKS ON p25	Barten barton marine.com			<b>bart</b> ®n	RA bartonmar			
РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
15	Double - reverse shackle + becket block	N06221	343	12.1	N16221	335	11.8	164	6 7/16
16	Double - swivel block	N06230	337	11.9	N16230	334	11.8		5 11/16
17	Double - swivel + becket block	N06231	360	12.7	N16231	354	12.5	175	6 7/8
18	Triple - fixed eye block	N06310	421	14.9	N16310	410	14.5	125	4 15/16
19	Triple - fixed eye + becket block	N06311	444	15.7	N16311	430	15.2	150	5 7/8
20	Triple - reverse shackle block	N06320	440	15.5	N16320	422	14.9		5 1/2
21	Triple - reverse shackle + becket block	N06321	467	16.5	N16321	447	15.8	167	6 9/16
22	Triple - swivel block	N06330	455	16	N16330	440	15.5		5 1/2
23	Triple - swivel + becket block	N06331	480	16.9	N16331	465	16.4	170	6 11/16
24	Single - swivel + cam block	N06510	403	14.2	N16510	390	13.8	145	5 11/16
25	Single - swivel + cam + becket block	N06511	430	15.2	N16511	417	14.7	167	6 9/16
26	Triple - swivel + cam block	N06930 30	672	23.7	N16930	646	22.8	140	5 1/2
27	Triple - swivel + becket + cam block	N06931	681	24	N16931	671	23.7	160	6 5/16

# 70mm Size 7 blocks


The 70mm sheave Size 7 high load cruising block range is engineered for superior strength and performance and offers both plain and ball bearing sheave assemblies. The range features high grade glass fibre nylon reinforced moulded side plates with internal 316 stainless steel frame that is through-bolted and riveted for added strength and durability. This well designed and versatile range is engineered for use on larger cruising and racing yachts and is compatible with our ball bearing mainsheet traveller system. See p8-9 for rigging specifications.




РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
1	Single – double tang	N07090	268	9.5	N17090	265	9.3	145	5 11/16
2	Single – fixed eye	N07110			N17110	255			5 3/8
3	Single – fixed eye + becket	N07111	298	10.5	N17111	300	10.6	168	6 5/8
4	Single – reverse shackle	N07120	313	11	N17120	312	11	168	6 <sup>5</sup> / <sub>8</sub>
5	Single – reverse shackle + becket	N07121	354	12.5	N17121	351	12.4	195	7 11/16
6	Single – swivel	N07130	352		N17130	353			6 1/2
7	Single – swivel + becket	N07131	396	14	N17131	393	13.9	197	7 3/4
8	Single – snap shackle	N07140	359		N17140	356	12.6		6 11/16
9	Single – snap shackle + becket	N07141	401	14.1	N17141	401	14.1	200	7 7/8
10	Single – stand up block + plastic spring	N07170	442	15.6	N17170	447	15.8		6 5/8
11	Single – stand up + becket + plastic spring	N07171	492	17.4	N17171	493	17.4	200	7 7/8
12	Block on a SK78 7mm Dyneema Strop with becket Length inc. strop 480mm	N07191	293	10.3	N17191	296	10.4	145	5 <sup>11</sup> / <sub>16</sub>

## **TECHNICAL DETAILS**

Cheeks - Glass Reinforced Nylon Sheaves - Acetal Straps & Fittings – 316 Stainless Steel Plain Bearing – Brass Ball Bearings – Delrin











BALL BEARING Max rolling load 875kg (1929lbs) Break load 2500kg (5500lbs)



i VIE	W SIZE 7 FIDDLE BLOCKS ON p25	bartonmarine.com				RA bartonmari		ı	
РНОТО NO	DESCRIPTION	PART NO	WEIGHT		PART NO	WEIGHT		LENGTH	
		PLAIN BEARING SHEAVE	G	OZ	BALL BEARING SHEAVE	G	oz	ММ	
13	Double – reverse shackle	N07220	465	16.4	N17220	463	16.3	170	
14	Double – reverse shackle + becket	N07221	506	17.8	N17221	503	17.7	200	

		SHEAVE	Ī		SHEAVE				
13	Double – reverse shackle	N07220	465	16.4	N17220	463	16.3	170	6 11/16
14	Double – reverse shackle + becket	N07221	506	17.8	N17221		17.7	200	7 7/8
15	Double – swivel	N07230	490	17.3	N17230	487	17.2	175	6 7/8
16	Double – swivel + becket	N07231	524	18.5	N17231	521	18.4	205	8 <sup>1</sup> / <sub>16</sub>
17	Triple – reverse shackle	N07320	622	21.9	N17320	618	21.8	170	6 11/16
18	Triple – reverse shackle + becket	N07321		23.5	N17321		23.3	200	7 7/8
19	Triple – swivel	N07330	645	22.8	N17330	635		165	6 1/2
20	Triple – swivel + becket	N07331	684	24.1	N17331	684	24.1	195	7 11/ <sub>16</sub>
21	Triple – swivel + cam	N07930	845	29.8	N17930	847	29.9	163	6 <sup>7</sup> / <sub>16</sub>
22	Triple – swivel + becket + cam	N07931			N17931		31.4	190	7 1/2

# Fiddle Blocks

SIZE 2

Fiddle 30/45mm x 11mm (1 3/16" /1 3/4" x 15/32") SIZE 3

Fiddle 30/45mm x 11mm (1 3/16" /1 3/4" x 15/32")

These blocks are riveted with 316 Stainless Steel pins and reinforced with washers.

Barton Fiddle Blocks are available in five sizes and up to 10 different formats. Block selection is based on rope size and application requirements.

Fiddle Blocks are named after the musical instrument, and have two inline sheaves making them a compact and efficient configuration. The two sheaves are different sizes with the primary sheave being the larger diameter.

The range features high grade glass fibre nylon reinforced moulded side plates with internal 316 stainless steel frame for added strength and durability. This well designed and versatile range is engineered for use in multiple applications including mainsheets and vangs. These pages show the riveted versions.

SIZE 2 PART NO

PLAIN BEARING SHEAVE

N02410

PHOTO NO

FIDDLE BLOCK DESCRIPTION

Fixed eye



WEIGHT

88 3.1

LENGTH

INCH

4 7/16

мм

113

WEIGHT

89 3.1

ΟZ

N12410

2	Fixed eye + becket	N02411	97	3.4	N12411	96	3.4	130	5 1/8
3	Swivel	N02430	96	3.4	N12430	98	3.5	130	5 1/8
4	Swivel + becket	N02431	106	3.7	N12431	106	3.7	145	5 11/16
5	Snap shackle	N02440	133	4.7	N12440	130	4.6	142	5 <sup>9</sup> / <sub>16</sub>
6	Snap shackle + becket	N02441	136	4.8	N12441	139	4.9	162	6 3/8
7	Swivel + cam	n/a							
8	Swivel + becket + cam	N02631	160	5.6	N12631	159	5.6	145	5 11/16
9	Snap shackle + becket + cam	N02641	196	6.9	N12641	195	6.9	162	6 3/8
9		SIZE 3 PART NO	WEI	GHT	PART NO	WEIG	ЭНТ	LENGTH	
Ö	FIDDLE BLOCK								
PHOTO NO	DESCRIPTION	PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE		oz	мм	INCH
1	Fixed eye	BEARING	G 128	OZ 4.5	BEARING	G 135	OZ 4.8	MM 133	5 1/ <sub>4</sub>
		BEARING SHEAVE			BEARING SHEAVE				
0	Fixed eye Fixed eye +	BEARING SHEAVE N03410	128	4.5	BEARING SHEAVE N13410	135	4.8	133	5 1/4
2	Fixed eye Fixed eye + becket	N03410	<b>128</b>	4.5	BEARING SHEAVE N13410 N13411	135	4.8	133 158	5 1/4
1 2 3	Fixed eye Fixed eye + becket Swivel	N03410 N03411 N03430	128 142 144	4.5 5 5.1	N13410 N13411 N13430	135 142 151	4.8 5 5.3	133 158 150	5 1/ <sub>4</sub> 6 1/ <sub>4</sub> 5 7/ <sub>8</sub>
1 2 3 4	Fixed eye + becket  Swivel  Swivel + becket	BEARING SHEAVE N03410 N03411 N03430 N03431	128 142 144 153	4.5 5 5.1 5.4	BEARING SHEAVE N13410 N13411 N13430 N13431	135 142 151 164	4.8 5 5.3 5.8	133 158 150 175	5 1/ <sub>4</sub> 6 1/ <sub>4</sub> 5 7/ <sub>8</sub> 6 7/ <sub>8</sub>
1 2 3 4 5	Fixed eye + becket Swivel + becket Snap shackle Snap shackle +	BEARING SHEAVE N03410 N03411 N03430 N03431 N03440	128 142 144 153 171	4.5 5 5.1 5.4 6	BEARING SHEAVE N13410 N13411 N13430 N13431 N13440	135 142 151 164 177	4.8 5 5.3 5.8 6.2	133 158 150 175 161	5 1/ <sub>4</sub> 6 1/ <sub>4</sub> 5 7/ <sub>8</sub> 6 7/ <sub>8</sub> 6 5/ <sub>16</sub>
1) 2) 3) 4) 5)	Fixed eye Fixed eye + becket  Swivel  Swivel + becket  Snap shackle  Snap shackle + becket	BEARING SHEAVE N03410 N03411 N03430 N03431 N03440 N03441	128 142 144 153 171 182	4.5 5 5.1 5.4 6	BEARING SHEAVE N13410 N13411 N13430 N13431 N13440 N13441	135 142 151 164 177 187	4.8 5 5.3 5.8 6.2 6.6	133 158 150 175 161 185	5 1/ <sub>4</sub> 6 1/ <sub>4</sub> 5 7/ <sub>8</sub> 6 7/ <sub>8</sub> 6 5/ <sub>16</sub> 7 5/ <sub>16</sub>



SIZE 5

SIZE 6

Fiddle 30/45mm x 11mm (1 <sup>3</sup>/<sub>16</sub>" /1 <sup>3</sup>/<sub>4</sub>" x <sup>15</sup>/<sub>32</sub>") Sheave size 64mm x 18mm (2 1/2" x 45/64") (1 3/16" /1 3/4" x 15/32") SIZE 7

Fiddle 44/72mm x 20mm (1 3/4" /2 53/64" x 3/4")

These blocks are through-bolted and riveted for increased loading and performance.

		Bar			bartonm	C	三		
ON O	FIDDLE BLOCK	SIZE 5 PART NO	WEIC	SHT	PART NO	WEIG	нт	LENGTH	
PHOTO NO	DESCRIPTION	PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	OZ	ММ	INCH
1	Fixed eye	N05410	247	8.7	N15410	235	8.3	168	6 5/8
12	Fixed eye + becket	N05411	272	9.6	N15411	254	9	188	7 3/8
13	Reverse shackle	N05420	272	9.6	N15420	254	9	185	7 <sup>5</sup> / <sub>16</sub>
14	Reverse shackle + becket	N05421	293	10.3	N15421	273	9.6	205	8 <sup>1</sup> / <sub>16</sub>
15	Swivel	N05430	290	10.2	N15430	273	9.6	185	7 5/16
16	Swivel + becket	N05431	310	10.9	N15431	293	10.3	205	8 <sup>1</sup> / <sub>16</sub>
17	Snap shackle	N05440	350	12.3	N15440	335	11.8	200	7 7/8
18	Snap shackle + becket	N05441	378	13.3	N15441	360	12.7	220	8 <sup>11/</sup> 16
19	Swivel + becket + cam	N05631	490	17.3	N15631	480	16.9	208	8 3/16
20		N05461	555		N15461				
O <sub>Z</sub>	FIDDLE BLOCK	SIZE 6 PART NO	WEIG	нт	PART NO	WEIG	НТ	LENGTH	
PHOTO NO	DESCRIPTION	PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	oz	мм	INCH
13	Reverse shackle	N06420	347	12.2	N16420	335	11.8	205	8 1/16
14	Reverse shackle + becket	N06421	383	13.5	N16421	370	13.1	235	9 1/4
15	Swivel	N06430	372	13.1	N16430	360	12.7	210	8 1/4
16	Swivel + becket	N06431	402	14.2	N16431	392	13.8	235	9 1/4
17	Snap shackle	N06440	430	15.2	N16440	420	14.8	220	8 11/16
18	Snap shackle + becket	N06441	468	16.5	N16441	450	15.9	250	9 13/16
19	Swivel + becket + cam	N06631	585	20.6	N16631	575	20.3	235	9 1/4
20	Snap shackle + becket + cam	N06641	649		N16641	635		204	9 1/32
9		SIZE 7 PART NO	WEIC	ЭНТ	PART NO	WEIC	ЭНТ	LENGTH	
PHOTO NO	FIDDLE BLOCK DESCRIPTION	PLAIN BEARING SHEAVE	G	oz	BALL BEARING SHEAVE	G	OZ	ММ	INCH
13	Reverse shackle	N07420	412	14.5	N17420	398	14.0	220	8 11/ <sub>16</sub>
14	Reverse shackle + becket	N07421	448	15.8	N17421	435	15.3	250	9 13/16
15	Swivel	N07430	455	16.0	N17430	443	15.6	220	8 11/16
16	Swivel + becket	N07431	488	17.2	N17431	474	16.7	250	9 13/16
7	Snap shackle	N07440	453	16.0	N17440	440	15.5	225	8 7/8
18	Snap shackle + becket	N07441	488	17.2	N17441	474	16.7	254	10
19	Swivel + becket + cam	N07631	668	23.6	N17631	660	23.3	250	9 13/16
20	Snap shackle + becket + cam	N07641	670		N17641	664		257	10 1/8



# **Barton Ball Bearing Ratchet Block**



PHOTO NO	DESCRIPTION	PART NO	SHEA	/E Ø	SHEA' WIDT		MAXI LINE		BREAK	LOAD	SWL		LENG <sup>*</sup>	тн	WEIGI	нт
			мм	INCH	мм	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	G	oz
1	Barton Ratchet block - 55mm hard anodised	90500	55	1 3/16	17	11/16	10	3/8	1200	2640	600	1320	114	4 1/2	135	4.8

#### **BARTON 25MM STANCHION RATCHET BLOCK**

This Barton Stanchion Ratchet block is ideal for removing some of the loading for the crew when furling in the jib. The ratchet allows the sheave to be locked in place in one direction offering a friction brake against the pull of the sail. Quick and simple, it fits onto a standard 25mm (1") guard rail stanchion. Adjustment is easy with the stainless steel clamping ring which allows mounting of the block at any angle.

PHOTO I	DESCRIPTION	PART	LENGT	Н	MAXIM LINE Ø		WIDTH		TUBE S	IZE	SWL	
NO		NO	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
2	Stanchion Ratchet Block	60160	120	4 3/4	10	3/8	55	2 3/16	25	1	350	770







# Classic Wooden Blocks with Torlon Needle Bearings

For sailors, owners and builders who desire traditional values and classic looks combined with performance, Barton introduced its Torlon Needle Roller Blocks.

This 80mm block provides performance, high loading and classic style -




PHOTO NO	DESCRIPTION	PART NO	BEARING	LENG	тн	WEIG	нт	SWL		BREAK	LOAD
				ММ	INCH	G	oz	кG	LBS	кG	LBS
1	80mm Single – fixed eye	50080	Torlon needle roller with Delrin ball side bearings	140	5 1/2	530	18.7	1250	2750	2500	5500
2	Fastener tool	50010	Wood block hand tool	145		130	4.6				-







Sheave size 80mm x 20mm

Max rope diameter 14mm

(3 3/8 x 3/4")

# Classic Wooden Blocks

# **The Victory Collection**



Crafted by sailors for sailors, Barton Victory Blocks are manufactured in the UK from traditional ash wood, with a high gloss marine varnish finish. Victory Blocks are bolted together and can be unfastened for servicing and re-finishing.

The Victory collection of wooden blocks not only look good, but are highly durable and designed to withstand many years of use in harsh marine environments. The sleek wooden plates conceal the modern technical working of Barton's proven high performance engineering, with Delrin ball bearings, gun metal coloured sheave and solid brass fittings.

#### **SINGLE FIXED EYE**

РНОТО	PART	LENGTH	l	SHEAVE	(Ø)	MAX RO	PE	BREAK L	.OAD
NO	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
1	50030	70	2 3/4	30	1 3/16	8	5/16	700	1543
1	50045	91	3 %16						1543
1	50060	120	4 3/4	64	2 1/2	12	7/ <sub>16</sub>	1400	3086

#### **DOUBLE WITH SWIVEL SHACKLE**

РНОТО	PART	LENGTH	ı	SHEAVE	(Ø)	MAX RO	PE	BREAK L	.OAD
NO	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
7	52330	83	3 1/4	30	1 <sup>1</sup> / <sub>5</sub>	8	5/16	700	1543
7	52345	110	4 5/16		1 3/4				1543
7	52360	145	5 3/4	64	2 1/2	12	7/ <sub>16</sub>	1400	3086

#### SINGLE FIXED EYE WITH BECKET

РНОТО	PART	LENGTH	ı	SHEAVE	(Ø)	MAX RC	PE	BREAK L	.OAD
NO	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
2	50230	87	3 7/16	30	1 3/16	8.0	5/16	700	1543
2	50245	112	4 7/16			10.0		700	1543
2	50260	146	5 3/4	64	2 1/2	12.0	7/ <sub>16</sub>	1400	3086

#### **DOUBLE WITH SWIVEL SHACKLE & BECKET**

РНОТО	PART	LENGTH		SHEAVE	(Ø)	MAX RO	PE	BREAK L	.OAD
NO	NO	MM INCH		ММ	INCH	ММ	INCH	KG LBS	
8	52430	110	4 5/16	30	1 3/16	8	5/16	700	1543
8	52445	128							1543
8	52460	170	6 11/16	64	2 1/2	12	7/16	1400	3086

#### SINGLE WITH SWIVEL SHACKLE

РНОТО	PART	LENGTH	ł	SHEAVE	(Ø)	MAX RC	PE	BREAK L	.OAD
ID	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
3	50330	83	3 1/4	30	1 3/16	8.0	5/16	700	1543
3	50345	110	4 5/16		1 3/4	10.0	3/8	700	1543
3	50360	142	5 5/8	64	2 1/2	12.0	7/16	1400	3086

#### **TRIPLE FIXED EYE**

РНОТО	PART	LENGTH	I	SHEAVE	(Ø)	MAX RO	PE	BREAK L	.OAD
NO	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
9	53030	70	2 3/4	30	1 3/16	8	5/16	700	1543
9	53045	91	3 %16		1 3/4				1543
9	53060	125	4 15/16	64	2 1/2	12	7/16	1400	3086

#### SINGLE WITH SWIVEL SHACKLE & BECKET

РНОТО	PART	LENGTH	ı	SHEAVE	(Ø)	MAX RC	PE	BREAK L	OAD
NO	NO	мм	INCH	MM INCH		ММ	INCH	KG	LBS
4	50430	101	4	30	1 3/16	8.0	5/16	700	1543
4	50445	128	5 1/16		1 3/4	10.0	3/8		1543
4	50460	170	6 11/16	64	2 1/2	12.0	7/16	1400	3086

#### **TRIPLE FIXED EYE & BECKET**

РНОТО	PART	LENGTH	1	SHEAVE	(Ø)	MAX RC	PE	BREAK LOAD		
NO	NO 53230	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS	
10	53230	87	3 7/16	30	1 3/16	8	5/16	700	1543	
10	53245	112	4 7/16		1 3/4		3/8	700	1543	
10	53260	145	5 7/8	64	2 1/2	12	7/16	1400	3086	

#### **DOUBLE FIXED EYE**

РНОТО	PART	LENGTH	ı	SHEAVE	(Ø)	MAX RO	PE	BREAK L	.OAD
NO	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
5	52030	70	2 3/4	30	1 3/16	8	5/16	700	1543
5	52045	91	3 9/16						1543
5	52060	125	4 15/16	64	2 1/2	12	7/16	1400	3086

# TRIPLE WITH SWIVEL SHACKLE

РНОТО	PART	LENGTH	ı	SHEAVE	(Ø)	MAX RC	PE	BREAK L	.OAD
NO	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
11	53330	88	3 7/16	30	1 1/5	8	5/16	700	1543
11	53345	110	4 5/16	45	1 3/4	10	3/8	700	1543
11	53360	145	5 3/4	64	2 1/2	12	7/16	1400	3086

# **DOUBLE FIXED EYE & BECKET**

РНОТО	PART	LENGTH	I	SHEAVE	(Ø)	MAX RC	PE	BREAK L	.OAD
NO	NO 52220	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
6	52230	87	3 7/16	30	1 1/5	8	5/16	700	1543
6	52245	113	4 7/16					700	1543
6	52260	150	5 3/4	64	2 1/2	12	7/16	1400	3086

## TRIPLE WITH SWIVEL SHACKLE & BECKET

PHO	ото	PART	LENGTH	ł	SHEAVE	(Ø)	MAX RO	PE	BREAK L	.OAD
NO	)	NO	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
•	12	53430	106	4 3/16	30	1 1/5	8	5/16	700	1543
6	12	53445	128	5 1/16		1 3/4		3/8		1543
•	12	53460	170	6 11/16	64	2 1/2	12	7/16	1400	3086



Barton Marine has expanded its 'Victory' range of classic, high performance wooden blocks. Combining high performance engineering and classic design, these blocks are for mariners who appreciate elegance and want technical excellence.

This classic range has been named in honour of the flagship of the British Royal Navy – the *HMS Victory*.

- High Performance sheaves
- Manufactured from ash wood
- High Gloss marine varnish finish
- Bolted together for servicing or refinishing
  - Range includes beckets and swivels; single, double and triple sheaves





In 1948, Ron Barton, a keen sailor and the founder of RSJ Barton Ltd, decided to dedicate his engineering and manufacturing experience to the production of leisure marine equipment. Barton Marine Equipment Ltd was born and was the first manufacturer to use Tufnol for deck gear. This delivers leisure marine blocks, cleats and other assemblies that stand up to the rigorous performance and environmental standards required on sailing yachts – and is non-conductive for industrial users. Tufnol equipment incorporated with stainless steel and brass components, were lighter and stronger than ever achieved in the past.

Barton produced the Tufnol range successfully through the 1970s, and then Ron changed to the new technology of plastic injection moulded equipment which sped up production and took over the market.





Now 50 years later Barton is returning to its retro roots to support the requirements of classic heritage vessels worldwide along with commercial and industrial users. The TUPHblox range is revived and Barton is proud to be producing a range of Tufnol marine equipment that is constructed with 316 marine grade stainless steel components and brass bearings. The result is a durable line of blocks and gear that provide high rolling loads, greater strength and durability, with UV and weather resistance to last for generations.



# THE MATERIALS

#### **TUFNOL - LAMINATED FABRIC AND RESIN MATERIALS**

Tufnol is a registered trade mark and is used throughout the TUPHblox range.

Tufnol is a synthetic resin bonded fabric, made using impregnated layers of woven cloth with a bespoke phenolic resin system. Many layers are stacked and heated under high pressure to produce laminated sheets to the required thickness.

#### 316 MARINE GRADE STAINLESS STEEL

Barton Marine knows the importance of quality assurance and only use 316 stainless steel for marine production. This means the blocks are strong, durable and aesthetically pleasing and will perform well in marine environments.

## **BRASS BEARINGS**

The brass bearing between the Tufnol sheaves and stainless steel pins ensure strength and high rolling loads that will last for the working life of the equipment.



# SINGLE BLOCK WITH EYE

PART NO WITHOUT	PART NO WITH	ROPE D	IA.	SHEAVE	E DIA.	BREAK LOAD	ING	WWL WORK LOAD		LENGT WITHO BECKE	DUT	LENGT WITH E	H BECKET
BEECKET	BECKET	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH
T01180	T01181		3/8	30			1543		771	70			
T02180	T02181	12	7/16	35	1 3/8	740	1630	370	815	80	3 3/8	98	3 7/8
T03180	T03181	13	1/2	45			1694		848	102			4 15/16
T04180	T04181	14	9/16	58	2 5/16	1260	2770	630	1385	120	4 3/4	148	5 13/16
T06180	T06181	16	5/8	64	2 1/2	1500	3300	750	1650	128	5 <sup>1</sup> / <sub>16</sub>	155	6 1/8



# SINGLE BLOCK WITH BOW

PART NO WITHOUT	PART NO WITH	ROPE D	IA.	SHEAVE	EDIA.	BREAK LOAD	ING	WWL WORK LOAD		LENG WITH BECK	OUT	LENGT WITH E	H BECKET
BEECKET	BECKET	ММ	INCH	мм	INCH	KG	LBS	KG	LBS	ММ	INCH	мм	INCH
T00110	T00111	8	5/16	20	13/16	550	1210	275	606	50	2	65	2 1/2
T01110	T01111						1543	350	771				
T02110	T02111	12	7/16	35	1 3/8	740	1630	370	815	83	3 1/4	101	3 <sup>15</sup> / <sub>16</sub>
T03110	T03111	13	1/2	45	1 3/4	770	1694	385	848	93	3 5/8	116	
T04110	T04111	14	9/16	58	2 5/16	1260	2770	630	1385	115	4 1/2	144	5 5/8
T06110	T06111						3300	750	1650	122			



# SINGLE BLOCK WITH SWIVEL

PART NO WITHOUT BEECKET	PART NO WITH	ROPE D	IA.	SHEAVE	E DIA.	BREAK LOAD	ING	WWL WORK LOAD		LENG WITH BECK	OUT	LENGT BECKE	H WITH T
	BECKET	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH
T00130	T00131	8	5/16	20	13/16	550	1210	275	606	65	2 1/2	80	3 1/8
T01130	T01131	10	3/8	30	1 3/16		1543		771			103	
T02130	T02131	12	7/16	35	1 3/8	740	1630	370	815	101	4	120	4 3/4
T03130	T03131		1/2										
T04130	T04131	14	9/16	58	2 5/16	1260	2770	630	1385	140	5 5/8	168	6 5/8
T06130	T06131	16	5/8	64	2 1/2	1500	3300	750	1650	144	5 3/4	170	6 3/4



# **DOUBLE BLOCK WITH BOW**

PART NO PART NO WITHOUT WITH BECKET	WITH	ROPE DIA.		SHEAVE DIA.		BREAKING LOAD		WWL WORKING LOAD LIMIT		LENGTH WITHOUT BECKET		LENGTH WITH BECKET	
	ММ	INCH	мм	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH	
T01210	T01211	10	3/8	30	1 <sup>3</sup> / <sub>16</sub>		1543		771		2 3/4		
T02210	T02211	12	7/16	35	1 3/8	740	1630	370	815	83	3 1/4	100	3 15/16
T03210	T03211	13	1/2	45	1 3/4	770	1694	385	848		3 5/8	116	4 1/2
T04210	T04211	14	9/16	58	2 5/16	1260	2770	630	1385	115	4 1/2	142	5 5/8
T06210	T06211	16	5/8	64	2 1/2	1500	3300		1650	122	4 3/4		5 7/8



# **DOUBLE BLOCK WITH SWIVEL**

PART NO PART NO WITHOUT BEECKET BECKET	WITH	ROPE DIA.		SHEAVE DIA.		BREAKING LOAD		WWL WORKING LOAD LIMIT		LENGTH WITHOUT BECKET		LENGTH WITH BECKET	
	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH	
T01230	T01231	10	3/8	30	1 3/16	700	1543	350	771	84	3 5/16	103	4 1/16
T02230	T02231	12	7/16	35	1 3/8	740	1630	370	815	101	4	120	4 3/4
T03230	T03231					770							5 1/4
T04230	T04231	14	9/16	58	2 5/16	1260	2770	630	1385	140	5 5/8	168	6 5/8
T06230	T06231					1500	3300		1650				6 3/4

# **TUPHblox**



## TRIPLE BLOCK WITH BOW

WITHOUT WIT	PART NO WITH	ROPE DIA		SHEAVE DIA		BREAKING LOAD		WWL WORKING LOAD LIMIT		LENGTH WITHOUT BECKET		LENGTH WITH BECKET	
	BECKET	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	мм	INCH	ММ	INCH
T01310	T01311					700	1543	350	771		2 3/4	87	3 1/2
T02310	T02311	12	7/16	35	1 3/8	740	1630	370	815	83	3 1/4	100	3 15/16
T03310	T03311								848		3 5/8		4 1/2
T04310	T04311	14	9/16	58	2 5/16	1260	2770	630	1385	115	4 1/2	142	5 5/8
T06310	T06311	16	5/8	64	2 1/2	1500	3300	750	1650	122	4 3/4	148	5 7/8



# TRIPLE BLOCK WITH SWIVEL

PART NO WITHOUT BEECKET	PART NO WITH	ROPE DIA Ø		SHEAVE DIA Ø		BREAKING LOAD		WWL WORKING LOAD LIMIT		LENGTH WITHOUT BECKET		LENGTH WITH BECKET	
	BECKET	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH
T01330	T01331	10	3/8				1543						
T02330	T02331	12	7/16	35	1 3/8	740	1630	370	815	101	4	120	4 3/4
T03330	T03331	13				770							
T04330	T04331	14	9/16	58	2 5/16	1260	2770	630	1385	140	5 5/8	168	6 5/8
T06330	T06331	16	5/8			1500	3300	750					



# FIDDLE BLOCK WITH BOW

PART NO WITHOUT BEECKET	PART NO WITH BECKET	ROPE DIA Ø		SHEAVE DIA Ø		BREAKING LOAD		WWL WORKING LOAD LIMIT		LENGTH WITHOUT BECKET		LENGTH WITH BECKET	
		ММ	INCH	мм	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH
T01410	T01411	10	3/8	20 & 40	13/ <sub>16</sub> & 1 9/ <sub>16</sub>	700	1543	350	771	117	4 5/8	140	5 1/2
T02410	T02411	12	<sup>7/</sup> 16	25 & 50	1 & 1 <sup>15</sup> / <sub>16</sub>			370	815	145	5 11/16		
T03410	T03411	13	1/2	30 & 58	1 3/16 & 2 5/16	770	1694	385	848	162	6 3/8	185	7 5/16



## FIDDLE BLOCK WITH SWIVEL

V	ART NO VITHOUT EECKET	PART NO WITH BECKET	ROPE DIA Ø		SHEAVE [	BREAKING LOAD		WWL WORKING LOAD LIMIT		LENGTH WITHOUT BECKET		LENGTH WITH BECKET		
			мм	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH
Т	01430	T01431	10	3/8	20 & 40	13/16 & 1 9/16	700	1543	350	771	127	5	152	6
Т	02430	T02431	12		25 & 50			1630	370				180	7 1/16
Т	03430	T03431	13	1/2	30 & 58	1 3/16 & 2 5/16	770	1694	385	848	170	6 11/16	188	7 3/8



## FIDDLE BLOCK WITH BOW & CAM

PART NO WITHOUT BEECKET	PART NO WITH BECKET	ROPE DIA Ø		SHEAVE	BREAKING LOAD		WWL WORKING LOAD LIMIT		LENGTH WITHOUT BECKET		LENGTH WITH BECKET		
		ММ	INCH	мм	INCH	KG	LBS	KG	LBS	ММ	INCH	ММ	INCH
T01610	T01611	10	3/8	20 & 40	13/16 & 1 9/16	700	1543	350	771	117	4 5/8	140	5 1/2
T02610	T02611		7/16	25 & 50		740	1630			145			6 <sup>7</sup> / <sub>16</sub>
T03610	T03611	13	1/2	30 & 58	1 3/16 & 2 5/16	770	1694	385	848	162	6 3/8	185	7 5/16



#### FIDDLE BLOCK WITH SWIVEL & CAM

PART NO WITHOUT BEECKET	PART NO WITH BECKET	ROPE D	DIA Ø	SHEAVE D	OIA Ø	BREA LOAI	KING )	WWL WORI LOAD LIMIT	) [	LENG WITH BECK	TUC	LENG WITH BECKI	
		мм	INCH	MM INCH		KG	LBS	KG	LBS	ММ	INCH	мм	INCH
T01630	T01631	10	3/8	20 & 40	13/16 & 1 9/16	700	1543	350	771	127	5	152	6
T02630	T02631	12	7/16	25 & 50	1 & 1 <sup>15</sup> / <sub>16</sub>	740	1630	370	815	155	6 1/8	180	7 1/16
T03630	T03631	13	1/2	30 & 58 1 <sup>3</sup> / <sub>16</sub> & 2 <sup>5</sup> / <sub>16</sub>		770	1694	385	848	170	6 11/16	188	7 3/8



#### **CAM CLEAT WITHOUT FAIRLEAD**

DADT NO	ROPE DIA	ø	HOLDING	POWER	LENGTH (	OVERALL	WIDTH C	OVERALL
PART NO	мм	INCH	KG	LBS	ММ	INCH	ММ	INCH
T70200	6-12	1/4-1/2	230	507	68	2 11/16	27	1 1/16
T70300			260	573				


All cams are designed for countersunk M5/#10 screw



#### **CAMS WITH FAIRLEAD**

PART NO	ROPE DIA	.ø	HOLDING	G POWER	LENGTH (	OVERALL	WIDTH C	OVERALL
PARTINO	мм	INCH	KG	LBS	ММ	INCH	ММ	INCH
T70201	6-12	1/4-1/2	230	507	68	2 11/16	32	1 1/4
T70301	10-14			573	81		38	

All cams are designed for countersunk M5/#10 screw



#### **TUPHBLOX SPARE SHEAVES FOR ROPE**

Spare sheaves are supplied in packs of five without bearings. Tufnol is bearing material on its own and can be used without a brass insert.



PART NO	DESCRIPTION	DIA Ø		THICKNES	SS 'T'	BORE Ø	
TUPHBLOX SH	IEAVES	ММ	INCH	ММ	INCH	ММ	INCH
T64030	TUPHblox sheave for rope	30	1 3/16	11	7/16	6	1/4
T64040	TUPHblox sheave for rope	40	1 9/16			6	1/4
T64050	TUPHblox sheave for rope	50	1 15/16	13	1/2	8	5/16
T64060	TUPHblox sheave for rope	60				8	
T64080	TUPHblox sheave for rope	80	3 1/8	16	5/8	10	3/8
T64100	TUPHblox sheave for rope	100	3 15/16			10	3/8

#### **TUPHBLOX SPARE SHEAVES FOR WIRE**

Spare sheaves are supplied in packs of five without bearings. Tufnol is bearing material on its own and can be used without a brass insert.



PART NO	DESCRIPTION	DIA Ø		THICKNE	SS 'T'	BORE Ø	
TUPHBLOX SHI	EAVES	ММ	INCH	ММ	INCH	ММ	INCH
T65030	TUPHblox sheave for wire	30	1 3/16	9	3/8	6	1/4
T65040	TUPHblox sheave for wire	40	1 9/16			6	
T65050	TUPHblox sheave for wire	50	1 15/16	11	7/16	8	5/16
T65060	TUPHblox sheave for wire	60	2 3/8			8	
T65080	TUPHblox sheave for wire	80	3 1/8	13	1/2	10	3/8
T65100	TUPHblox sheave for wire	100	3 15/16	15		10	

### **TUPHblox**



#### **CHEEK BLOCKS**

PART NO STAINLESS	PART NO TUFNOL	ROPE DIA (		SHEA DIA @		BREAK LOAD	ING	WWL WO		LENGT OVERA		WIDTH	OVERALL
BASE	BASE	ММ	INCH	мм	INCH	KG	LBS	KG	LBS	мм	INCH	ММ	INCH
-	T01160	10	3/8	30	1 3/16	700	1543	350	771	66	2 5/8	40	1 9/16
T02160S	T02160		7/16		1 3/8		1630						
T03160S	T03160	13	8/16	45	1 3/4	770	1694	385	848	92	3 5/8	53	2 1/16
T04160S	T04160	14	9/16	58	2 5/16	1260	2770	630	1385	107	4 3/16	68	2 11/16



#### WIRE BLOCKS WITH CLEVIS PIN

PART NO	WIRE DIA	Ø	SHEAVE [	SHEAVE DIA Ø		G LOAD	WWL WO		LENGTH	
WITHOUT BECKET	мм	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH
T91304	4	3/16	35	1 3/8	1140	2508	570	1254	90	3 9/16
T91305	5	3/16	45	1 3/4	1225	2695		1347.5	98	
T91306	6	1/4	50	1 15/16	2050	4510	1025	2255	110	4 5/16
T91307	7	1/4	60	2 1/4		4510				



#### **WIRE BLOCKS WITH EYE**

PART NO WITHOUT	WIRE DIA	.ø	SHEAVE [	DIA Ø	BREAKIN	G LOAD	WWL WO		LENGTH	
BECKET	ММ	INCH	MM INCH		KG	LBS	KG	LBS	мм	INCH
T92304	4	3/16	60	2 1/4	1140	2508	570	1254	85	3 3/8
T92305	5	3/16	75		1225	2695	613		95	
T92306	6	1/4	90	3 9/16	2050	4510	1025	2255	105	4 1/8
T92308			100			4510		2255	125	

#### **INTERNALLY BOUND TUPHBLOX**


PART NO	DESCRIPTION	SHEA	VE DIA	BREAKIN	G LOAD	WWL WO	
		ММ	INCH	KG	LBS	KG	LBS
T46110	TuphBlox Single Fixed Bow Internally Bound 16mm Rope Pulley Block	90	3 9/16	4100	9020	2050	4510
T47110	TuphBlox Single Fixed Bow Internally Bound 20mm Rope Pulley Block	100	3 <sup>15/</sup> 16	4700	10340	2350	5170
T47111	TuphBlox Single Fixed Bow & Becket, Internally Bound 20mm Rope Pulley Block	100	3 15/16	4700	10340	2350	5170
T47230	TuphBlox Double With Fixed Bow Internally Bound 20mm Rope Pulley Block	100		4700		2350	5170
T47231	TuphBlox Double With Fixed Bow & Becket, Internally Bound 20mm Rope Pulley Block	100	3 15/16	4700	10340	2350	5170

#### LARGE COMMERCIAL TUPHBLOX

As part of Barton's commitment to the TUPHblox range and Tufnol products, our strategy is to develop larger industrial blocks with enhanced performance values and to respond to special project requests. Please contact the sales team at sales@bartonmarine.com with your specifications and requirements.

Industrial TUPHblox are engineered with stainless steel bindings. Custom blocks can be manufactured with aluminium or galvanised bindings as required.





### Wire Rope Blocks

#### **BACKSTAY TENSIONER SYSTEM (1)**

#### **BACKSTAY TENSIONER BLOCKS (2 & 3)**

A block and tackle system designed for use on split or twin backstays. Features stainless steel double block with brass sheaves, together with tensioning blocks from our series 2 range (see page 8 for setup options).

Featuring laser-cut stainless steel side plates with precision turned brass sheaves. For use on twin or split backstays - for backstay wire of up to  $10mm \emptyset$  (see page 8 for setup options).

PHOTO NO	DESCRIPTION	PART NO	SHEA\ DIA Ø			ROPE	DIA Ø	WIRE I	DIA Ø	BREAK LOAD		SWL		WEIGI	НT	
BACKSTAY	BACKSTAY TENSIONER		ММ	INCH	ММ	INCH	ММ	INCH	мм	INCH	KG	LBS	KG	LBS	G	oz
1	Backstay tensioner system	N02740	45	1 3/4	8	5/16	5	3/16	5	3/16	1300	2866	650	1433	163	5.75
2	Backstay tensioner block	91020	35	1 3/8			-	-	5				-			9.77
3	Backstay tensioner block	91040	50	2	15	9/16	-	-	10	3/8	-	-	-	-	600	21.2









#### **BRASS SHEAVE BLOCKS**

A simple lead block with turned brass sheave and stainless steel fixed eye strap.













91300



PHOTO NO	DESCRIPTION	PART NO	SHEA\ DIA	/E Ø		SHEAVE WIDTH		ROPE Ø DIA		IA WIRE Ø DIA		BREAK LOAD			WEIGH	нт
BRASS SH	BRASS SHEAVE BLOCKS		мм	INCH	мм	INCH	мм	INCH	мм	INCH	KG	LBS	KG	LBS	G	oz
4	Single - fixed eye	91200	35	1 <sup>3</sup> / <sub>8</sub>	8	5/16	4	3/16	4	3/16	400	882	200	441	65	2.3
5	Single - fixed eye	91300	45	1 3/4	8	<sup>5</sup> /16	5	3/16		3/16			375	827	107	3.8

#### **HIGH LOAD WIRE ROPE BLOCKS**

Available in fixed eye or swivel head. Cheeks are manufactured from 316 stainless steel and sheaves are precision turned from solid brass bar, running on a stainless steel centre bush.

















91303








PHOTO NO	DESCRIPTION	PART NO	SHEAV DIA			SHEAVE WIDTH		Ø DIA	WIRE Ø DIA		BREAK	LOAD	SWL		WEIGI	нт
HIGH LOAD WIRE ROPE BLOCKS			мм	INCH	мм	INCH	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	G	oz
6	Fixed eye	91301	45	1 3/4	8	5/16	5	3/16	5	3/16	1300	2866	650	1433	163	5.75
7	Swivel eye	91302		1 3/4		5/16	5	3/16			1300	2866	650	1433	212	7.47
8	Fixed eye with Shackle	91303	45	1 3/4	8	5/16	5	3/16	5	3/16	1300	2866	650	1433	205	7.2

#### **UPRIGHT BLOCKS**

With heavy-duty 316 stainless steel side plates. Sheaves are precision turned from solid aluminium bar, silver anodised and run on nylon bearings to reduce friction under load

#### **UPRIGHT BLOCK DIMENSIONS**

**91400** Base 38 x 45mm Fastenings 5mm

**91500** Base 51 x 55mm Fastenings 6mm





PHOTO NO			SHEAV DIA	Æ Ø	Ø SHEAVE RI		ROPE Ø DIA		WIRE Ø DIA		BREAK LOAD		SWL		WEIGHT	
UPRIGHT BLOCKS			ММ	INCH	мм	INCH	ММ	INCH	мм	INCH	KG	LBS	KG	LBS	G	OZ
9	Single - fixed eye	91400	38	1 1/2	12	1/2	8	5/16	4	3/16	-	-	-	-	92	3.24
10	Single - fixed eye	91500			15	9/16	12		5	3/16			-		160	5.64

#### **ALUMINIUM HIGH LOAD BLOCKS**

A range of high strength blocks designed for use with wire ropes and exceptionally rugged applications. Cheeks are manufactured from marine grade aluminium, grey anodised for high UV-resistance and durability. Sheaves are precision turned from solid aluminium bar, silver anodised and running on nylon bearings to reduce friction under load. Reinforcing plates, rivets, shackles and straps are all from 316 stainless steel.





91600







91700



PHOTO NO			SHEAVE Ø SHEAVE DIA RC		ROPE Ø DIA WIRE		WIRE	WIRE Ø DIA BR		BREAK LOAD			WEIGHT			
ALUMINIUM BLOCKS			ММ	INCH	мм	INCH	мм	INCH	мм	INCH	KG	LBS	KG	LBS	G	OZ
11	Single - fixed eye	91600	51	2	15	9/16	12	1/2	4	3/16	1750	3858	875	1929	155	5.47
12	Single - fixed eye	91700	63	2 1/2	18				5	3/16	3000	6614	1500	3307	248	8.75

### CHEEK BLOCK DIMENSIONS

**91650** Base 103 x 53mm Fastenings 5mm

**91750** Base 120 x 65mm Fastenings 6mm

13	$\odot$	91650	6
			0.0
			000





PHOTO NO	DESCRIPTION	PART NO SHEAVE Ø SHEAVE WIDTH RO					ROPE	ROPE Ø WIRE Ø				LOAD	SWL		WEIGH	нт
CHEEK BL	.OCKS		мм	INCH	мм	INCH	мм	INCH	ММ	INCH	KG	LBS	KG	LBS	G	OZ
13	Cheek	91650	51	2	15	9/16	12	1/2	4	3/16	-	-	-	-	141	4.97
<b>(10)</b>	Cl. I	04750	/2	2.1/		11./									207	0.0



## Wire blocks also available in the TUPHblox range

see page 32

### **High Load & Foot Blocks**

#### **HIGH LOAD BLOCKS**

Manufactured from marine grade aluminium and grey anodised for high UV stability and durability. Sheaves are precision turned from solid 'Ertalyte' bar with a profile that is kind to modern ropes.

- Running on a large diameter centre bearing for easy running under high loads.
- Fitted with a stainless steel bow shackle to allow for snag-free operation.
- Available in three sizes, these blocks are compatible with the toggle connections on our ball bearing mainsheet travellers (see p48).
- Bolt-together construction adds to good looks and enables easy dismantling for servicing.




PHOTO NO	DESCRIPTION	PART NO	SHEAN	/E Ø DIA	SHEAV WIDTH		ROPE	Ø DIA	BREAK	LOAD	SWL	SWL		SWL		н	WEIGH	нт
HIGH LOA	AD BLOCKS		мм	INCH	мм	INCH	мм	INCH	KG	LBS	KG	LBS	мм	INCH	G	oz		
1	50mm High load block	82100	50	2	15	9/16	12	7/16	1000	2205	500	1102	116	4 9/16	146	5.15		
2	65mm High load block	82200		2 9/16		11/16			1600	3528	800	1764	142	5 9/16	267	9.42		
3	85mm High load block	82300	85	3 3/8	21	13/16	18	11/16	3000	6614	1500	3307	185	7 1/4	525	18.5		

#### **FOOT BLOCKS**

Featuring the same side plate and sheave construction as the high load blocks detailed above

- Hollow stainless steel rivets allow for through-bolt fastening, giving added strength.
- Through-bolt mounting means these blocks can easily be stacked to achieve double block capabilities. Note: stacking blocks will reduce working loads.
- Fastenings of the minimum diameter suggested should be used to gain full load capability (see table for fastening size specifications).
- Ensure that suitable mounting pads are used under deck.



Foot blocks have a three bolt fixing and can be stacked to achieve doubles.

#### **MAX HOLDING POWER OF CAMS:**

50mm - 250kg 65mm - 300kg











PHOTO NO	DESCRIPTION	PART NO	SHEA	/E Ø	SHEAV WIDTH		ROPE	Ø	BREAK	LOAD	SWL		LENGT	Ή	FASTENINGS	WEIGI	НТ
FOOT BLC	OCKS		ММ	INCH	мм	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	мм	G	oz
4	Foot block – 50mm	82995	50	2	15	9/16	12	7/16	1000	2205	500	1102	79	3 1/8	3 x M6	114	4.0
5	Foot block – 65mm	82996	65	2 9/16					1600	3528	800	1764	100	3 15/16	2 x M6 / 1 x M8	211	7.4
6	Foot block – 85mm	82997	85	3 3/8	21	13/16	18	11/16	3000	6614	1500	3307	132	5 <sup>3</sup> / <sub>16</sub>	2 x M8 / 1 x M10	420	14.8
FOOT BLC	OCKS WITH CAMS																
7	Foot block – 50mm	82998	50	2	15	9/16	12	7/16	1000	2205	500	1102	84	3 <sup>5</sup> / <sub>16</sub>	3 x M6	130	4.59
8	Foot block – 65mm	82999		2 9/16		11/ <sub>16</sub>	16		1600	3528	800	1764	105	4 1/8	2 x M6 / 1 x M8	230	8.11

### **Snatch Blocks**


Our popular range of snatch blocks is offered in two sizes with a choice of a D shackle or snap shackle. All feature rugged construction with an easy open/close action.



PHOTO NO	DESCRIPTION	PART NO	SHEA	VE Ø	SHEAVE WIDTH		ROPE	Ø	BREAK	LOAD	SWL		LENG	тн	WEIGI	нт
			ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	ММ	INCH	G	oz
1	Small snatch block + S/S snap	90301	35	1 3/8	17	11/16	12	1/2	800	1760	400	880	110	4 5/26	170	6.0
2	Snatch block + S/S snap	90401		1 7/8	20	13/16		5/16	1100	2420		1210		5 7/8	378	13.3
3	Snatch block + S/S 'D' shackle	90402	48	1 7/8	20	13/16	16	5/16	1300	2860	650	1430	144	5 11/16	316	11.1

#### **SKYLOCK BLOCKS**

The Barton Marine SkyLock Blocks feature 316 stainless steel side plates, glass reinforced nylon cover plates and internal self-locking aluminium cam to lift and lock loads securely. The clever design and construction of the locking cams means the control line will never allow loads to drop even when accidentally released. Designed for use in conjunction with 3:1 or 4:1 purchase systems.







SKYLOCK 40 PART NO NO	
SWL:	400kg (880 lbs)
BREAK LOAD:	800kg (1760lbs)
LINE SIZE:	5mm ( <sup>3</sup> / <sub>16</sub> ")
LENGTH:	110mm (4 <sup>5</sup> / <sub>16</sub> ")
HEIGHT:	28mm (1 1/ <sub>8</sub> ")
WIDTH:	90mm (3 <sup>9</sup> / <sub>16</sub> ")
WEIGHT:	181g (0.4 lbs)



BARTON S	SKYLOCK 800 N09421
SWL:	800kg (1760lbs)
BREAK LOA	<b>AD:</b> 1600kg (3500lb)
LINE SIZE:	8-12mm ( <sup>5</sup> / <sub>16</sub> - <sup>7</sup> / <sub>16</sub> ")
LENGTH:	152 mm (5 <sup>49</sup> / <sub>50</sub> ")
HEIGHT:	38 mm (1 1/ <sub>2</sub> ")
WIDTH:	110 mm (4 <sup>1</sup> / <sub>3</sub> ")
WEIGHT:	475g (1.05lbs)

### **Low Friction Rings**

#### **HIGH LOAD EYES**

Available in six sizes. Manufactured in marine grade aluminium with a hard anodised finish.

These lightweight high load eyes are suitable for a variety of uses on board, from lazy jacks, barber haulers, mast base tidies to stanchion lead eyes. The smallest size can be attached using a 3mm line with a bullseye diameter of 6mm. The largest size can be attached using a 16mm line with a bullseye diameter of 28mm.



Ergonomically designed to maximise the strength and efficiency of the eye. With HV500 hard anodising and the profile of the curved surfaces, these rings have been developed to keep friction to a minimum. The products in this range have amazing strength to weight ratios, making them ideal for use as kickers, tweakers, Genoa barber haulers, or use anywhere else where weight saving and strength is important.

#### WEAR RESISTANCE

The hard anodising HV500 has amazing low friction properties. After over 300 hours on an abrasion test machine no visual signs of wear on the anodised coating could be found.




#### STANCHION HIGH LOAD BULLSEYE

This new design features our super smooth hard anodised finish 60452 Low Friction Rings mounted within a metal retaining rod covered in a Dyneema effect durable strap, through bolted onto a fully enclosed backing plate for a clean finish. Lightweight, easy to fix in place and provides excellent line support. Will fit stanchion diameters up to 32mm with an overall effect that is visually stunning.


High load eye compared to a standard plain bearing block on average across the range:

- Friction increased by only 15%
- Strength increased by 272%
- Weight reduced by 51%
- Data based on using 4mm D12 SK75 Dyneema core.

PHOTO NO	DESCRIPTION	PART NO	EXTER DIA Ø		INTER ROPE		BORE	DIA Ø	LOOP	LENGTH	H SWL		WEIGHT	
HIGH LOA	AD LOW FRICTION EYE		мм	INCH	ММ	INCH	мм	INCH	мм	INCH	кG	LBS	G	oz
1	High load low friction eye - 12mm	60449	12	7/16	3	1/8	6	1/4	-	-	300	662	0.8	0.03
2	High load low friction eye - 18mm	60450	18	11/ <sub>16</sub>	4	1/8	9	3/8	-	-	550	1213	3	0.1
3	High load low friction eye - 26mm	60451	26	1	6	1/4	12	7/ <sub>16</sub>	-	-	800	1764	5	0.18
4	High load low friction eye - 38mm	60452		1 1/2		3/8	16	5/8	-		1800	3968	22	0.8
5	High load low friction eye - 52mm	60453	52	2 1/16	12	7/16	22	7/8	-	-	3300	7275	52	1.83
6	High load low friction eye - 65mm	60454	65	2 9/16		5/8	28	1 1/8	-	-	4500	9921	97	3.42
STANCHIO	TANCHION BULLSEYE WITH HIGH LOAD EYE													
7	60150 Stanchion High Load Bullseye – fit	ted with a 16mr	n (60452	l) low frictio	n ring. F	its 25mm-3	2mm sta	anchions/tu	be (1"-1	1/4")			98	3.46
HIGH LOA	AD LOW FRICTION EYE WITH DYNEEMA L	ООР												
8	High load low friction eye with Dyneema loop – 12mm	60460	26	1	6	1/4	12	7/16	100	3 15/16	750	1653	11	0.39
9	High load low friction eye with Dyneema loop – 16mm	60463				3/8		5/8	180		1500	3300		1.6
10	High load low friction eye with Dyneema loop – 22mm	60461	52	2 1/16	12	7/16	22	7/8	230	9 1/16	2400	5291	75	2.6
11	High load low friction eye with Dyneema loop – 28mm	60462	65	2 9/16	16	5/8	28	1 1/8	310	12 3/ <sub>16</sub>	3600	7964	140	4.9







## Bulkhead Pipe Glands

In consultation with naval architects and engineers, boat builders and surveyors, Barton responds with a proven Bulkhead Pipe Gland design to allow pipes and tubes to move through vessel compartments providing vapour and watertight integrity, meeting the new MCA Work Boat Code 3 and MGN 200/280 regulations.

Ideal for boat builders, restorers and refitters to meet challenging new marine protocols and satisfy requirements for workboats and leisure charters to seal bulkheads as proficiently as petrochemical equipment glands. Barton Bulkhead Pipe Glands make use of two different resins to meet heat resistant factors for pipes. They are designed specifically as robust seals for marine vessels with longer stainless steel studs for bulkhead wall variances and curved surfaces – while allowing for pipes and tubes to be adjusted and serviced. Bolt and clamp fittings can be removed quickly and easily with basic tools. Manufactured in high grade, light grey material means they blend in with the bulkhead for style and performance.


#### Barton Bulkhead Pipe Glands tick all the boxes:

- Vapour and watertight construction
- ✓ Seals the aperture for pipe and tube integration
- Compatible for angled pipes and curved surfaces
- ✓ Sealed but fully serviceable & adjustable
- Stainless Steel and Nitrile Rubber (BS2751)
- Suitable for bulks up to 35mm thick






	AD PIPE GLA		<del></del>					
PHOTO NO	PART NO	DESCRIPTION	DESIGN I	FOR PIPE OD	HOLE CUTT DIAM		FAST	ENER!
			мм	INCH	ММ	INCH	NO	SIZE
1	BPG-50	Bulkhead Pipe Gland 50mm OD	45-50	1 3/4-2	60	2 3/8	4	M6
1	BPG-63	Bulkhead Pipe Gland 63mm OD	58-63	2 5/16-2 1/2		4 1/4	6	M6
1	BPG-110	Bulkhead Pipe Gland 110mm OD	98-110	3 7/8-4 5/16	140	5 1/2	10	M6
1	BPG-180	Bulkhead Pipe Gland 180mm OD	160-180	6 5/16-7 1/16	200	7 7/8	12	M6
2	BPI-25	Bulkhead Reducing Insert 25mm OD for BPG-50	22.5-25	7/8-1	-	-	-	-
2	BPI-32	Bulkhead Reducing Insert 32mm OD for BPG-50	28 -32	1 1/8-1 1/4	-	-	-	-
2	BPI-50	Bulkhead Reducing Insert 50mm OD for BPG-63	45-50	1 3/4-2	-	-	-	-
2	BPI-75	Bulkhead Reducing Insert 75mm OD for BPG-110	68-75	2 11/ <sub>16</sub> -3	-	-	-	_
2	BPI-90	Bulkhead Reducing Insert 88mm OD for BPG-110	82-90	3 1/4-3 7/16	-	-	-	-
2	BPI-125	Bulkhead Reducing Insert 125mm OD for BPG-180	105-125	4 1/8-5	_	_	-	_
2	BPI-140	Bulkhead Reducing Insert 140mm OD for BPG-180	117-140	4 5/8-5 1/2	-	-	-	-
2	BPI-160	Bulkhead Reducing Insert 160mm OD for BPG-180	122-160	4 13/16-6 5/16	_	-	-	_
3	BPB-50	Blanking Plug Insert for BPG-50	-	-	-	-	-	-
3	BPB-63	Blanking Plug Insert for BPG-63	_	-	-	-	-	-
3	BPB-110	Blanking Plug Insert for BPG-110	-	-	-	-	-	-
3	BPB-180	Blanking Plug Insert for BPG-180	_	_	-	-	_	_



Suitable for curved surfaces and angled pipe entry





**BPG - BULKHEAD PIPE GLANDS** – four popular sizes of Barton Bulkhead Glands (BPG) for pipes and tubes are supplied as standard. The Glands are moulded from Nitrile Rubber with heat resistance to 105°C. The excellent physical properties and Shore hardness of Nitrile Rubber means no sealants or mastics are required and the stainless fittings allow for adjustments and servicing. Standard Gland sizes can be converted for different size pipes using Barton Bulkhead Reducing Inserts.

**BPI – BULKHEAD REDUCING INSERTS** – Barton's Bulkhead Reducing Inserts (BPI) reduce the apature diameter to allow standard Gland conversion for multiple pipe and tube sizes. When using Barton Inserts with the Barton Bulkhead Pipe Glands, heat resistance increases to 150°C. The Bulkhead heat Inserts shield the Gland and pipe while sustaining a superior bulkhead seal.

**BPB – BULKHEAD BLANKING PLUGS** – Barton's Bulkhead Blanking Plugs (BPB) are primarily used to seal off the Gland. This seal can be permanent or temporary. Plugs can be drilled or cut to match a different size diameter or aperture shape when required.

## Industrial Blocks & Block on a Strop

#### **INDUSTRIAL BLOCKS - CE CERTIFIED**

Industrial snatch blocks are designed for easy use in commercial, industrial or marine settings to move or lift loads securely.

These durable snatch blocks are made of 316 stainless steel with anodised aluminium sheaves and are CE certified and stamped. The Industrial Range handles rope or wire thicknesses of 8-14 mm – and a special design that handles 32mm line. Snatch blocks are easy to load and instantly mobile for diverse projects used for:

- Construction sites / manufacturing sites
- Commercial marine environments
- Rigging projects
- Agricultural, building repairs, home improvements
- Entertainment venues
- Lift and pulling applications
- CE certified and stamped



Easy to open and close - locked in place with your choice of shackle or snap hook.

#### **BLOCK ON A STROP - CE CERTIFIED**

This special block was designed and developed for marinas, scaffolders, builders and any engineer who needs multiple lift options at a given worksite.


Manufactured of graphite glass filled nylon and stainless steel, this durable Series 7 precision plain or ball bearing sheave block is CE certified for secure quality and compliance. The stainless steel becket at the base an attachment point when required. The attached Dyneema spliced strop can be slipped around a pole, tube or bar to create a bespoke lifting device for tools, equipment or panels - and then removed or relocated when the job is complete.

CIZE	DARTAGO	WLL		BREAK L	.OAD
SIZE	PART NO	KG	LBS	KG	LBS
Block on strop - plain sheave	N07191	600	1320	2400	5280
Block on strop - ball bearing sheave	N17191		1320	2400	5280

CE approved at 4:1 rating.
The WLL can be reviewed for marine applications.



	PART	WLL	WLL BREAK LO		AD	MAX ROPE DIA Ø	
SIZE		KG	LBS	KG	LBS	ММ	INCH
30mm sheave	92030	75	165	300	660	8	5/16
50mm sheave	92050	125	275	500	1100		
75mm sheave	92075	275	605	1100	2480	12	7/16
100mm sheave	92100	375	825	1500	3300	14	7/ <sub>16</sub>
70mm sheave	92135	225	495	900	1980	32	1 1/4



## **Custom Design & Build**



and performance standards to produce significant results for your projects. Our partnerships

with OEMs and their individual market sectors, have resulted in key advances and equipment strategies for multiple applications worldwide.

We design and manufacture in the UK, so projects progress at pace with minimal lead times to meet crucial delivery schedules. Contact Barton Marine for more information and to discuss marine and general industrial projects.

sales@bartonmarine.com

# Recirculating Ball Traveller Systems

#### TRACK 20MM / 26MM / 30MM

#### Per metre or in set lengths - choose from the table below.

Lightweight hollowed aluminium track retains high load capacity. Extremely durable Spectro anodised finish adds to the friction-free efficient performance of these products.

All systems available in black and Spectro anodised finish. Three track styles available – drilled, sliding bolt and beam:

#### **DRILLED TRACK**

The most commonly used, drilled and countersunk at 100mm centres (Size 1, 2, 3), with the first hole at 50mm from track end. The size 0 Track is drilled at 50mm whole centres.

SPECIFICATIONS	SIZE 0	SIZE 1	SIZE 2	SIZE 3
<b>W</b> Width	16mm	20mm	26mm	30mm
<b>H</b> Height	9mm	12mm	15mm	18mm
Fastenings	4mm	5mm	6mm	8mm



#### **SLIDING BOLT TRACK**

To allow for a smooth profile with no visible fastenings. Also makes retro fit an easier job, as bolts can slide along the extrusion to match existing fastening holes. Ensure washers are fitted beneath track to ensure a good seal (see diagram).

SPECIFICATIONS	SIZE 1	SIZE 2	SIZE 3
<b>W</b> Width	20mm	26mm	30mm
<b>H</b> Height	12mm	16.5mm	19mm
Fastenings	5mm	6mm	8mm



#### **BEAM TRACK**

Use beam track when spanning cockpits or companionway hatches, where an unsupported length is required. A minimum of three fastenings should be used on either side of the unsupported length – place fastenings at 100mm centres in supported sections. Ensure washers are fitted under the head of the bolt and between track and deck to ensure a secure seal (see diagram).

		1	1	
SPECIFICATIONS	SIZE 1	SIZE 2	SIZE 3	
W Width 1	20mm	26mm	30mm	<b>5 – 1</b>
<b>H</b> Width 2	26mm	34mm	40mm	
Height	27mm	34.5mm	40.5mm	
Fastenings	6mm	8mm	10mm	w2 ·
Maximum Unsupported Span	400mm	700mm	800mm	

#### FITTING SLIDING BOLT TRACK








PHOTO NO		SIZE 0	SIZE 1	SIZE 2	SIZE 3
Drilled t	rack				
1	PER METRE	18000	20000	24000	30000
	0.6 metre		20010	24010	30010
	1.2 metre	18020	20020	24020	30020
	1.8 metre	18030	20030	24030	30030
	2.4 metre	18040	20040	24040	30040
	3.0 metre	18050	20050	24050	30050
	5.0 metre	18060	20060	24060	30060
2	END CAP (PAIR)	18001	20001	24001	30001
Sliding l	oolt track				
4	PER METRE		20002	24002	30002
	0.6 metre		20012	24012	30012
	1.2 metre		20022	24022	30022
	1.8 metre		20032	24032	30032
	2.4 metre		20042	24042	30042
	3.0 metre		20052	24052	30052
	5.0 metre		20062	24062	30062
2	END CAP (PAIR)		20001	24001	30001
Beam tr	ack				
5	PER METRE		20003	24003	30003
	0.6 metre		20013	24013	30013
	1.2 metre		20023	24023	30023
	1.8 metre		20033	24033	30033
	2.4 metre		20043	24043	30043
	3.0 metre		20053	24053	30053
	5.0 metre		20063	24063	30063
3	END CAP (PAIR)		20100	24100	30100

#### **CONVERSIONS**

METRES	FEET
1	3′ 3 3/8″
2	6′6 3/4″
	9′ 10 1/8″
4	13′1 1/2″
5	16′ 4 7/8″

#### **COMPLETE SYSTEMS**

Pre-packaged mainsheet systems with all components required in one complete kit - sliding bolt track, traveller, end fittings, plastic end caps, pilot track and full fitting instructions.

Travellers, end fittings and track are manufactured from high quality marine grade aluminium with our unique Spectro anodised finish for added protection. Sliding bolt track allows for a smooth, clean profile and also makes retro-fitting easier as bolts can slide along the extrusion to match existing fastening holes.

- Three sizes for yachts up to 14m LOA (45ft)
- 2:1 or 4:1 purchase systems
- Recirculating precision ground Delrin ball system

#### **SIZE GUIDE**

Size 1 for yachts up to 8.5m (28ft)

Size 2 for yachts up to 11.0m (36ft)

Size 3 for yachts up to 14.0m (45ft)

#### **SLIDING BOLT TRACK SECTIONS**

These kits are supplied with sliding bolt track and are not recommended for unsupported spans across cockpits or hatches. Please use the 'Beam Track' profile (p49) and build up the parts from pages 50-55. Rope not supplied.

#### **2:1 PURCHASE KIT** with cleats at 70° on end fittings

•	1.4m (size 1) /1.6m (size 2) /1.8m (size 3)	SIZE 1
	sliding bolt track	20900
•	Traveller car with single shackle take off	SIZE 2
•	End fittings (pair)	24900
•	Plastic end caps (pair)	SIZE 3
•	Pilot track and fitting instructions	30900

#### **4:1 PURCHASE KIT** with cleats at 70° on end fittings

• 1.4m (size 1) /1.6m (size 2) /1.8m (size 3)	SIZE 1
sliding bolt track	20901
• Traveller car with single shackle take off	SIZE 2
• End fittings (pair)	24901
Plastic end caps (pair)	SIZE 3
<ul> <li>Pilot track and fitting instructions</li> </ul>	30901

#### 4:1 PURCHASE KIT Incorporating cleats on traveller

1.4m (size 1) /1.6m (size 2) /1.8m (size 3) sliding bolt track	SIZE 1 20902
Traveller car with single shackle take off	SIZE 2
End fittings (pair)	24902
Plastic end caps (pair)	SIZE 3
Pilot track and fitting instructions	30902
	sliding bolt track Traveller car with single shackle take off End fittings (pair) Plastic end caps (pair)









# Removable Mainsheet System Kits

- creates more space in the cockpit
- recirculating ball traveller systems

#### The removable mainsheet track system, ideally suited for all yachts up to 12m (39ft)

This adaptable mainsheet track system is designed to span between the cockpit seats when sailing but is easily removed to give maximum cockpit space when you want to relax on board. It also can provide the perfect solution for converting coach roof mainsheet sheeting systems to one that is within reach of the helmsman, offering greater sail control and safety.

The removable Beam Track system is available in three sizes for use on yachts up to a maximum of 12m (39ft). See p48.

#### All systems available in Spectro or black anodised finish.

Barton Marine's removable track system is simple to install. End plates are bolted on both sides of the cockpit. Slide the track under these plates and then lift vertically, which automatically locks in position. To remove the mainsheet track, simply push in the locking pins on each end, lower the Beam Track and slide it out.

Beam Track Ending Plates are 100mm (3 <sup>15</sup>/<sub>16</sub>") diameter and use 5mm Socket head fasteners (not supplied). Plates must be installed in a vertical position so wedges may be required to ensure level surfaces.



РНОТС	NO	PART NO SILVER	PART NO BLACK	MAX UNSUPPORTED LENGTH
BEAM .	FRACK END PLATE FITTINGS (PAIR)			
1	Fits size 1 20003 Beam Track	20090	20090B	400mm
	Fits size 2 24003 Beam Track	24090	24090B	700mm
	Fits size 3 30003 Beam Track	30090	30900B	800mm
BEAM '	TRACK	SIZE 1	SIZE 2	SIZE 3
	PER METRE	20003	24003	30003
	0.6 metre	20013	24013	30013
	1.2 metre	20023	24023	30023
	1.8 metre	20033	24033	30033
COMPI TRACK	ETE REMOVABLE MAINSHEET SYSTEM KITS	PART NO SILVER	PART NO BLACK	
2	Suitable for yachts up to 8.5m (28.5ft)	20910	20910B	-
	Suitable for yachts up to 11.0m (36ft)	24910	24910B	-
	Suitable for yachts up to 11.0m (36ft)	30910	30910B	-

#### **BEAM TRACK**

Beam Track is used when spanning cockpits that are unsupported. For installations with excess cockpit width, support can be doubled by installing a pelican hook assembly or Dyneema strop, fitted from the underside of the middle of the track and connected to a floor-mounted pad eye.



#### **REMOVABLE MAINSHEET TRACK**

- Part no 20910 (Spectro) Suitable for yachts up to 8.5m (28.5ft)
- Part no 20910B (Black) Size 1 beam track 1m length
  - 1 Pair removable mainsheet track plates
  - 4:1 traveller system with cleats on the traveller

- Part no 24910 (Spectro) Suitable for yachts up to 11m (36ft)
- Part no 24910B (Black) Size 2 beam track 1m length
  - 1 Pair removable mainsheet track plates
  - 4:1 traveller system with cleats on the traveller

Part no 30910B (Black)

- Part no 30910 (Spectro) Suitable for yachts up to 12m (40ft)
  - Size 3 beam track 1m length
  - 1 Pair removable mainsheet track plates
  - 4:1 traveller system with cleats on the traveller

The maximum unsupported span of the beam track is

Size 1 = 400mm for yachts up to 8.5m (28ft)

Size 2 = 700mm for yachts up to 11.0m (36ft)

Size 3 = 800mm for yachts up to 12m (40ft))



Removable mainsheet track system kits create more space in the cockpit.





# Recirculating Ball Mainsheet Systems

#### MODULAR 'SHACKLE FIXING' COMPONENTS FOR RECIRCULATING BALL BEARING TRAVELLER SYSTEMS

'Shackle Take Off' travellers are the traditional choice for yachtsmen. With high break loads, and a single swivel point through the centre of the car, these durable travellers are fitted with Delrin ball bearings as standard (upgrades to Torlon balls are available by special order and will increase the break loads). Three car sizes are available to match the vessel size for peak loading performance. We provide solutions from day boats to 14m (46') yachts.

Choose the individual components required to build the system which is the most suitable for your boat. See pages 49-51 for pre-designed kits.

Available in Spectro and black anodised finish - All part numbers below are for Spectro anodising. For black anodising put a B at the end of the part number shown.



#### Traveller Car

With single shackle take off and integral control line sheaves 2:1 or 3:1 purchase.

Size 1	Size 2	Size 3
20101	24101	30101
20101	24101	30101



With single shackle take off 4:1 purchase. Comprises:

Size 1 Size 2 Size 3	
20101 24101 30101	
20112 24112 30112	

Order both part numbers to achieve the product shown.



**GUIDE TO CHOICE OF SIZE:** 

**Size 1** – for yachts up to 8.5m (28.5ft)

Size 2 - for yachts up to 11.0m (36ft)

Size 3 - for yachts up to 14.0m (46ft)

**Traveller Car** With cleats and single shackle take off 4:1 purchase. Comprises:

Size 1	Size 2	Size 3
20101	24101	30101
20117	24117	30117

Order both part numbers to achieve the product shown.



#### **Traveller Car**

**Traveller Car** 

With double shackle take off and integral control line sheaves 2:1 or 3:1 purchase.

Size 1	Size 2	Size 3
20103	24103	30103



#### Traveller Car

With double shackle take off 4:1 purchase. Comprises:

Size 1	Size 2	Size 3
20103	24103	30103
20112	24112	30112

Order both part numbers to achieve the product shown.



#### Traveller Car

With cleats and double shackle take off 4:1 purchase. Comprises:

Size 1	Size 2	Size 3
20103	24103	30103
20117	24117	30117

Order both part numbers to achieve the product shown.

#### **DOUBLE TAKE OFF SHACKLE TRAVELLERS**

With either shackle or toggle attachments, these allow coarse and fine tune mainsheet systems to be achieved. They can also be used with a link plate (p54-55) to allow for increased rolling load with the longer cars (see p12).

#### **CONTROL LINE SHEAVE CAGE**

Size 1 uses a plain bearing sheave. Sizes 2 and 3 feature our low friction large diameter ball bearing sheave system.

#### MODULAR 'TOGGLE FIXING' COMPONENTS FOR RECIRCULATING BALL BEARING TRAVELLER SYSTEMS

#### The unique Barton modular system allows a wide variety of control line options.

In the following tables, order both part numbers listed (where appropriate) for the traveller illustrated.

### 'Toggle take off' travellers are a more modern approach to connecting your mainsheet.

Featuring a solid cast stainless steel upstand fork with a soft rubber anti-tumble bearing fitted, preventing damage when blocks are not under load. These take offs accept the swivel post from our cruiser blocks and help achieve a truly low profile system. The stand up fork design allows for articulation in two directions giving better performance and block alignment.



With single toggle take off and internal control line sheaves.

Size 1	Size 2	Size 3
20105	24105	30105



With single toggle take off 4:1 purchase. Comprises:

Size 1	Size 2	Size 3
20105	24105	30105
20112	24112	30112

Order both part numbers to achieve the product shown.

#### **GUIDE TO CHOICE OF SIZE:**

**Size 1** – or yachts up to 8.5m (28.5ft)

Size 2 – for yachts up to 11.0m (36ft)

**Size 3** – for yachts up to 14.0m (46ft)



With cleats and single toggle take off 4:1 purchase. Comprises:

Size 1	Size 2	Size 3
20105	24105	30105
20117	24117	30117

Order both part numbers to achieve the product shown.



#### **Traveller Car**

With double toggle take off and integral control line sheaves 2:1 or 3:1 purchase.

Size 1	Size 2	Size 3	
20107	24107	30107	

#### Traveller Car

With double toggle take off 4:1 purchase. Comprises:

Size 1	Size 2	Size 3
20107	24107	30107
20112	24112	30112

Order both part numbers to achieve the product shown.

#### **Traveller Car**

With cleats and double toggle take off 4:1 purchase. Comprises:

Size 1	Size 2	Size 3
20107	24107	30107
20117	24117	30117

Order both part numbers to achieve the product shown.

### **End Fittings & Accessories**

#### TRAVELLER CONTROL LINE CAGES AND CAMS

All systems available in black and Spectro anodised finish. Add 'B' to the end of the part number for black anodising.

DESCRIPTION	LENG	тн	WEIGH	<del>1</del> Т	WIDTI	1	SHEAV	Æ Ø	MAX C	CONTROL S
CONTROL LINE SHEAVE CAGE	мм	INCH	G	oz	мм	INCH	мм	INCH	ММ	INCH
Size 1 - 20112 Plain Bearing	41	1 5/8	15	0.5	38	1 1/2	20	13/16	6	1/4
Size 2 - 24112 Ball Bearing	52		27	1		1 15/ <sub>16</sub>				5/16
Size 3 - 30112 Ball Bearing	65	2 9/16	42	1.5	57	2 1/4	35	1 3/8	8	5/16



**Control Line Sheave Cage** 

For use on travellers and end fittings (supplied in pairs).

Size 1	Size 2	Size 3
20112	24112	30112



Traveller Car

Long double toggle take off car with link plate fitted. Ideal for heavy duty applications.

Size 1	Size 2	Size 3
20107	24107	30107
20202	24202	30202



**End Fitting** 2:1 or 3:1 purchase (supplied in pairs).

Size 1	Size 2	Size 3
20110	24110	30110



**Traveller Cleat Plate** Assembly

(supplied in pairs).

Size 1	Size 2	Size 3
20117	24117	30117



**Link Plate** 

For long double toggle take off cars. Heavy duty stainless plate that spans toggles - for heavy duty applications.

Size 1	Size 2	Size 3
20202	24202	30202



**End Fitting** 

4:1 purchase (supplied as a pair).

Size 1	Size 2	Size 3
20110	24110	30110
20112	24112	30112

Order both part numbers to achieve the product shown.



**End Fitting Cleat Plate** 

At 70° to track (supplied in pairs).

Size 1	Size 2	Size 3
20114	24114	30114



**Torlon Balls** 

Torlon ball packages available for all traveller sizes.

Short Car		
Size 2	Size 3	
24200	30200	
nr		
Size 2	Size 3	
24201	30201	
	Size 2 24200 ar Size 2	



End Fitting with Cleat at 90°

2:1 or 3:1 purchase (supplied as a pair).

Size 1	Size 2	Size 3
20110	24110	30110
20113	24113	30113

Order both part numbers to achieve the product shown.



**End Fitting Cleat Plate** 

At 90° to track (supplied in pairs).

Size 1	Size 2	Size 3
20113	24113	30113



**Link Plate & Twin Travelers** 

Designed for curved track applications. Comes assembled ready to load on to the track.

Size 1	Size 2	Size 3
20108	24108	30108



End Fitting with Cleat at 70°

2:1 or 3:1 purchase (supplied as a pair of each p/no).

Size 1	Size 2	Size 3
20110	24110	30110
20114	24114	30114

#### **END FITTINGS - RECIRCULATING BALL BEARING**

The unique Barton modular system allows a wide variety of systems to be constructed, giving multiple control line and cleating options for track end fittings. The end fittings use an acetal rod instead of balls to locate the car to the track. End fittings are pre-drilled, which require a locating bolt hole to be drilled in the track.

In the following tables, order both part numbers listed (where appropriate) for the traveller end fitting illustrated.



End Fitting with Cleat at 90° 4:1 purchase (supplied as a pair of each p/no).

Size 1	Size 2	Size 3
20110	24110	30110
20113	24113	30113
20112	24112	30112

Order all part numbers to achieve the product shown.



**End Fitting with Cleat at 70°** 4:1 purchase (supplied as a pair of each p/no).

Size 1	Size 2	Size 3
20110	24110	30110
20114	24114	30114
20112	24112	30112
20112	22	00112

Order all part numbers to achieve the product shown.



Crash Stop for Genoa Track (supplied in pairs).

Size 1	Size 2	Size 3
20310	24310	30310

#### **TECHNICAL SUMMARY & SIZES RECIRCULATING BALL SYSTEM**

Aesthetic design, clean lines, high-tech materials and finishes all go into make this range of traveller cars a functional and practical enhancement for any sailboat. All end fittings feature a soft rubberised moulded cap, designed to withstand high impact without causing damage. Standard travellers run on precision ground Delrin ball bearings. A Torlon ball bearing package is available where higher load applications are required. Torlon balls give up to 40% more load bearing capacity. These packages are available in size 1, 2, 3 and for long or short travellers.

	LENG SINGI OFF	TH _E TAKE	LENG DOUE TAKE	BLE	WEIG SINGI TAKE	LE	WEIGH DOUBI TAKE (	ĹĖ	WID.	тн	FASTI	ENING	WIDTH CONTI LINE C	ROL	HEIGI	HT 2:1	HEIGI	HT 4:1	SWL		MAX CON LINE	
	ММ	INCH	ММ	INCH	G	oz	G	oz	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS	мм	INCH
TRAVEL	LERS									ALI	MEAS	UREMEI	NTS ARE	FROM D	ECK TO	TOP O	F CAR	WHEN M	OUNTED	ON DR	ILLED 1	TRACK
Size 0	65	2 9/16	-	-	62	2.2	-	-	43	1 11/16	M4	3/16	-	-	19	3/4	-	-	130	286	5	3/16
Size 1	132	5 <sup>3</sup> / <sub>16</sub>	204	8 <sup>1</sup> / <sub>16</sub>	252	8.9	411	14.5	60	2 3/8	M4	3/16	98	3 7/8	35	1 3/8	48	1 <sup>7</sup> / <sub>8</sub>	500	1100	6	1/4
Size 2	166	6 9/16	254	10	547	19.3	923	32.6	76	3	M6	1/4	120	4 3/4	44	1 3/4	57	2 1/4	700	1540	8	5/16
Size 3	198	7 3/16	292	111/2	872	30.8	1378	48.6	78	3 1/16	M6	1/4	130	5 1/8	47	1 7/8	65	2 9/16	1000	2200	8	5/16

	LENG <sup>*</sup>	тн	WEIGH	łT	WIDTH	1		H WITH ROL LINE S	HEIGH	T 2:1	HEIGH	T 4:1	MAX C	ONTROL
	мм	INCH	G	OZ	мм	INCH	мм	INCH	мм	INCH	мм	INCH	мм	INCH
END FITTINGS						ALL M	EASURE	MENTS ARE FF	ROM DE	CK TO TOP OF	CAR WH	IEN MOUNTE	ON DR	ILLED TRACK
Size 0	45	1 3/4	37	1.3	43	1 11/16	-	-	19	3/4	-	-	5	3/16
Size 1 - 20110	67	2 5/8	117	4.1	60	2 3/8	100	3 <sup>15/</sup> 16	35	1 <sup>3</sup> / <sub>8</sub>	48	1 7/8	6	1/4
Size 2 - 24110	88	3 7/16	234	8.3	76	3	127	5	50	1 15/16	65	2 9/16	8	5/16
Size 3 - 30110	96	3 3/4	362	12.8		3 1/2	137	5 3/8		2 3/8		2 15/16	8	5/16

# Ball Bearing Traveller Spare Kits

Barton Marine offers spares packs for each range of our ball bearing traveller cars. Each kit comprises new black nylon traveller end caps, new end cap fixing screws and a new set of Delrin ball bearings.

Inspecting the condition of your existing end caps which hold the ball bearings within the ball race should be a part of routine maintenance as these can be damaged by crash gybes and salt degradation over time. Any damage here will result in ball bearings being lost and failure of the traveller car.



#### 18210

Dinghy Traveller Service Kit Balls and End Caps for standard length cars.

#### 24210

Size 2 Traveller Service Kit Balls and End Caps for the standard length cars.

#### 20210

Size 1 Traveller Service Kit Balls and End Caps for standard length cars.

#### 30210

Size 3 Traveller Service Kit Balls and End Caps for the standard length cars.

#### **CURVED TRACK SOLUTIONS**

Barton Marine curves track to order, in any plane to suit an application.

Curved tracks with tight bend radi can require short cars with a link plate to allow them to move freely around the curve. The link plate kits shown here are ideal for this application. They feature Delrin ball bearings and stainless steel plates.

Contact **sales@bartonmarine.com** for lead times and more information.



#### **Link Plate & Twin Traveller Kits**

Designed for curved track applications. Comes assembled ready to load on to the track. The Link Plate working in conjunction with the two short cars and nylon bushes ensures a free running car along the track.

Available for size 1, 2 and 3 tracks.







## Recirculating Ball Towable Genoa Car Systems

#### HIGH PERFORMANCE TOWABLE GENOA CAR SYSTEM

Available in three sizes for yachts up to 13m LOA (42ft) - all three run on the three track types available

2:1, 3:1 and 4:1 systems can be achieved with the unique Barton modular system. End fittings and parts are compatible with the Barton recirculating components. Featuring a precision turned Ertalyte sheave running on a large diameter bearing. The bolt through sheave design not only looks good, but gives added strength to these rugged units.



**Genoa Car**With integral sheaves (2:1, 3:1 or 4:1).

 Size 1
 Size 2
 Size 3

 20300
 24300
 30300



**Genoa Car**With integral control line sheaves (4:1).

Size 1	Size 2	Size 3
20300	24300	30300
20112	24112	30112

Order both part numbers to achieve the product shown.



**End Fitting**With integral sheaves (supplied in pairs).

 Size 1
 Size 2
 Size 3

 20110
 24110
 30110

#### 2:1 Purchase System

NOTE: All systems available in Spectro or black anodised finish. Add 'B' to the end of the part number shown for black anodising.

	LENGTH		WEIGHT		WIDTH	1	HEIGH	IT	SWL		SHEAV	'E Ø	SHEAVE WIDTH		
	ММ	INCH	G	OZ	мм	INCH	ММ	INCH	KG	LBS	мм	INCH	ММ	INCH	
GENOA CAR						ALL M	EASURE	MENTS ARE FR	OM DEC	CK TO TOP OF	CAR WH	HEN MOUNTED	ON DR	ILLED TRACK	
Size 1 – 20300	118	4 5/8	400	14.1	57	2 1/4	97	3 13/16	500	1100	50	1 15/16	36	1 7/16	
Size 2 – 24300	145		775	27.3			116	4 9/16	700	1540	60			1 7/16	
Size 3 – 30300	170	6 11/16	1181	41.7	87	3 7/16	133	5 1/4	1000	2200	70	2 3/4	45	1 3/4	

#### **WORKING JIB POSITION NO. 2 GENOA POSITION FULL SAIL** Furled to second marker on foot of Genoa. Furled to first marker on foot of Genoa. Genoa car in optimum position for windward Genoa car moved forward Genoa car moved forward from sailing performance. Rule of position 1 to position 2 for from position 2 to position thumb - sheet lead angle 3 for optimum windward optimum windward bisects luff length sailing performance. sailing performance. of Genoa. Genoa car Genoa car Genoa car position 3 position 2 position 1

# Recirculating Ball 16mm Track

### RECIRCULATING BALL BEARING DINGHY TRAVELLER RANGE

Complementing Barton's recognised larger traveller range, the dinghy traveller system uses proven recirculating Delrin ball technology and features a 16mm wide track.

With holding power of up to 130kg; the attachment eye allows the system to be easily secured to our block range, creating powerful purchase ratios.

Travellers, end fitting and track are manufactured from high quality marine grade aluminium with our unique Spectro or black anodised finish for added protection.

See p7 for our suggested boat size table designed to help you clarify the correct size of traveller for your application.

DINGHY TRA	VELLERS						
PHOTO NO	DESCRIPTION	PART NO					
1	Traveller car with single shackle take off	18101					
	Traveller car with single toggle take off	18105					
3	End fitting (supplied in pairs)	18110					
	Control attachment eye (supplied in pairs)	18111					
5	Loop eyes (supplied in pairs)	18112					
DRILLED TRA	ск						
РНОТО NO	DESCRIPTION	PART NO					
6	Per metre	18000					
	0.6 metre	18010					
	1.2 metre	18020					
	1.8 metre	18030					
	2.4 metre	18040					
	3.0 metre	18050					
	5.0 metre	18060					
	Track end cap (pair)	18001					

**NOTE:** All systems available in black or Spectro anodised finish. Add a 'B' to the end of the part number for black anodised.



### **Barton Genoa Car Range**

### **Endurance restyled**

### **NEW ICONIC DESIGN**



#### **KEY FEATURES**

- Sleek, bold design reflects two years of styling and development
- Ertalyte Sheaves are machined with a riveted tube for extra strength
- Large tubular stainless steel bearings for optional 2:1 Genoa sail rigging
- Plunger Pin features easy grip knob and twist-lock action for easy adjustment
- HD Versions for larger yachts and heavy duty loads
- Spectro or black anodised



## T Track Systems

#### BARTON T TRACK SYSTEMS ARE AN ESTABLISHED FAVOURITE WITH SAILORS AROUND THE WORLD

T Track is Spectro or black anodised and predominantly used with Genoa Cars. Coupled with the bold new GT and HD Genoa Car line, mariners achieve a stream-line assembly to resist sheet fouling and improve performance for speed and sail control. Barton Genoa Cars fit all types of functional T Track, but to ensure track compatibility when refitting, adaptable inserts are available. So a key benefit of the Barton Genoa Car range is that it fits all T Track extrusions so changing existing track on decks is unnecessary.

Manufactured from anodised marine-grade aluminium and engineered with internal nylon slide inserts for free running, the Ertalyte sheaves with a central riveted tube create strength and durability on plunger and towable designs. Plunger Genoa Cars feature a moulded knob and stainless steel pin that is easy to grip even when wearing sailing gloves and the pin action can twist and lock open for ease of adjustment.

T Track Systems with Genoa Cars or mainsheet cars can be assembled using our component scheme to build custom solutions for any boat. Available in three sizes for yachts from 5m-15m (16'-49'): 20mm T Track; 25mm T Track; 32mm T Track.

#### **BARTON PLUNGER T TRACK GENOA CARS**

These cars are compatible with all types of functional T Track. A simple pull up plunger is fitted to the car which allows the car to be positioned on the track, to obtain perfect headsail trim. This movement cannot be achieved while the head sail sheet is under tension. Plunger cars offer a cost effective way to move and lock a car into position.

#### **BARTON TOWABLE T TRACK GENOA CARS**

These cars are compatible with all types of T Track. The advantage of a line adjust system is that the crew do not have to leave the safety of the cockpit to obtain perfect headsail trim. We developed this design to incorporate control line sheaves within the body of the sliders and end fittings. The result is a sleek, compact unit with less likelihood of sheet fouling.


#### **BARTON MAINSHEET T TRACK CARS**

These cars are compatible with all types of functional T Track. The simple stainless steel D-ring which is bolted and riveted through the car body provides a cost effective solution for many boats. Often used in conjunction with a pair of plunger stops to limit travel along the track.

#### **BARTON SPINNAKER T TRACK CARS & TRACK**

The T Track produced by Barton has a small radius on the back to allow it to be mounted on the front of a mast so 'Spinnaker Pole Sliders' can be used. Getting the spinnaker pole at the right height for a sail set can improve boat speed dramatically. There are two options with the spinnaker pole cars: built in plunger or towed. Adding standard components from the T Track family produces a custom system to suit all needs.

GENOA CAR AND TRACK SELECTION GUIDE										
BOAT SIZE	7M	8.5M	11.5M	14.5M						
20MM T TRACK										
25MM T TRACK										
32MM T TRACK			•							
32MM T TRACK HIGH LOAD										



TRAC	K SIZE	WIDT <b>W</b>	н	WIDT <b>X</b>	гн	HEIG <b>H</b>	нт	LIP THICI <b>J</b>	KNESS	FAST CEN <sup>-</sup>	ENING FRES	FAST SIZE	ENER	PLUN HOLE CENT	·	PLUN HOLE		WEIG PER N	HT METER	SUGGES <sup>®</sup> BOAT SIZ	
ММ	INCH	мм	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	G	OZ	METRES	FEET
20	13/16	20	13/16	11	7/16	8	5/16	2.5	1/8	100	3 15/16	5	3/16	50	1 15/16	6.5	1/4	270	9.5	5-8	16-26
25	1	25		14	9/16	10	3/8	4	3/16	100	3 <sup>15</sup> / <sub>16</sub>	5	3/16	50	1 <sup>15</sup> / <sub>16</sub>		1/4	441	15.6	7-10	23-49
32	1 1/4	32	1 1/4	20	13/16	15	9/16	5	3/16	100	3 15/16	6	1/4	50	1 15/16	10	3/8	756	26.7	9-15	30-49

### **20mm T Section Track**

#### T SECTION TRACK, SLIDERS, ORIGINAL GENOA CARS SUITABLE FOR BOATS 5m-8m (16'-26')

#### PLAIN BEARING GENOA CARS AND SLIDERS

A lightweight and compact range of plain bearing extruded aluminium sliders, running on 20mm (34") T track and manufactured from high quality marine grade aluminium with our unique Spectro anodised finish for added protection. Cars and track can also be anodised black. This useful range will find a wide variety of applications on larger dinghies, dayboats and light cruiser/racers. See p7 for the suggested boat size table designed to help you clarify the correct size of sliders for your application.



#### **GENOA CAR WITH PLUNGER STOP**

Features a precision turned Ertalyte sheave, through-bolted for extra strength. The positive action plunger mechanism has an easy grip knob (see page 9 for setup options).



**TOWABLE GENOA CARS 1:1** 

With tow eyes both ends, this allows a control line to be led forward & aft so the Genoa car can be adjusted from the cockpit. Used in conjunction with end fitting 22221.



**CARS 2:1** 

This is designed to be rigged to give a 2:1 mechanical advantage when pulling the car forward along the track. The single line attachment point has a removable stainless steel bolt machined to aluminium body of the car. Control lines can be led aft so that Genoa car adjustments can be made from the cockpit. Use in conjunction with end fitting 22221.





**TOWABLE CAR END FITTING** 

Features a becket and single sheave. These do need to be bolted into the track or deck. Can be used with the 1:1 and 2:1 towable Genoa cars.

РНОТО	LDESCRIPTION	PART NO SPECTRO	PART NO BLACK	LENG	STH	WID	тн	HEIC	ЭНТ	SHE	AVE Ø	MAX ROP		BREAK	LOAD	SWL		WEIG	нт
NO		ANODISE	ANODISE	ММ	INCH	ММ	INCH	мм	INCH	ММ	INCH	мм	INCH	KG	LBS	KG	LBS	G	oz
1	Genoa car plunger system	22100	22100B	60	2 23/64	34	1 5/16	65	2 9/16	30	1 3/16	10	3/8	1160	2552	580	1276	119	4.2
2	Towable Genoa car 1:1	22200	22200B	110	4 5/16	34	1 <sup>5/</sup> 16	65	2 9/16	30	1 3/ <sub>16</sub>	10	3/8	1160	2552	580	1276	127	4.5
3	Towable Genoa car 2:1 purchase	22220	22220B	138	5 7/16	34	1 5/16	65	2 9/16	30	1 3/16	10	3/8	1160	2552	580	1276	160	5.6
TOWABL	E CAR END FITTINGS																		
4	Track end + becket	22221	22221B	80	3 1/8	32	1 1/4	47	17/8	30	1 3/16	8	5/16	-	-	-	-	99	3.5

#### **20MM T SECTION TRACK**

For use with all sliders featured on this page. Drilled for fastenings and plunger stops. Grey anodised and supplied in metric lengths.



w	Width	20mm (	(13/47")
• • •	vviatii	20111111	(10/16/
X	Width	11mm	(7/ <sub>16</sub> ")
Н	Height	8mm	(5/16")
J	Height	2.5mm	1 (1/8")









Plunger hole centres 50mm (2")







270g 307



For use with mainsheet or Genoa track sliders. Sold as single units.

#### BULLSEYE SLIDE 8



With a swivelling bullseye that will always accommodate the correct angle of sheeting. Accepts lines up to 14mm (9/16") diameter. A stainless steel insert is provided to prevent wear.

#### T SECTION TRACK, SLIDERS, GENOA CARS SUITABLE FOR BOATS 5m-8m (16'-26')

20MM T SECTI	20MM T SECTION TRACK SUITABLE FOR BOATS 5m-8m (16'-26')							
РНОТО NO	DESCRIPTION	PART NO						
5	Per metre	22000						
	0.6 metre	22010						
	1.2	22020						
	1.8	22030						
	2.4	22040						
	3.0	22050						
	5.0	22060						
6	Track End Cap (pair)	22901						

Black track is available. Add a B to the part numbers above for black anodised.

#### 



22300

13

Has a stainless steel eye fitted to a stainless steel loop, through-bolted for strength. The moulded plastic spring/gaiter prevents the block tumbling or ropes snagging. Supplied with a series 2 block accepting lines up to 8mm diameter.

#### GENOA SLIDE WITH PLUNGER 10



A robust unit which will accept most Barton blocks – with a stainless steel attachment loop, through-bolted for strength. Fitted with a plunger so the car can be held where required.

#### FAIRLEAD SLIDE 11



Features a plain moulded plastic fairlead fitted to an adjustable slide. Accepts lines up to 12mm diameter; not suitable for high loads.

#### FAIRLEAD SLIDE WITH CAM KIT 12



Features a plain moulded plastic fairlead and cam fitted to an adjustable slide. Accepts up to 12mm lines. Supplied as a handed pair; not suitable for high loads. The kit includes 40cm of track and end caps for each side of the boat.

#### MAINSHEET SLIDES 13



A strong car with a stainless steel attachment loop, through-bolted for strength. Will accept most Barton blocks.

GENOA (	CARS AND TOABLE GEN	IOA CARS																	
РНОТО	DESCRIPTION	PART NO SPECTRO	PART NO BLACK	LENG	тн	WIDT	'H	HEIG	нт	SHE	AVE Ø	MAX ROP		BREAK LOAD		SWL		WEIG	нт
NO		ANODISE	ANODISE	мм	INCH	ММ	INCH	мм	INCH	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	G	oz
7	Plunger stop	22900	22900B	30	1 <sup>3</sup> / <sub>16</sub>	32	1 1/4	30	1 <sup>3</sup> / <sub>16</sub>	-	-	-	-	-	-	-	-	30	1.1
8	Bullseye slide plunger system	22310	22310B	80	3 1/8	32	1 1/4	60	2 3/8	-	-	14	9/16	400	880	200	440	150	5.3
9	Stand up block plunger	22312	22312B	75	2 15/16	45	1 1/4	103	4 1/16	35	1 3/8	8	5/16	740	1628	370	814	145	5.1
10	Genoa slide plunger system	22301	22301B		2 3/8	32				-	-	-		1200	2640		1320	68	2.4
11	Fairlead slide plunger system	22311	22311B	90	3 9/16	32	1 1/4	42	1 5/8	-	-	12	1/2	400	880	200	440	102	3.6
12	Fairlead + cam (handed pair) plunger includes 40cm track	42102	42102B	400	15 3/4		3 <sup>13</sup> / <sub>16</sub>	40	1 9/16	-	-	12	1/2		-	-	-	732	25.8
MAINSH	EET SLIDER																		
13	Mainsheet slide	22300	22300B	60	2 3/8	32	1 1/4	35	1 6/16	-	-	-	-	1200	2640	600	1320	55	1.9

### **25mm T Section Track**

### PLAIN BEARING GENOA CARS, SLIDERS SUITABLE FOR BOATS 7m-10m (23'-33')

This sleek new range of Genoa cars and sliders is designed to run on 25mm (1") T track. All are manufactured from high quality marine grade aluminium with our Spectro anodise or black anodise finish for added protection. All cars and sliders featured on these pages have moulded nylon inserts to ensure, smooth running under load and prevent damage to finish or potential corrosion.

- Spectro or black anodised finish
- Stainless steel plunger stops with positive action
- Moulded nylon slide inserts ensure free running
- Large, easy grip plunger knobs with twist and lock up plunger facility

Cars and sliders are compatible with most makes of T track. This size track is suitable for 7m-10m (23'-33') cruising boats.


#### T SECTION TRACK, GT GENOA CARS



#### **GENOA CAR WITH PLUNGER STOP**



Features precision turned Ertalyte sheaves, designed with extra width to accept two sheets. The sheave axle is a riveted tube to reduce friction on the bearing.



#### **TOWABLE GENOA CAR**

With a tow eye and a sheave in place of the plunger, this allows a control line to be led aft as stop but 2:1 forward pull so that the Genoa car adjustments can be made from the cockpit. Use in conjunction with end fittings shown (25221GT).



РНОТО	DESCRIPTION	PART NO SPECTRO	PART NO BLACK	OVEF		BODY LENG	тн	WIDT	'H	HEIG	нт	SHEA	VE Ø	MAX ROPE	Ø	BREAK	LOAD	SWL		WEIG	нт
NO		ANODISE		мм	INCH	мм	INCH	ММ	INCH	ММ	INCH	мм	INCH	мм	INCH	KG	LBS	KG	LBS	G	oz
GENOA (	CARS AND TOWABLE	E GENOA CA	ARS																		
4	Genoa car plunger stop	25100GT	25100GTB	84	3 <sup>5</sup> / <sub>16</sub>	80	3 1/8	42	1 <sup>5</sup> / <sub>8</sub>	87	3 7/16	40	1 91/6	16	5/8	2280	5016	1140	2508	247	8.7
5	Towable Genoa car 2:1 purchase	25220GT	25220GTB	170	6 11/16	104	4 1/8	42	1 5/8	87	3 7/16	40	1 9/16	16	5/8	2280	5016	1140	2508	297	10.5
TOWABL	E CAR END FITTING	S																			
6	Towable track end + becket	25221GT	25221GTB	84	3 5/16	80	3 1/8	37	1 7/16	50	1 <sup>15</sup> / <sub>16</sub>	35	1 <sup>3</sup> / <sub>8</sub>	8	5/16	-	-	-	-	121	4.3

#### **25MM T SECTION TRACK**

For use with all sliders featured on this page. Drilled for fastenings and plunger stops. Grey or black anodised and supplied in metric lengths.





#### **GENOA AND MAINSHEET SLIDES**

Designed with a heavy duty stainless steel attachment loop, through-bolted and riveted for extra strength. These units will accept most Barton blocks.



#### **BULLSEYE SLIDE**

Features a swivelling bullseye that will always accommodate the correct angle of sheeting. The car has a stainless steel insert to prevent rope wear. Accepts lines up to 14mm (9/16") diameter.



#### STAND UP BLOCK WITH PLUNGER

Featuring a stainless steel eye fitted to a stainless steel loop, through-bolted for strength. The moulded plastic spring/gaiter prevents the block tumbling or ropes snagging. Two sizes are available – for 10mm (5/16") and 12mm (1/2") lines.

РНОТО	DESCRIPTION	PART NO	PART NO BLACK	OVE		BODY LENG		WIDT	Ή	HEIG	нт	SHEA	VE Ø	MAX ROPE		BREAK	LOAD	SWL		WEIG	НТ
NO			ANODISE	ММ	INCH	мм	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS	KG	LBS	G	oz
GENOA (	CARS AND TOWABLE	GENOA CAI	RS																		
7	Mainsheet slide	25300	25300B	84	3 1/3	80	3 1/8	42	1 5/8	42	1 5/8	-	-	-	-	2860	6292	1430	3146	111	3.9
8	Genoa slide plunger	25301	25301B	84	35/16	80	3 1/8	42	1 <sup>5</sup> / <sub>8</sub>	40	1 9/16	-	-	-	-	2860	6292	1430	3146	123	4.3
BULLSEY	E SLIDE																				
9	Bullseye slide plunger	25303	25303B	84	3 5/16	80	3 1/8	42	1 5/8	60	2 3/8	-	-	14	9/16	-	-	-	-	184	6.5
STAND U	P BLOCKS																				
10	Stand-up block – size 3 with plunger	25310	25310B	84	3 5/16	80	3 1/8	42	1 5/8	120	4 3/4	45	1 3/4	10	3/8	980	2156	490	1078	204	7.2
	Stand-up block – size 4/5	25311	25311B	84	3 <sup>5</sup> / <sub>16</sub>	80	3 1/8	42	1 <sup>5</sup> / <sub>8</sub>	142	5 9/16	45	1 3/4	12	1/2	1580	3476	790	1738	296	10.4
	Stand-up block + becket	25312	25312B	84	3 5/16	80	3 1/8	42	1 5/8	150	5 7/8	45	1 3/4	12	1/2	1580	3476	790	1738	300	10.6

#### **SLIDING CLEATS**



A cost effective solution to fitting a midship spring cleat where access on the side deck is limited – simply remove a Genoa track end stop, slide on the cleat and lock it in the desired position. When not in use, slide the cleat to one end of the track, or leave off one track end permanently to enable easy removal of cleat. Alternatively, fit a short length of track in the desired position so that cleats can be fitted when required and removed when not in use - reducing deck clutter and rope snags. 25mm cleats have an extruded aluminium base, nylon moulded cleat and screw type lock.

RUOTO NO	DESCRIPTION	PART NO SILVER	PART NO BLACK	CLEAT MATERIAL	LENGTH		T TRACK \	WIDTH	WEIGHT	
PHOTO NO	DESCRIPTION	ANODISE	ANODISE	CLEAT MATERIAL	мм	INCH	мм	INCH	G	oz
SLIDING CLEAT										
11	165mm sliding cleat	51253	51253B	Nylon	165	6 1/2	25	1	134	4.7
12	200mm sliding cleat	51254	51254B	Nylon	200					

#### **SPARE PARTS**

Barton believes in making equipment that lasts and can be serviced. Below are the part numbers for spares for the Genoa cars. Other parts are available on request.

PHOTO NO	DESCRIPTION	PART NO	SHEAVE	WIDTH	SHEAVE @		SHEAVE H	HOLE Ø	BEARING	HOLE Ø
			ММ	INCH	MM	INCH	ММ	INCH	мм	INCH
13	Replacement sheave & bearing for current style 25mm Genoa car (Black)	N25997	34	1 <sup>5</sup> / <sub>16</sub>	38.5		18.2	11/ <sub>16</sub>		-
14	Nylon Slider Insert for 25mm car – body length 104mm (4 1/8")	25998		13 N	125997	14	259	998		
	Nylon Slider Insert for 25mm car – body length 80mm (3 1/8")	25999	1					more to		
							4 4 12		1400	

### **32mm T Section Track**

#### T SECTION TRACK, SLIDERS, GENOA CARS SUITABLE FOR BOATS 9m-15m (30'-49')

The new sleek range features Genoa cars and sliders that are designed to run on 32mm (11/4") T track. All are manufactured from high grade aluminium with our unique Spectro anodised finish for added protection. Also available in black anodised finish – add 'B' to the end of the product code to order.

All cars and sliders featured on these pages have moulded nylon inserts to ensure smooth running and prevent damage to the anodised finish. Features precision turned Ertalyte sheaves with extra width to accept two sheets.

All Genoa cars in this range are available in a heavy duty version for larger craft or for larger load applications.

- Spectro or black anodised finish
- Stainless steel plunger stops with positive action
- Ertalyte sheave axle is a riveted tube to reduce friction
- Moulded nylon slide inserts ensure free running
- Large, easy grip plunger knobs
- Heavy duty Genoa car options

Cars and sliders are compatible with most makes of 'T' track. Modified slider inserts available for obscure track sizes. Please contact Barton Marine for further information.

PHOTO NO	DESCRIPTION	PART NO
	JITABLE FOR BOATS 9M-15M ( E ADD 'B' TO THE PART NUME	
1	Per metre	32000
	0.6 metre	32010
	1.2 metre	32020
	1.8 metre	32030
	2.4 metre	32040
	3.0 metre	32050
	5.0 metre	32060
TRACK END CAP (PAIR)		
2		32901



32900


32000

32901

#### 32MM T SECTION TRACK

For use with all sliders featured on this page. Drilled for fastenings and plunger stops. Grey or black anodised and supplied in metric lengths.














Plunger hole centres 50mm (2")







756g 8oz

РНОТО	DESCRIPTION	PART NO SPECTRO	PART NO BLACK	LENC	STH	WIE	TH	HEIG	НТ	SHE	AVE Ø	MAX ROPE (	ð	BREAK	LOAD	SWL		WEIG	нт
NO	J 2001 11011	ANODISE	ANODISE	ММ	INCH	ММ	INCH	ММ	INCH	мм	INCH	мм	INCH	KG	LBS	KG	LBS	G	oz
GENOA	CARS AND TOWABLE GENO	A CARS																	
3	Plunger stop	32900	32900B	35	1 3/8	42	1 5/8	40	1 9/16									70	2.5
4	Genoa car with plunger stop	32100GT	32100GTB	134	5 1/4	52	2 1/16	108	4 1/4	50	1 <sup>15</sup> / <sub>16</sub>	2 x16	2 x <sup>5</sup> / <sub>8</sub>	3280	7216	1640	3608	573	20.2
5	Genoa car – heavy duty with plunger stop	32101HD	32101HDB	155	6 1/8	52	2 1/16	117	4 5/8	60	2 3/8	2 x 16	2 5/8	5970	13134	2985	6567	728	25.7
6	Towable Genoa car 2:1 purchase	32210GT	32210GTB	134	5 1/4	52	2 1/16	110	4 <sup>5</sup> / <sub>16</sub>	50	1 <sup>15</sup> / <sub>16</sub>	2 x16	2 x <sup>5</sup> / <sub>8</sub>	3280	7216	1640	3608	561	19.8
7	Towable Genoa car 2:1 purchase – heavy duty	32211HD	32211HDB	155	6 1/8	52	2 1/16	117	4 5/8	60	2 3/8	2 x 16	2 5/8	5970	13134	2985	6567	820	28.9
TOWABL	E CAR END FITTINGS																		
8	Track end + becket	32221GT	32221GTB	115	4 1/2	52	2 1/16	43	1 11/16	32	1 1/4	10	3/8					236	8.3
MAINSH	EET/GENOA SLIDES AND STO	OPS																	
9	Mainsheet slide	32300	32300B	115	4 1/2	53	2 1/16	50	1 15/16					2980	6556	1490	3278	225	7.9
10	Genoa slide	32301	32301B	115	4 1/2	52	2 1/16	50	1 <sup>15</sup> / <sub>16</sub>					2980	6556	1490	3278	254	9
11	32mm Car with bullseye -internal hole 18mm	32303	32303B	115	4 1/2	53	2 1/16	66	2 5/8									304	10.7
STAND U	JP BLOCKS																		
12	Stand up block - size 4/5	32310	32310B	115	4 1/2	52	2 1/16	150	5 7/8	54	2 1/8	12	1/2	1800	1800	3960	900	440	15.5
	Stand up block - size 6	32311	32311B	115	4 1/2	52	2 1/16	165	6 1/2	60	2 3/8	12	1/2	2300	5060	5060	1150	472	16.6
	Stand up block - size 7	32312	32312B	115	4 1/2	52	2 1/16	178	7	72	2 13/16	14	9/16	2800	6160	6160	1400	555	19.6

#### **NYLON INSERTS FOR CARS**

Barton provides a spares service for the inserts for its range of Barton cars. We also provide 'milled' inserts. These milled inserts allow our 32mm cars to be fitted to older 32mm x 6mm track produced by other manufacturers.





PHOTO ID	DESCRII	PTION	PART NO	SHEAV	E WIC	отн	SHEAV OVERA			EAVE D ST	HOLE Ø YLE	BEARIN OLD ST	IG HOLE ( YLE	ا (		HOLE Ø YLE (No
				ММ	INCI	н	мм	INCH	мм		INCH	мм	INCH	ı	ММ	INCH
13		ment sheave and bearing for standard enoa Car	N32997	37	1 7/	<sup>/</sup> 16	50	1 15/16	13.3	3	1/2	8.3	5/16		18.2	11/16
	Replacement sheave and bearing for Heavy Duty 32mm Genoa Car		N32995	36.5	1 7/		60	2 3/8	19.4			10.2				
PHOTO N	0	DESCRIPTION				PART I					RT NO			LEN	NGTH O	F INSERT
11101011	J	BESCHII HOIV				FOR B	ARTON 5	MM TRACK		FO	R 32MM X 6	MM TRA	CK	ММ		INCH
14	4	Nylon Slider Insert for 32mm car – Body le	ength 109mm			32999				329	999M			109	>	4 5/16
		Nylon Slider Insert for 32mm car – Body le	ength 128mm			32998				329	998M			128		
		Nylon Slider Insert for 32mm car – Body le	ength 152mm			32996				329	996M			152	2	6

#### **GENOA CARS WITH** PLUNGER STOPS 4 & 5

Feature precision turned Ertalyte sheaves running on a large diameter bearing, for increased performance under load. Extra wide sheaves accept two sheets. The sheave axle is throughriveted on a stainless steel tube for extra strength (see p12 for set-up options).

#### **TOWABLE GENOA CARS** 6 & 7

With tow eye or sheave in place of plunger, allowing control line to be lead aft so that Genoa car adjustments can be made from

the cockpit. Use in conjunction with end fittings shown.

#### **GENOA AND MAINSHEET** SLIDES 9 & 10

With a heavy duty stainless steel attachment loop, through-bolted and riveted for extra strength. These units will accept most Barton blocks.

#### BULLSEYE SLIDE 11

Features a swivelling bullseye to always accommodate the correct angle of sheeting. The car has a stainless steel insert to prevent rope wear. Accepts lines up to 14mm (9/<sub>16</sub>") diameter.

#### STAND UP BLOCKS 12

Have a stainless steel eye fitted to a stainless steel loop, through-bolted for strength. The moulded plastic spring/gaiter prevents the block tumbling or ropes snagging. Three sizes are available - for lines up to 14mm.

#### SLIDING CLEATS 15

A cost effective solution to fitting a midship spring cleat where access under the side deck is limited - simply remove a Genoa track end stop, slide on the cleat and lock it in the

desired position. When not in use, slide the cleat to one end of the track, or leave off one track end permanently to enable easy removal of cleat. Alternatively, fit a short length of track in the desired position to enable cleat removal when not in use reducing deck clutter and rope snags. Sliding cleats are 150mm (6") in length manufactured in polished 316 stainless steel.



## T Track Spinnaker Pole Parts & Systems

#### **SPINNAKER POLE SLIDERS 25mm**

#### SPINNAKER POLE SLIDE

Features a heavy duty stainless steel ring welded to an attachment plate which is through-bolted to the slide. Generous ring opening to accept most pole ends. The plunger stop allows the slide to position on the track and locked in place.

#### **TOWABLE SPINNAKER POLE SLIDE**

Eyes are fitted to both ends of the slide for the attachment of control lines (6mm max). Used with 25221GT end fittings and cams 70100, allows the pole to be moved up and down with the control lines.



РНОТО	DESCRIPTION	PART NO SPECTRO	PART NO BLACK	LENGTH	1	WIDTH		HEIGHT		EYE INT	ERNAL	EYE INT Ø	ERNAL	WEIGHT	
NO		ANODISE	ANODISE	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	G	oz
SPINNAK	ER POLE SLIDES														
1	Spinnaker pole slide plunger	25302	25302B	84	3 5/16	42	1 5/8	93	3 11/16	50	1 15/16	70	2 3/4	273	9.6
2	Towable spinnaker pole slide	25304	25304B			42									10.0

#### **SPINNAKER POLE SLIDERS 32mm**



#### SPINNAKER POLE SLIDE


Has a heavy duty stainless steel ring welded to an attachment plate which is through-bolted to the slide. Generous ring opening to accept most pole ends.



#### **TOWABLE SPINNAKER POLE SLIDE**

Have eyes fitted to both ends of the slide for the attachment of control lines. Use with 32221GT end fittings (see p?? for setup options).

РНОТО	DESCRIPTION	PART NO SPECTRO	PART NO BLACK	LENGTH	1	WIDTH		HEIGHT		EYE INT Ø	ERNAL	EYE INTI Ø	ERNAL	WEIGHT	
NO		ANODISE	ANODISE	ММ	INCH	ММ	INCH	мм	INCH	ММ	INCH	ММ	INCH	G	oz
SPINNAK	(ER POLE SLIDES														
4	Spinnaker pole slide	32302	32302B	109	4 5/16	52	2 1/6	100	3 15/16	40	1 9/16	384	13.5	357	12.6
5	Towable spinnaker pole slide	32304	32304B	109	4 5/16		2 1/6			40			13.6	359	



"I have used Barton fittings for years. The reason is simple. They just never broke. So when it came to the two-handed Fastnet Race it was obvious I would go to Barton."

Chris Lewns
Barton Customer



# 19mm I Beam Track, Cars & Accessories



PHOTO NO	DESCRIPTION	PART NO	END FITTING	LENG	TH	WIDT	rh 	LOAD	· 	SWL		WEIG	SHT
NO.		NO	FITTING	ММ	INCH	ММ	INCH	КG	LBS	KG	LBS	G	oz
19mm TRA	VELLER CARS												
1	4 Wheel plain	19100	19900	52	2 1/16	38	1 1/2	1200	2640	600	1320	127	4.5
2	4 Wheels, control cleats + sheaves	19103	19902	122	4 13/16	75	2 <sup>15</sup> / <sub>16</sub>	1000	2200	500	1100	339	12
3	6 Wheels, control line + sheaves	19105	19902	85	3 3/8	38	1 1/2	2240	4928	1120	2464	283	10
19mm TRA	CK END FITTINGS (PAIR)												
4	Adjustable plunger stops (pair)	19900	-	29	1 1/8	32	1 1/4	-	-	-	-	30	1.1
5	Plastic track end (pair)	19901	-	20	13/16	39	1 9/16	-	-	-	-	8	0.3
6	End fitting - horizontal sheave (pair)	19902	-	82	3 1/4	22	7/8	-	-	-	-	22	0.8

PHOTO NO	DESCRIPTION	PART NO
	CTION TRACK FO TO 7.3m (24ft) LC	
7	Per metre	19000
	0.6 metre	19010
	1.2 metre	19020
	1.8 metre	19030
	2.4 metre	19040
	3.0 metre	19050
	5.0 metre	19060
5	Plastic track end cap (pair)	19901

#### 19mm I SECTION TRACK

Extruded with a hollow section for lightweight and high load capacity. Drilled for fastenings and plunger stops.

Supplied in metric lengths as shown in the table above.

W Width W
X Width X
H Height H
19mm
Fastenings Ø
5mm
Fastening centres
100mm
Plunger hole centres
50mm



# 24mm I Beam Track, Cars & Accessories



#### For yachts up to 10.7m (35ft) LOA.

A mid range traveller system, manufactured from marine grade aluminium and stainless steel. All feature heavy duty attachments. Control line blocks (where fitted) have low friction ball bearing sheaves, accepting lines up to 8mm diameter. I section track is silver anodised. Fittings are black anodised. End fittings are secured through track, with track fastening bolts.

- Heavy duty take off attachments
- Stainless steel captive bearing ball race wheels
- Ball bearing control line blocks
- End fittings give varied control line options
- Cam cleat versions feature `K cam' Kevlar cleats
- 6 Wheel Cars available to order



PHOTO NO	DESCRIPTION	PART NO	END FITTING	LENC	ЭТН	WID.	гн	BREAK LOAD		SWL		WEIGHT	
NO.		NO	FITTING	ММ	INCH	MM	INCH	KG	LBS	KG	LBS	G	oz
24mm TR	AVELLER CARS												
1	4 Wheel plain	26101	26900	69	2 11/16	47	1 7/8	2560	5632	1280	2816	257	9.1
2	4 Wheels, control line sheave	26102	26110	69	2 11/16	47	1 <sup>7</sup> / <sub>8</sub>	2560	5632	1280	2816	287	10.1
24mm TR	ACK END FITTINGS (PAIR)												
3	End fitting with sheave + cleat (pairs)	26110	-	90	3 9/ <sub>16</sub>	75	2 <sup>15/</sup> 16	-	-	-	-	426	15
	End fitting with double sheave + cleat (pairs)	26111			3 %16				-	-		483	17.0
4	Adjustable plunger stops (pairs)	26900	-	32	1 1/4	30	1 3/16	-	-	-	-	64	2.3
5	Plastic track end (pair)		-	-	-	-	-		-	-	-	20	0.7
6	Crash stop	26902	-	32	1 1/4	30	1 <sup>3</sup> / <sub>16</sub>	-	-	-	-	36	1.3

PHOTO NO	DESCRIPTION	PART NO
	TION TRACK FOF TO 10.7m (35ft) L	
7	Per metre	26000
	0.6 metre	26010
	1.2 metre	26020
	1.8 metre	26030
	2.4 metre	26040
	3.0 metre	26050
	5.0 metre	26060
5	Plastic track end (pair)	26901

#### 24mm I SECTION TRACK

Extruded with a hollow section for lightweight and high load capacity. Silver anodised drilled for fastenings and plunger stops.

Supplied in metric lengths as shown in the table above.

28mm

W Width W 24mm X Width X 16mm

**H** Height H

Fastenings Ø

5mm

Fastening centres 100mm Plunger hole centres 50mm



**₩** Weight per m

721g

## 28mm I Beam Track, Cars & Accessories

#### 28mm I SECTION TRACK & TRAVELLER

#### For yachts up to 12m (40ft) LOA.

A range of traveller systems for yachts up to 12m LOA running on our heavy duty track.

All feature heavy duty attachments, throughbolted for added security. Control line blocks (where fitted) have low friction ball bearing sheaves, accepting lines up to 10mm diameter. I section track is silver anodised. Fittings are black anodised.

End fittings are secured through track with track fastening bolts.

- Stainless steel captive bearing ball race wheels
- Rugged, lightweight I section track
- Cam cleat versions feature `K cam' Kevlar cleats
- End fittings give varied control line options
- Ball bearing control line blocks.
- Anodised in silver or black
- I section track can be custom curved to special requirements – see p56
- Other versions available



PHOTO NO	DESCRIPTION	PART NO	END FITTING	LENG				BREAK LOAD		SWL		WEIGHT	
NO		NO	FITTING	MM	INCH	ММ	INCH	KG	LBS	KG	LBS	G	oz
28mm TRA	28mm TRAVELLER CARS												
8	4 Wheel plain	28101	28900	88	3 7/16	54	2 1/8	2522	5548	1250	2750	438	15.5
9	4 Wheels, control line sheaves	28102	28110	88	3 7/16	54	2 1/8	2500	5500	1250	2750	472	16.6
28mm TRA	CK END FITTINGS (PAIR)												
10	End fitting with sheave, becket + cleat (pair)	28110	-	108	4 1/4	90	3 9/16	-	-	-	-	687	24.2
11	End fitting with double sheave, becket + cleat (pair)	28112			4 1/4		9 9/16	-				790	27.9
12	Adjustable plunger stops	28900	-	35	1 3/8	42	1 5/8	-	-	-	-	112	4
13	Plastic track end (pair)	28901	-	-		-	-	-		-	-	42	1.5
14	Crash stop (pair)	28902	-	35	1 3/8	42	1 5/8	-	-	-	-	76	2.7

PHOTO NO	DESCRIPTION	PART NO
	TION TRACK FOR TO 12m (40ft) LO	
15	Per metre	28000
	0.6 metre	
	1.2 metre	28020
	1.8 metre	
	2.4 metre	28040
	3.0 metre	28050
	5.0 metre	28060
13	Plastic track end (pair)	28901

#### 28mm I SECTION TRACK

Extruded with a hollow section for lightweight and high load capacity. Silver anodised drilled for fastenings and plunger stops.

Supplied in metric lengths as shown in the table above.

28110

 W
 Width W
 28mm

 X
 Width X
 17mm

 H
 Height H
 34mm

Fastenings Ø 6mm
Fastening centres 100mm
Plunger hole centres 50mm




**∭** Weight per m


1041g



# Sliding Roof, Seat & Furniture Track

Barton Sliding Car Systems provide exceptional performance for manual sliding assemblies. These systems feature an unrivalled combined surface height of only 20mm when using our 16mm x 9mm track construction. Barton systems use Delrin ball bearings to provide a cost-effective long-lasting sliding solution for harsh marine environments.







## Sliding System Modules

#### **SLIDING ROOF MODULE**





PHOTO NO	DESCRIPTION	PART NO
1	Complete roof car assembly	99701
2	Roof car beam support only for Tube with internal size of 18mm x 18mm	99701-01
3	M5 x C/S 35mm Screw 20mm extension above surface when installed	99701-02
4	Car Body only for 18000 track supplied with balls	99701-03



#### **TWIN STUD MODULE**






PHOTO NO	DESCRIPTION	PART NO
1	Complete twin stud assembly	99767
2	M5 x C/S 35mm Screw 20mm extension above surface when installed	99767-01
3	Twin Stud Car Body only for 18000 track supplied with balls	99767-02




## **Locking Modules**

#### **MANUAL PLUNGER**



#### **REMOTE PLUNGER**



**Barton DO 550 Clutches** 

For cruising and racing yachts up to 12m (40ft), offering a holding power of up to 550kgs (see chart below).

#### MODERN, HIGH PERFORMANCE MATERIALS

The DO 550's moulded parts are manufactured from high grade plastics which are strong, light and impact resistant. Cams and bases are from high grade aluminium, Spectro anodised for long life in the harsh marine environment.

#### TRUE CLUTCH MECHANISM

This true clutch mechanism allows lines to be adjusted through the unit in the closed, locked position with minimal slippage. Release under load is positive and requires little effort. The mechanism's opening and closing action is precise and easy to operate, even with cold, wet hands. A positive handle lock in the closed position is also featured.

#### KIND TO LINES

The clutch's cam and base, manufactured from high grade extruded aluminium, feature a specially tempered tooth design which allows for maximum grip with minimal slippage, whilst being kind to your lines. Stainless steel rope fairleads are fitted to both line entry and exit points; a feature which helps to prevent wear to both clutch and lines.

#### BOLT-TOGETHER CONSTRUCTION FOR STRAIGHTFORWARD SERVICING

The DO 550 clutch range features the advantage of a bolt-together construction which allows for ease of servicing and replacement of parts. A full range of components is available from your Barton stockist.

#### **ERGONOMICALLY DESIGNED HANDLE**

The handle is strong and easy to grip, with a positive smooth lock and unlock action. A unique feature of this tried and tested design is the removable insert on the top face of the handle. These inserts are available packaged separately with a selection for both cruising and racing yachts (see right).

#### **CHOOSING THE RIGHT FITTING**

Please view our suggested boat size table on p10-11, to assist you in making the correct choice when determining the appropriate size of fitting for your application.

#### 81540

'Cruiser' insert pack contains: main, Genoa 1, spin halyard 1, topping lift, spin pole up, spin pole down, blank.



РНОТО	DESCRIPTION	PART	LENGTH		WIDTH		HEIGHT		WEIGHT	
NO		NO	ММ	INCH	ММ	INCH	ММ	INCH	G	oz
DO 550 C	CLUTCHES									
1	Single DO 550 clutch	81500	133	5 1/4	38	1 1/2	68	2 11/16	343	12.1
2	Double DO 550 clutch	81501	133		65		68	2 11/16	544	19.2
3	Triple DO 550 clutch	81502	133	5 1/4	91	3 9/16	68	2 11/16	788	27.8



#### Important fitting notes: rope clutches

When fitting rope clutches ensure a fair lead straight through the clutch to prevent wear to side plates and/or reduced load capabilities. For best performance site clutch approximately 1ft (300mm) forward of the winch to ensure a fair lead both vertically and horizontally. Use Barton deck organisers

forward of the clutch to gain perfect alignment. Always use a bolt-through fastening with a suitable sealant. A drilling template is provided on our packaging for your convenience.

# SPECIFICATIONS Max holding capacity 550kg Rope capacity 8mm-12mm Hole centres 79mm Fastenings 6mm

#### PRINTED HANDLE INSERTS AND SPARE CLUTCH PARTS PART DESCRIPTION PRINTED HANDLE INSERTS 'Cruiser' handle insert pack (7 inserts) 81540 SPARE CLUTCH PARTS (SUPPLIED AS SINGLES PER CAM) Handle 81545 81547 'Racer' insert pack contains: reef 1, cunningham, reef 2, kicker, mainsheet, Replacement spring assembly 81549 Genoa furling, Genoa 2, spin halyard 2, backstay, outhaul, downhaul, blank.

Rope Clutches & Mast Base Organisers

#### **ROPE CLUTCHES**

Manufactured from high grade plastics and aluminium with Spectro anodised finish.

Even with the clutch locked down, the rope can be pulled through to increase tension and raise the sails. The clutch can be released when under load by lifting the arm to release the line.

This compact range is suitable for securing halyards and control lines on yachts up to approx 30ft - or for lighter duties on large craft (see p9 for setup options).

Locking levers come in grey, red and white and a set of marking stickers is included. Suitable for boats up to 10m. Please see our suggested boat size table on p6-7, to assist you in making the correct choice when determining the correct size of fitting for your application.



РНОТО	DESCRIPTION	PART NO	LENGTH		WIDTH		HEIC	ЭНТ	WEIGHT		
NO			ММ	INCH	ММ	INCH	ММ	INCH	G	OZ	
ROPE CLUTCH											
1	Single rope clutch	80500	107	4 3/16	28	1 1/8	62	2 7/16	250	8.8	
2	Double rope clutch	80501	107	4 3/16	54					16.9	
3	Triple rope clutch	80502	107	4 3/16	80	3 1/8	62	2 7/16	710	25.0	



#### **MAST BASE ORGANISER**

to N05090 double tang blocks

The Barton mast base organiser is finished in Spectro or black anodising for a long lasting finish. It accepts up to four double tang blocks mounted on individual stainless steel swivel posts, with just three deck fixing points.

The unit is fitted close to the mast base to accept halyards, reefing lines and topping lift to turn lines from a vertical fall to a horizontal pull. Designed to work in conjunction with our range of deck organisers, rope clutches and winches, doing away with the need to leave the cockpit when reefing, hoisting or lowering the mainsail (see p9 for set-up options).



											NO	5090, I	N05091	I, N150	90 an	d N150	<b>91</b> from	p24
PHOTO NO	DESCRIPTION	PART NO	LENGT	гн	WIDTH	ı	HEIGH	т	WEIGHT		SWL		BREAK LOAD		FIXING HOLE		SWIVEL POST	
			ММ	INCH	ММ	INCH	мм	INCH	G	oz	KG	LBS	KG	LBS	мм	INCH	мм	INCH
MAST BA	SE ORGANISER																	
4	Mast base organiser	81550	160	6 5/16	25	1	28	1 1/8	166	5.9	1540	3388	3080	6776	6	1/4	10	3/8
5	Mast base organiser – Black	81550B	160	6 5/16			28	1 1/8	166	5.9	1540	3388	3080	6776		1/4		3/8

N03090, N03091, N13090 and N13091 from p22

## Deck Organisers

#### Available in two sheave sizes and in 2, 3, 4, 5 and 6 sheave models.

Designed to lead control lines and halyards across the coach roof and back to the cockpit.

This range features aluminium construction with Spectro or black anodised finish. Sheaves are from moulded Acetal with hollow stainless steel rivets to allow easy and tidy fitting (see p9 for set-up options).

Size 1 Suitable for boats up to 10m (33')

Size 2 Suitable for boats up to 14m (46')

SPECIFICATIONS	(SIZE 1)	SIZE 2
Sheave Ø Sheave width	32mm 17mm	44mm 18m
Hole centres	43mm	58mm
Fastenings	6mm	8mm
Max line Ø	12mm	14mm



#### **COMPACT ORGANISER**

Ideal where space is at a premium and you need a compact deck organiser. Features 32mm sheaves and 43mm hole centres for 6mm bolts, but does not have the curved end drops. Suitable for up to 12mm rope.



PHOTO NO	DESCRIPTION	PART NO SPECTRO	PART NO BLACK	LENGTH		ALUMINIUM WIDTH		HEIGHT		WEIGHT	
		ANODISE	ANODISE	ММ	INCH	мм	INCH	ММ	INCH	G	oz
SIZE 1 DECK OR	GANISER										
1	2-sheave	81582	81582B	115	4 1/2	28	1	23	15/16	86	3.0
2	3-sheave	81583	81583B	157	6 <sup>3</sup> / <sub>16</sub>	28	1 <sup>1</sup> / <sub>8</sub>	23	<sup>15/</sup> 16	122	4.3
3	4-sheave	81584	81584B	205	8 1/16	28	1 1/8	23	15/16	157	5.5
4	5-sheave	81585	81585B	245	9 5/8	28	1 1/8	23	<sup>15/</sup> 16	192	6.8
5	6-sheave	81586	81586B	287	11 <sup>5</sup> / <sub>16</sub>	28	1 <sup>1</sup> / <sub>8</sub>	23	15/16	226	8.0
6	Replacement Sheave (grey)	N64803	-	32	1 1/4	11	<sup>7/</sup> 16	17	11/ <sub>16</sub>	11	0.4
SIZE 2 DECK OR	GANISER										
	2-sheave	81682	81682B	155	6 1/8	38	1 1/2	28	1 <sup>1</sup> / <sub>8</sub>	169	6.0
7	3-sheave	81683	81683B	210	8 1/4	38	1 1/2	28	1 1/8	237	8.4
8	4-sheave	81684	81684B	270	10 <sup>5</sup> / <sub>8</sub>	38	1 1/2	28	1 <sup>1</sup> / <sub>8</sub>	310	10.9
	5-sheave	81685	81685B	325	12 <sup>13/</sup> 16	38	1 1/8	28	1 1/8	379	13.4
	6-sheave	81686	81686B	385	15 <sup>3</sup> / <sub>16</sub>	38	1 1/2	28	1 1/8	450	15.9
9	Replacement Sheave (grey)	N64808	-	44	1 3/4	13	1/2	20	13/16	26	0.9
10	2-Sheave Compact	81581	81581B	75	2 15/16	28	1 1/8	23	7/8	65	2.3

## **Barton Composite Winches**



#### **BARTON COMPOSITE WINCHES**

A versatile alternative to conventional steel winches, the Barton range of composite winches offers significant cost and weight savings and are truly low maintenance. Virtually self-lubricating, friction-free and corrosion resistant, the ingenious use of advanced materials ensures consistent performance and reliability. The composite drum has a 'moulded in' stainless steel insert for wear resistance.

- Three models available a single-speed 8:1 and two twin-speeds;
   16:1 and 23:1
- Suitable as primaries for yachts up to 10m (30ft) or as spinnaker/ halyard winches on larger craft
- Red, blue and green coloured top rings are included, giving you the ability to colour-code winches to control lines, port or starboard, or just to match the colour scheme of your boat
- Comprehensive spares kits available.

See p12 for setup options and p10-11 for our suggested boat size table designed to help you clarify the correct size of winch for your application.

РНОТО	I DESCRIPTION I	PART	BASE (	o .	DRUM	Ø	WEIGHT	
NO		NO	ММ	INCH	ММ	INCH	G	oz
SHEET W	INCHES							
1	Single speed 8:1	21200	101.6	4	66.7	2 5/8	835	29.5
2	Twin speed 16:1	21201	114.3		66.7	2 5/8	1264	44.6
3	Twin speed 23:1	21202	114.3	4 1/2	66.7	2 5/8	1565	55.2
4	Snubbing winch	21101	75	2 <sup>15/</sup> 16	50	1 <sup>15/</sup> 16	230	8.1
SERVICE	KIT							
	Single speed 8:1 for 21200	21210	-	-	-	-	106	3.7
6	Twin speed 16:1 for 21201	21211						3.5
	Twin speed 23:1 for 21202	21212	-	-	-	-	100	3.5
7	Set of 7 pawls and springs	21200-04						-
5	Spare set of colour-coded tops	21200-03	-	-	-	-	-	-



#### WINCH TECHNICAL SPECIFICATION

 SWL/WLL
 325kg (717lbs)

 FAILURE LOAD
 650kg (1433lbs)

 Fixings 21200
 6 x M6 @ Ø70mm

 Fixings 21201
 6 x M6 @ Ø80mm

 Fixings 21202
 6 x M6 @ Ø80mm

#### **BARTON WINCH SERVICE KITS**

Barton winches are fully serviceable and individual spares are available. To maximise the performance of your winch, regular service is recommended. A standard service kit is available for each winch. Each kit contains replacement springs and pawls, roller bearings, spiral top retainer, nylon washers and circlips.



#### **SNUBBING WINCH**

Neat, lightweight unit which is ideal for use on larger dinghies and dayboats. Manufactured from glass fibre reinforced nylon with anodised aluminium ribs.



## The Barton Wincher

A specially designed rubber moulding which fits over the top of standard winches, converting them to self-tailing.

This simple operation works when the line is sheeted under load, which means the coils climb up the winch drum and then become gripped by the underside of the Wincher's rubber body.

Cleating is achieved by locking the sheet into the Wincher's ribbed central groove.

The Barton Winchers are easy to fit and available in four sizes to suit a wide range of popular winches. Full fitting instructions are included - see videos on www.bartonmarine.com

21642



21643

#### **TIPS FOR USE**

As the photo (right) shows the drum must be fully wound with rope so that the rope is being pushed up from the bottom and forced in to the Wincher at the top. This action creates a self-tailing function. The groove in the Wincher is for cleating off only and is not used during winching operations.





Ready to winch



Locked off

PHOTO NO	DESCRIPTION			TOP FLANGE OF WINCHER UNSTRETCHED Ø (ACTUAL MEASUREMENT)		MAX DRUM Ø		MAX ROPE Ø		
			мм	INCH	ММ	INCH	ММ	INCH	G	OZ
BARTON 'WINC	:HERS'									
	Wincher small (pair)	21641	98	3 7/8	64-70	2 1/4 - 2 3/4	8-10	5/16 - 3/8	202	7.1
	Wincher medium (pair)	21642	102	4	70-80	2 3/4 - 3	10-14	3/8 - 1/2	223	7.9
2	Wincher large (pair)	21643	120	4 3/4	80-90	3 - 3 1/2	12-14	1/2 - 9/16	278	9.8
	Wincher extra large (pair)	21644	130	5 1/8	90-100	3 1/2 - 4	12-16	1/2 - 5/8	387	13.7
BARTON WINC	H SPARE SPRINGS									
3	V-Springs – suitable for a range of archive Barton and other manufacturers' winches. Arms approximately 25mm (1") long	60125	_	_	_	-	_	_	_	-
4	S-Springs – suitable for a range of archive Barton and other manufacturers winches.	60124	-	-	-	-	-	-	-	-











Barton Winchers will NOT fit the following: Anderson 10, 40, 18:2 speed; Barient 18, 19, 24, 28; Barbarossa 40, Arco 40; Lewmar 6, 55; Barlow 19, 24, 25, 28, 30.

## Winch Handles & Accessories

#### A range of light duty winch handles and accessories.

All designed to fit international star sockets and standard deck filler caps.

#### **EXTRUDED ALUMINIUM HANDLES**

Light duty, inexpensive handles in two lengths. Both styles have easy-grip roller handles and anodised finish.



Featuring a moulded body with an integral moulded handle shaft. Locking mechanism has a positive, easy action thumb switch.

#### Important note

Floating winch handles have a SWL of 40kg (88lbs) and are intended for lightweight use only.



21050

#### **HANDLE POCKET**

**FABRIC WINCH** 

Manufactured from hard wearing synthetic flexible sail cloth fabric. It is ideal where you need the winch handle pocket to fold out of the way when not in use. Manufactured with three stainless steel mounting eyelets.



65mm -105mm

#### **PVC WINCH** HANDLE POCKET

Manufactured from flexible dip moulded PVC to enable a wide range of handle types to be stored quickly and securely. Includes draining hole at base.



#### COMPACT WINCH HANDLE MOUNT

Manufactured from a tough moulded plastic with a rounded design to reduce snagging this mount is a safe way to securely store a locking winch handle.



#### **REEFING GEAR HANDLE**

For use with the nowdiscontinued '323' roller reefing gear. 8mm square end. While stock lasts.

РНОТО	DESCRIPTION	PART NO	LENGTH		WEIG	нт
NO	DESCRIPTION	PART NO	ММ	INCH	G	oz
ALUMINIUM	WINCH HANDLES					
1	8" Aluminium handle	21001	225	8 7/8	290	10.2
2	10" Aluminium handle	21002			335	11.8
FLOATING W	VINCH HANDLES					
3	8" Floating handle - locking	21034	235	9 1/4	267	9.4
4	10" Floating handle - locking	21033	290		300	10.6
SPECIAL HAI	NDLES					
5	Reefing gear handle	21323	170	6 11/16	160	5.6
WINCH HAN	DLE POCKET					
6	Fabric winch handle pocket	21050	295	11 <sup>5</sup> / <sub>8</sub>	50	1.8
7	Moulded PVC winch handle pocket	21053	325	12 <sup>13</sup> / <sub>16</sub>	253	8.9
8	Deck/Bulkhead mount for winch handle	21055	ø52 x 25	ø2 x 1	21	0.7
	nancie					

21323

# Stanchion Lead Blocks & Accessories





#### SINGLE STANCHION LEAD BLOCKS

Mainly used for leading headsail furling lines aft from single line furlers, Barton stanchion blocks are available in three sizes to suit most applications and rope sizes. The block is constructed from the latest advanced materials, using 30% fibreglass-filled nylon and Acetal sheaves.

A larger size 5 block should be used for final take off, especially if the furling line is to be lead to a winch.

All stanchion blocks are available with either plain or ball-bearing sheave.

		Barten bartonmarine.com	RACE bartonmarine.com	or ball-bearing sheave.							
РНОТО	DESCRIPTION.	PART NO	PART NO	SHEAVE	Ø	MAX LINI	ΞØ	MAX TUBE Ø			
NO	DESCRIPTION	PLAIN BEARING SHEAVE	BALL BEARING SHEAVE	MM INCH		ММ	INCH	ММ	INCH		
1	Single stanchion - Size 2	N02190	N12190	35 1 <sup>3</sup> / <sub>8</sub>		8	<sup>5</sup> / <sub>16</sub>	25	1		
2	Single stanchion - Size 3	N03190	N13190	45	45 1 3/4			25	1		
3	Single stanchion - Size 5	N05190	N15190	58 2 <sup>5</sup> / <sub>16</sub>		12	1/2	25	1		



#### **DOUBLE STANCHION LEAD BLOCKS**

Mainly used for leading headsail furling lines aft from continuous line furlers or where a vessel has twin headsails on single line furlers. Barton stanchion blocks are available in three sizes to suit most applications and rope sizes. The block is constructed from the latest advanced materials, using 30% fibreglass-filled nylon and Acetal sheaves

A larger size 5 block should be used for final take off, especially if the furling line leads to a winch. All stanchion blocks are available with either plain or ball-bearing sheave.

		Barten bartonmarine.com	bart®n RACE bartonmorine.com						
РНОТО	DESCRIPTION	PART NO	PART NO	SHEAVE	Ø	MAX LINE	ΞØ	MAX TUBE Ø	
NO	DESCRIPTION	PLAIN BEARING SHEAVE	BALL BEARING SHEAVE	ММ	INCH	ММ	INCH	ММ	INCH
4	Double stanchion - Size 2	N02290 N12290		35	1 3/8	8	<sup>5</sup> / <sub>16</sub>	25	1
	Double stanchion - Size 3	N03290	N13290	45		10		25	
	Double stanchion - Size 5	N05290	N15290	58	2 5/16	12	1/2	25	1



#### DOUBLE STANCHION LEAD WITH REMOVABLE SHEAVES BLOCKS

Ideal for continuous line furling systems as the sheaves can be removed to allow the line to be installed without the need to splice on board. The sheaves are retained with a stainless steel clevis pin and split ring. All stanchion blocks are available with either plain or ball-bearing sheave.

		Barten bartonmarine.com	bart®n RACE bartonmarine.com							
РНОТО	DECODINE ON	PART NO	PART NO	T NO SHEAVE Ø			ΞØ	MAX TUBE Ø		
NO	DESCRIPTION	PLAIN BEARING SHEAVE	BALL BEARING SHEAVE	мм	INCH	мм	INCH	ММ	INCH	
5	Double stanchion - Size 2	N02290R	N12290R	35	1 3/8	8	5/16	25	1	
	Double stanchion - Size 3	N03290R	N13290R			10	3/8	25	1	
	Double stanchion - Size 5	N05290R	N15290R	58	2 5/16	12	1/2	25	1	

#### 60142

#### STANCHION BULLSEYE

Designed to fit stanchions or pushpit/pullpit with 25mm (1") tubes. Fits in seconds and features soft nylon jaws that will not damage the tube. Constructed with stainless steel 316 fasteners.

РНОТО NO	DESCRIPTION	PART NO	INTERNAL D	IAMETER
			мм	INCH
6	Stanchion bullseye	60142	17	11/16

#### 52100



#### STANCHION CLEAT

Designed to fit stanchions or pushpit/pullpit with 25mm (1") tubes. Fits in seconds and features soft nylon jaws that will not damage the tube. Constructed with stainless steel 316 grade fasteners.

PHOTO NO	DESCRIPTION	PART NO	DESIGNED FOR STANCHION SIZE					
			мм	INCH				
7	Stanchion cleat	52100	25	1				

#### STANCHION LOW FRICTION RING BULLSEYE



This new design features Barton's super smooth hard anodised finish 60452 Low Friction Ring (High Load Eye) mounted within a metal retaining rod covered in a Dyneema effect durable strap, through-bolted onto a fully enclosed backing plate for a clean finish.

Lightweight, easy to fix in place and provides excellent line support. Will fit stanchion diameters up to 32mm with an overall effect that is visually stunning. 'Endurance restyled'.

PHOTO NO	PART NO	LENGTH		BORE Ø		WIDTH		TUBE SIZE		
		ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	
	8	60150	79	3/ <sub>18</sub>	16	5/8	54	2 1/8	25-32	1-1 1/4

#### N02591





This stanchion block has a cam cleat built into the design to save the need for a cleat in your cockpit or side deck. Installation is quick and simple and fits onto a standard 25mm (1") guard rail stanchion. Adjustment is easy with the stainless steel clamping ring which allows mounting of the block at any angle.

РНОТО	PART NO	LENGTH		MAXIMUM	LINE Ø	WIDTH		TUBE SIZE		
NO		мм	INCH	ММ	INCH	ММ	INCH	ММ	INCH	
9	N03591	110	4 11/16	8	5/ <sub>16</sub>	70	2 3/4	25	1	
	N03591	130	5 1/8	10	3/8	107	4 3/16	25	1	
	N05591	230 9 1/16		12	9/16	125	4 15/16	25	1	





#### STANCHION RATCHET BLOCK

This Stanchion Ratchet Block is ideal for reducing some of the loading for the crew when furling in the jib. The ratchet means that the sheave can be locked in place in one direction offering a friction brake against the pull of the sail. It is quick, simple and fits onto a standard 25mm (1") guard rail stanchion. Adjustment is easy with the stainless steel clamping ring which allows mounting of the block at any angle.

	PHOTO P	PART NO	LENGTH		MAXIMUM	LINE Ø	WIDTH		TUBE SIZE		
ı	NO		мм	INCH	ММ	INCH	ММ	INCH	мм	INCH	
	10	60160	120	4 3/4	10	3/8	55	2 3/16	25	1	

## **Continuous Line Furler**

#### **BARTON HBT1 FURLER SIZE 1**

42340

Barton has incorporated the latest Hybrid Bearing Technology to create a continuous line furler featuring the latest solid state bearings combined with Torlon ball bearings, resulting in a smooth and low friction drum that rotates with greater loads more effectively. Superior friction reduction is achieved using PTFE anodised coating.

The tri-grip furling drum has superb grip on the furling line. Manufactured with an aluminium body and load-bearing mandrel with a 316 stainless steel shaft so the static loading on this small compact furler is very high. The tri-grip furling drum is manufactured with reinforced plastic for durability and endurance.

Designed for sailors who want performance and style. This compact unit is ideal for dinghies and day boats. It is geared to give optimal furling speed, without making the unit large and heavy.

The anodised aluminium body delivers strength and durability in the most harsh environments.

New larger size available soon.

Contact sales@bartonmarine.com for more information.



Please scan the QR code for full information



- PTFE anodised aluminium body
- Stainless steel 316 central drive shaft
- Hybrid Bearing Technology
- Suitable for furling lines 4mm-6mm (3/16"-1/4")
- Furling line can be installed without disassembly
- Low weight compact design 195g / 6.2oz

### HBT1 ingenuity – endurance restyled

DESCRIPTION	PART NO	LENGTH OVERALL		LENGTH PIN TO PIN		PIN DIA		MAXIMUM SAIL AREA		BREAK LOAD		WORKING LOAD LIMIT		DRUM DIA.		OVERALL DIA.	
	NO	ММ	INCH	мм	INCH	мм	INCH	M.SQ	FT.SQ	KG	LBS	KG	LBS	мм	INCH	мм	INCH
HBT1 CONTINUOUS LINE F	URLER																
Hybrid bearing technology continuous line furler for small boats	42340	90	3 9/16	65	2 9/16	6	1/4	12	130	1200	2640	600	1320	50	2	68	2 11/16

## Single Line Furler







42336

Single line operation for dinghies, dayboats and light cruising yachts – two drum sizes work with a common top head swivel. All have stainless steel ball races for smooth operation.

Drums are moulded from glass fibre reinforced nylon with stainless steel swivel and ball bearing assemblies.

The top head swivel is constructed from machine turned solid aluminium with stainless steel ball bearings.

Designed to enhance style and increase performance.

- Three-point line retention.
- Invisible easy furling line attachment.
- Furling line guides to eliminate line drop.
- Drum has deck pin size 5mm and sail (top) pin size 6mm for increased strength.

These drums are fitted on new boats around the world by boat builders and design engineers.




PHOTO DESCRIPTION  FURLING GEAR	DESCRIPTION	PART NO	DRUM Ø	)	MAXIMI LINE SIZ		SAIL		BREAK	LOAD	SWL		PIN TO CENTRE		WEIGHT	Г
			ММ	INCH	ММ	INCH	M/SQ	SQ/FT	KG	LBS	KG	LBS	ММ	INCH	G	oz
1	Small furling drum	42334	76	3	5	3/16	5.6	60	1108	2437	554	1218	61.5	2 7/16	218	7.7
2	Large furling drum	42335	95	3 3/4			9.3		1108	2437	554	1218	72.5	2 7/8	281	9.9
3	Top swivel	42336	25	1			9.3	100	1108	2437	554	1218	43.5	1 11/16	55	1.9

## Lazy Jack Kits & Mast Step

Lazy Jacks allow mainsails to be dropped with ease, by retaining the sail between lines running from the mast (near the hounds) to the boom. These lines can be slackened while sailing to avoid restricting sail shape.

A unique feature of Barton Lazy Jack Kits is the soft plastic block covers which prevent sail chafe and enhance appearance.

# No modifications to sail, mast or boom required 1 41140

#### KITS CONTAIN:

- High quality braided line
- High quality cheek blocks
- Adjustment cleat
- Stainless steel pad eyes
- Full instructions

PHOTO NO	DESCRIPTION	PART NO							
LIGHTWEIGHT LAZY JACK KITS									
1	For yachts up to 9m (30ft)	41140							
2	Cascade system for yachts up to 10.5m (35ft)	41143							


These all-rope kits feature our unique block covers and are intended for yachts up to 9m (30') or lightweight use.

Not recommended for large yachts or fully battened mains. We also recommend that the use of a topping lift is retained.

#### **CASCADE LAZY JACK KITS**

For use with longer boom lengths or where more sail control is required and are intended for yachts upto 10.5m (35').

Blocks, cleats, mounting eyes and fixings included in the kit.





#### **PVC BLOCK COVERS IN WHITE**

PHOTO NO	DESCRIPTION	PART NO	DIAM AT B	METER ASE	LENGTH TO BLOCK SHOULDER						
			ММ	INCH	MM	INCH					
PVC CHA	PVC CHAFE COVERS FOR BLOCKS										
3	Block Cover for Size 2 blocks	41160	40	1 1/2	50	2					
	Block Cover for Size 3 blocks	41161									
	Block Cover for Size 5 blocks	41162	65	2 1/2	80	3					

Made from UV stable white plastic, these covers are designed to stop UV degradation of the rope in the top of the blocks. Supplied as part of the Lazy Jack Kits. Can be used in a range of positions to prevent wear and damage.



#### **MAST STEP**




Reefing Kits & Hooks

#### **SLAB REEFING KITS**

Supplied with sliding blocks which are held in place with spring-loaded plungers. Manufactured from stainless steel and anodised aluminium. Available in two sizes and complete with a length of T track and end caps.

#### SINGLE LINE REEFING KIT

A boxed complete single line reefing kit that allows reefing lines to be led aft to the safety of the cockpit. This system makes reefing your mainsail a quick and easy operation – just lower the main to a predetermined mark on the halyard, tension the reefing line and re-trim the sail.



			0
PHOTO NO	DESCRIPTION	SPECIFICATION	PART NO
SINGLE LI	NE REEFING KIT		
3	For yachts up to 9m (30ft)	Complete set with all parts and fixings required plus full fitting instructions. All you need to provide is a line and a cleat or stopper.	41130
SLAB REE	FING KIT		
4	For yachts up to 8.5m (28ft)	Supplied with 60cm of 25mm anodised `T´ track and 2 cars (Maximum 8mm rope)	41483
	Spare slider for above		41484
5	For yachts up to 12m (40ft)	Supplied with 100cm of 32mm anodised `T´ track and 3 cars (Maximum 12mm rope)	41496
	Spare slider for above		41497



#### **REEFING HOOKS**

Also known as cringle hooks, these are available in two types.

Manufactured in stainless steel, both types of hook are used in conjunction with slab reefing kits for securing the mainsail tack. Type 41517 is supplied as a pair to be riveted or bolted to either side of the boom at gooseneck level for attaching the tack of the sail to when reefing.

Type 41518 can be pinned above the gooseneck or used at the stemhead to accept a job tack.



#### **BOOM OUTHAUL TRAVELLER KITS**

DESCRIPTION	PART	MAX ROPE DIA		
	NO	ММ	INCH	
BARTON MARINE BOOM OUTHAUL TRAVEL	LER KITS			
Size 2 Traveller for Boom Outhaul Size 5	24400	12	1/2	
Size 2 Traveller for Boom Outhaul Size 6	24401	12	1/2	
Size 2 Traveller for Boom Outhaul Size 7	24402	14	9/16	



Designed for fitting onto an existing boom profile with the lugged screwed fasteners. Purchased as a standard kit which comes with fixings, end caps, track and block, or purchase individually to create a custom fit for your boat. For use within mast furling mainsails.

#### OUTHAUL CAR WITH BLOCK ONLY

DESCRIPTION	PART	MAX ROPE DIA					
	NO	ММ	INCH				
OUTHAUL CAR WITH BLOCK ONLY							
Boom Outhaul kit Size 5, 2.4m track	24905	12	1/2				
Boom Outhaul kit Size 6, 3.0m track	24906	12	1/2				
Boom Outhaul kit Size 7, 3.0m track	24907	14	9/16				

Suitable for use with the Size 2 track Part No 24000 to 24060 (0.6m to 5m Lengths).

#### FITTING SLUGS FOR BOOM

#### 24905SK

- Pack of 10 Slugs
- Recommended spacing is 1 every 100mm (4in)
- Size Slug 40mm x 10mmScrew M6 x 25mm (1in)

Mounting slugs can be used to fit other equipment into mast tracks. Made in anodised aluminium with a stainless steel M6 fastener



## Boom Vang Systems

(Handy Billies)

#### 4:1 & 6:1 BOOM VANG SYSTEMS

Upgrade your existing vang system or use as a boom preventer. Snap shackle fixings allow for quick and easy deployment. Professionally spliced and assembled. These can be used as Handy Billies.









#### 02900 - Size 2 4:1 Vang System, Swivel Head For Boats up to 6.1m/20'

Comprises: N02631 fiddle block with swivel shackle, becket and cam and N02430 fiddle block with swivel shackle.

6.1m (20ft) of 8mm (5/16") braided polyester line with soft eye.

SWL		LENGT	Ή	HEIGH	т	WIDTH		WEIGHT		
KG	LBS	мм	INCH	ММ	INCH	ММ	INCH	KG	LBS	
370	815	400	15 <sup>3</sup> / <sub>4</sub>	40	1 9/16	80	3 1/8	0.6	1.5	

#### 03900 - Size 3 4:1 Vang System, with Snap Shackles For boats up to 7.6m/25'

Comprises: N03641 fiddle block with swivel snap shackle, becket and cam and N02440 fiddle block with swivel snap shackle.

7.3m (24ft) of 8mm (5/16") braided polyester line with soft spliced eye.

SWL		LENGT	н	HEIGHT WIDTH WI		WIDTH		WEIGH	IT
KG	LBS	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
400	880	400	15 3/4	70	2 3/4	100	3 15/16	0.8	1.12

#### 03901 - Size 3 6:1 Vang System, with Ball Bearings, Locking Carabiner with bar For any size of boat

Comprises: N13531 fiddle block with becket and cam and N13330 fiddle block.

32m (104ft) of 8mm (5/16") braided polyester line, spliced and ready to use.

SWL		LENGT	Ή	HEIGH	т	WIDTH		WEIGHT		
KG	LBS	мм	INCH	ММ	INCH	ММ	INCH	KG	LBS	
400	880	42	16 <sup>9</sup> / <sub>16</sub>	21	8 1/2	9	3 9/16	2.1	4.62	

#### 05900 - Size 5 4:1 Vang System with Snap Shackles For boats up to 10.7m/35'

Comprises: N05641 fiddle block with swivel snap shackle, becket and cam and N05440 fiddle block with swivel snap shackle

12.2m (40ft) of 10mm (3/8") braided polyester line with soft spliced eye.

SWL		LENGT	н	HEIGH	т	WIDTH		WEIGHT		
KG	LBS	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS	
750	1650	490	19 5/ <sub>16</sub>	90	3 9/16	140	5 1/2	1.8	4	



## BOOMSTRUT

#### **EIGHT SIZES TO SUIT YACHTS UP TO 12M/40FT LOA**

Barton's Boomstruts feature a flexing spring design that provides fast response and a constant force for vang efficiency. Available in two fitting arrangements – 'Sliding Pin' for traditional booms and 'Webbing Cradle' for rotating booms.

The Boomstrut's lightweight, low-profile design features two flexible coated fibreglass rods which provide the force to support the boom. Pulling the boom down with a conventional kicker causes the Boomstrut to flex; releasing straightens the rods, thereby lifting and supporting the boom.

#### Maintenance-free, durable design

Eliminates friction and sliding parts.

#### Improved performance

Less weight and windage than competive gas and spring systems.

#### Easy installation

There's no need to replace your existing hardware - the Boomstrut mounts independently inside the existing kicking strap tackle.

#### Simple to follow instructions

The Boomstrut is supplied with complete fitting instructions and more details are available on our website www.bartonmarine.com

#### Mast fitting can use existing luff groove

To eliminate drilling, the Boomstrut's mast bracket can be slotted into your mast's luff groove.

#### Contoured boom fitting

The Boomstrut's boom bracket is contoured to fit both round and flat boom profiles.

#### Carefully designed and constructed

Barton Boomstruts have been carefully designed and constructed to eliminate sharp edges, minimise parts and provide trouble-free installation and use. All parts are from high-grade stainless steel and black or Spectro anodised aluminium for good looks and durability. Spare parts available.






#### **ENHANCED SAILING PERFORMANCE**

The Boomstrut is fitted to new yachts by manufacturers to provide enhanced sailing performance. The uplift provided by the Boomstrut means the sail shape can be managed and controlled to suit the conditions. Even in light winds the weight of the boom and shape of the sail is controlled for optimum performance.

- Improved control of sail shape
- Never again will your boom fall accidentally
- Easy to adjust and no hang-ups
- No topping lift hassles
- Available with black or white rods, anodised Spectro or black





"Easy to fit, simple to use and maintenance free...the Barton Boomstrut with its black anodised finish represents a cool, discrete contrast to the flashy chrome of other suppliers." Paul Durkin *Barton Customer* 

#### **WEBBING CRADLE**

#### Maintenance free | Fits in minutes | No drilling required

With no extra parts or drilling required, the Webbing Cradle Boomstrut is simply tied off at the mast to secure in place, negating the need for drilling. At the top of the rods, a fully adjustable Webbing Cradle supports the boom and as the cradle is not directly attached to the boom, it does not restrict the boom from rolling around its central axis to follow the sail when reefing.

Class approved for Folk Boats and Dragons. It is an ideal solution for dinghies and larger boats that have roller boom furling. To see a full list of yachts fitted with our Boomstrut please go to <a href="https://www.bartonmarine.com/">www.bartonmarine.com/</a> products-boomstrut-boats-fitted.asp. For a comprehensive range of spare parts please visit: <a href="https://www.bartonmarine.com/products-boomstrut-fitting-instructions.asp">www.bartonmarine.com/products-boomstrut-fitting-instructions.asp</a>

#### Ideal for:

- Sailing schools
- Training boats
- Trailer sailors

- Cruising dayboats
- Boats with roller boom furling
- Racing boats







#### **SPECIFYING YOUR BOOMSTRUT**

Ensure that the Boomstrut has enough power to lift the boom, the sails and all lines used when sailing. By weighing the tip of the boom (as shown left) an accurate selection can be made. Other factors include the available space inside the triangle created by the kicking stap/vange, boom and mast.

Rods can be cut down to length as noted within the table below.

Full technical support is available at www.bartonmarine.com or please send us an email at sales@bartonmarine.com

Max tip weight

SUGGESTED BOAT LENGTH	PART NO WHITE RODS	PART NO BLACK RODS	MAX TIP WEIGHT INSTALL BOOMS	BEFORE ING THE	PIN-TO-PIN LENGTH	N	MAX ROE BE REDU		MAX INIT ADJUSTM		MAX STRO		FORCE *	**
BARTON BOOMSTRUT	-		KG	LBS	мм	INCH	мм	INCH	мм	INCH	мм	INCH	KG	LBS
Dinghy with Webbing Cradle	-	44001	5	11	750 (Pin to Cradle)	29 1/2	125	4 15/16	130	5 1/8	150	6	45	99
Webbing Cradle for up to 6m (25')	44009	44007	6.3	13.9	840 (Pin to Cradle)	33 1/16			300					198
Webbing Cradle for up to 7.5m (25') & Folkboats	44008	44006	9.5	20.9	950 (Pin to Cradle)	37 3/8	150	5 7/8	300	11 13/16	150	6	140	308
Sliding Pin Boomstrut up to 6m	44010	44011	6.3	13.9	960	37 <sup>13</sup> / <sub>16</sub>	150	5 7/8	300	11 <sup>13</sup> / <sub>16</sub>	150	6	90	198
Sliding Pin Boomstrut 6m to 7.5m	44020	44021	9.5	20.9	1070	42 1/8	150	5 7/8	300	11 13/16	150	6	140	308
Sliding Pin Boomstrut 7.5m to 9m	44030	44031	15	33	1180	46 7/16	150	5 7/8	300	11 13/ <sub>16</sub>	150	6	185	407
Sliding Pin Boomstrut 9m to 10.5m	44035	44036	19	41.8	1320	51 <sup>15</sup> / <sub>16</sub>	150	5 7/8	400	15 <sup>3</sup> / <sub>4</sub>	200	7 7/8	230	506
Sliding Pin Boomstrut 10.5m to 12m	44040	44041	23	50.6	1450				400					594

 $<sup>\*</sup>$  The maximum amount the Boomstrut rods can be shortened to fit inside the vang area.

<sup>\*\*</sup> The maximum amount of available pin-to-pin travel when flexed.

<sup>\*\*\*</sup> The downward force the Boomstrut will support at the point of the boom fitting attachment.

These are approximate measurements which may vary depending on boat type.

## **Dinghy Kits**



98075



LASER REPLICA 15:1 KICKING STRAP ASSEMBLY (98075) UPGRADED TO BALL BEARING BLOCKS

The Barton kicking strap assembly gives all the advantages of similar systems at a fraction of the cost. 15:1 purchase is achieved through clever design of the base plate, fitted with the unique Barton swivelling triple cam block. It is simple to fit and easy to use.

**98075 Comprises** Barton anodised aluminium base plate, anodised aluminium with three fixing bolts; **N10930** Series 0 triple, swivel, cam block attached to base plate by shackle; **N10110** Series 0 single fixed eye block attached to base plate by shackle; **N10211** Series 0 double block with becket; **N11091** Series 1 single tang block with becket and curved kicker key for boom; 1.2m x 4mm Dyneema for primary red control line; 3m x 4mm line for secondary red control line.



98078



#### LASER REPLICA CLEAT BASE ASSEMBLY (98078) UPGRADED TO BALL BEARING BLOCKS

The replica cleat mount comes fitted with two mini K Cams and our new pillar fairlead design for ease of adjustment from all angles.

**98078 Comprises** Cleat base with two fixing holes; **70100** K Cam mini cleats  $\times$  2; **70105** K Cam pillar fairleads  $\times$  2.

This double cam arrangement makes adjustment of cunningham and outhaul easy to access and in one location. Ideal for club racing and is a simple boat upgrade.



98076




#### LASER REPLICA OUTHAUL ASSEMBLY (98076) UPGRADED TO BALL BEARING BLOCKS

The Barton outhaul assembly is class legal offering the same purchase as standard systems fitted. Our outhaul is simple, lightweight, strong and comes with a simple toggle release for the main sail clew.

**98076 Comprises N10110** Series 0 single fixed eye (fitted to short red strop); **N10111** Series 0 single fixed eye becket (fitted to primary red line); **N10110** Series 0 single fixed eye, (attaches to gooseneck by twist shackle or line – not supplied); Primary line 2m x 4mm red Dyneema, Short strop 0.24m x 4mm red Dyneema; Secondary line 4m x 4mm blue line, Elastic 1.5m x 4mm.



98079



#### LASER REPLICA CUNNINGHAM ASSEMBLY (98079) UPGRADED TO BALL BEARING BLOCKS

The Barton Cunningham assembly comes with 8:1 purchase for those who find the standard system a struggle. It is simple to fit and easy to use. Components can be configured to be class legal.

**98079 Comprises N10110** Series 0 single fixed eye (attached to primary red line through sail eye); **N10110** Series 0 single fixed eye (attached to secondary yellow line short tail); Primary line 0.44m x 4mm red Dyneema (with long and short loops); Secondary line 3.5m x 4mm yellow line (large loop provided with long and short tails).





The Barton Marine Pico 6:1 Kicking Strap Assembly is designed to be robust and strong yet is simple to fit and easy to use.

**98095 Comprises N02630** Size 2 fiddle swivel cam block with side mounted becket and carabiner hook, **N01111** Size 1 single fixed eye block with becket and **N01130** Size 1 single swivel boom block.

Primary control line is 3m x 5mm 8-plait polyester.

3

98077



#### LASER REPLICA MAST BASE ASSEMBLY (98077) UPGRADED TO BALL BEARING BLOCKS

**98077 Comprises** two size 0 fixed eye blocks built into the stainless steel mount for added security and no risk of twisting. These are permanently fixed to the mast base deck plate.

**98077 Comprises** Stainless steel mast base plate with two loops; **N10110** Series 0 blocks x 2.



#### **TOPPER 6:1 DOWNHAUL ASSEMBLY KIT**

The Barton Marine Topper Downhaul comes with a 6:1 purchase for those who find the standard system a struggle and for those wanting that extra force in a breeze. It is simple to fit and easy to use on both tacks thanks to the unique swivelling triple block fitted, ideal for club racing and training.

**98080 Comprises N00932** Size 0 triple swivel block with 90 degree cleat base plate, Kevlar cleat and pillar fairlead. 5mm carabiner hook fitted and a **N00310** Size 0 triple fixed eye block with 5mm carabiner hook fitted.

Primary control line 3m x 4mm 8 plait polylock.

#### Disclaimer:

This part is not International Topper Class legal and should not be used for official Topper Class events. 'Topper' is a registered Trademark (name &Top Hat logo) and subject to Licence.

#### Disclaimer:

Barton fittings are high quality replacements that perform the same function as the original part. They should not be confused with official parts bearing the Laser® registered trademark. They cannot be used if you are sailing at an Association event. However, they are perfect for social sailing, sailing schools, club sailing or training. Laser® is a registered trademark owned by Velum Limited and currently licensed for use in Europe to Laser Performance (Europe) Limited.

## **Land Sailing Kits**



#### MAINSHEET BLOCK KIT SUITABLE FOR BLOKART DESIGNS

Barton landsailing kits include the popular **Barton Ratchet Block 90500**. A superior design of ratchet style block that allows the sailor to have control of the mainsheet line. Included with the Ratchet block is a loaded spring to hold it at the best possible angle and upright. Rope is not included, but the kit works with 6mm-8mm (1/4" - 5/16") ropes.

**98096 Comprises** 1 x Ratchet Block **90500**; 2 x 30mm Single swivel block **N01130**; 1 x Stand up Spring 2 x Rope Stopper Black (6mm & 8mm)





#### ODYSSEY/MANTA 2:1 MAINSHEET BLOCK KIT

These kits are designed to work at 2:1 ratio and are suitable for both brands of carts. Featuring the Ratchet Block which reduces the load on the user when holding the sail, particularly on upwind tacks.

98098 Comprises 1 x Ratchet Block 90500;  $2 \times 45 \text{mm}$  Single Swivel Block N03130;  $1 \times 45 \text{mm}$  Single Swivel with Becket N03131;  $1 \times 5 \text{mm}$  up Spring.

No rope is included with this kit, but it is designed to work with 10 mm (3/8") rope.



#### ODYSSEY/MANTA 3:1 MAINSHEET BLOCK KIT

This kit is designed to work with a 3:1 ratio, ideal for where users find the load using 2:1 kit excessive. The extra block reduces comparable load on the hand by a further 30% in comparison to a 2:1 kit.

**98099** Comprises 1 x Ratchet Block 90500; 3 x 45mm Single swivel block **N03130**; 1 x 45mm Single swivel with Becket **N03131**; 1 x Stand up Spring.

No rope is included with this kit, but it is designed to work with 10mm (3/8") rope.



Land yachting images courtesy of Randy Badger at Odyssey Land Yachts




#### Land Sailing Disclaimer:

Barton fittings and replica kits are high quality replacements that perform the same function as the original part. They should not be confused with official parts bearing the OEM company or trademark. Barton replica parts and kits are perfect for racing and training.

## **Tiller Extensions**

#### PLAIN BUTTON ALUMINIUM TILLER EXTENSIONS

Manufactured from 15mm diameter aluminium and available in a wide variety of lengths. All Barton tiller extensions feature our flexible Universal Joint which can easily be removed from the tiller when required.



- Manufactured from anodised aluminium
- Made in Britain

Strong and durable with our unique button end which fits in the palm of your hand and gives increased grip. Excellent for entry level tiller extension use.

PHOTO NO	DESCRIPTION	PART NO								
ALUMINIU	ALUMINIUM TILLER EXTENSIONS – PLAIN BUTTON									
1	Tiller extension – aluminium – plain button 600mm (23 <sup>5</sup> / <sub>8</sub> ")	43101								
2	Tiller extension – aluminium – plain button 700mm (27 9/ <sub>16</sub> ")	43102								
3	Tiller extension - aluminium - plain button 800mm (31 ½")	43103								
4	Tiller extension – aluminium – plain button 900mm (35 7/ <sub>16</sub> ")	43104								
5	Tiller extension – aluminium – plain button 1050mm (41 <sup>5</sup> / <sub>16</sub> ")	43105								
6	Tiller extension – aluminium – plain button 1200mm (47 ½")	43106								

#### **SOFT GRIP ALUMINIUM TILLER EXTENSIONS**

Manufactured from 15mm diameter aluminium and available in a wide variety of lengths.

These soft grip tiller extensions feature our flexible Universal Joint which can easily be removed from the tiller extension when required.

- Manufactured from anodised aluminium
- Featuring a soft grip handle in sea blue heat shrink bonded cover, has a textured surface to enhance grip even when wet



# Carbon Tiller Extensions & Flexible Tiller Joints

#### **CARBON TILLER EXTENSIONS**

Features the latest in uni-directional 16mm carbon fibre tube which incorporates an additional pullwound spiral layer for optimum strength, making it stronger than conventional carbon fibre tube. The custom designed soft grip heat shrink bonded handle reduces fatigue during long periods of use. Includes tiller clip.

PHOTO NO	DESCRIPTION	PART NO
13	Length 600mm (23 5/8")	43500
14	Length 700mm (27 9/ <sub>16</sub> ")	43501
15	Length 800mm (31 <sup>1</sup> / <sub>2</sub> ")	43502
16	Length 900mm (35 7/ <sub>16</sub> ")	43503
17	Length 1000mm (39 <sup>3</sup> / <sub>8</sub> ")	43504
18	Length 1200mm (47 1/4")	43506
19	Length 1500mm (59 <sup>1</sup> / <sub>16</sub> ")	43509
20	Length 2000mm (78 <sup>3</sup> / <sub>4</sub> ")	43514
21	Length 2100mm (82 11/ <sub>16</sub> ")	43515

#### **FLEXIBLE TILLER JOINTS**

43600

Manufactured from high performance polymers to withstand countless tiller flexings.

The tiller extension Universal Joint can easily be removed from the assembly by popping off the snap-on cover.

Two versions are available - light flexible or flexible.

РНОТО	DESCRIPTION			GTH	TUBI INT.		WEIGHT	
NO			MM	INCH	MM	INCH	G	oz
FLEXIBLE	TILLER JOINTS							
22	Light flexible tiller joint	43600	58	2 5/16	13	1/2	20	0.7
23	Flexible tiller joint	43601		2 5/16	13			0.7
TILLER CI	LIP							
24	Tiller clip	43605	51	2	-	-	5	0.2

23 43601



## **Dinghy & Dayboat**



#### **FAIRLEADS**

Fairleads with plunger and cam cleat for use on 20mm T track (see p62 for complete range of 20mm T track fittings). Sold in handed pairs. Includes cam cleat fixed on stainless steel plate. **Sheet fairlead** – a moulded plastic fixed fairlead. **Spinnaker fairlead** – a moulded plastic fairlead with snap in/out hook.

РНОТО	DESCRIPTION	PART	PART LENGTH		FASTENINGS Ø		MAX LINE Ø		WEIGHT	
NO		NO	ММ	INCH	ММ	INCH	ММ	INCH	G	oz
FAIRLEA	os									
1	Fairlead + cam (handed pair) Includes 40cm of track and end fittings	42102	90	3 9/16	5	3/ <sub>16</sub>	12	1/2	732	25.8
2	Sheet fairlead	42200	65	2 9/16	5	3/16	14	9/16	16	0.6
3	Spinnaker fairlead	42201	75	2 15/16	5	3/16	8	5/16	8	0.3

#### **DRAIN BUNGS AND SOCKETS**

This screw type drain bung and socket is still among the best available. Supplied with rubber 'O' ring for a watertight seal. Available in black or white. Also Rubber Bungs for simple drain plug.

РНОТО	DESCRIPTION	PART	BORE Ø		CUTTING Ø		FASTENINGS Ø		WEIGHT	
NO		NO	MM	INCH	MM	INCH	ММ	INCH	G	oz
DRAIN B	DRAIN BUNGS AND SOCKETS									
4	Bung + socket – black	42356	15	9/16	22	7/8	4	3/16	11	0.4
5	Bung only – black	42357								0.2
6	Bung + socket - white	42358	15	9/16	22	7/8	4	3/16	11	0.4
7	Bung only – white	42359	15			-			7	0.2
8	Bung (pair) orange	42354	Dia Ø 19mm (3/4") to 22mm (7/8"); length 28mm (1 1/8"						/8")	

#### **RUDDER AND TRANSOM FITTINGS**

Manufactured from stainless steel with tough nylon surrounds. A wide range of rudder fitting widths are available.

РНОТО	DESCRIPTION	PART	STRAF	STRAP WIDTH		LE Ø	FASTE	NINGS Ø	WEIG	нт
NO		NO	ММ	INCH	ММ	INCH	мм	INCH	G	oz
RUDDER	AND TRANSOM FIT	TINGS								
9	Rudder pintle	42419	19	3/4	9.5	3/8	5	3/16	91	3.2
	Rudder pintle	42422	22		9.5					3.4
	Rudder pintle	42435	35	1 3/8	9.5	3/8	5	<sup>3</sup> / <sub>16</sub>	104	3.7
	Rudder pintle	42450			9.5			3/16	114	
10	Rudder gudgeon	42519	19	3/4	10	7/16	5	3/16	81	2.9
	Rudder gudgeon	42522	22						82	2.9
	Rudder gudgeon	42535	35	1 3/8	10	7/16	5	3/16	91	3.2
	Rudder gudgeon	42550								3.6
11	Transom pintle	42400	-	-	9.5	3/8	5	3/16	70	2.5
12	Transom gudgeon	42500	-	-	-	-	5	3/16	30	1.1

#### RIGGING ADJUSTER

Manufactured from 16mm stainless steel plate - allows for total 50mm adjustment in 10mm steps. Clevis pin 5mm Ø. Overall length 91mm.

#### **BULLSEYE SWIVELS WITH CAM CLEAT**

Swivel bullseye accepts lines up to 12mm Ø and features a stainless steel insert and 'K' cam cleat with top fairlead.

РНОТО	DESCRIPTION	PART	MAX Ø	LINE	BASI	ΕØ	FASTE Ø	NINGS	WEIG	нт	
NO		NO	MM	INCH	MM	INCH	мм	INCH	G	oz	
RIGGING	RIGGING ADJUSTER										
13	Rigging adjuster	42700	-	-	-	-	-	-	35	1.2	
BULLSEY	E SWIVEL WITH CAM										
14	Bullseye swivel with cam	42601	12	1/2	58	2 5/16	5	3/16	172	6.1	

## **Dinghy Mast Support**


Designed to support the aft end of a dinghy mast when towing or stowed in a boat yard. Simply fit onto standard transom rudder fittings and is instantly ready for use. Fully adjustable for different transom heights and features removable pintles to accommodate different transom layouts.


A soft neoprene pad on the yoke protects the mast, shrouds and lines. Generous eyelets in the yoke allow for a securing line to be easily attached. The cross plate can mount a trailer board with  $2 \times 6$ mm screws (not supplied).

- Easy to fit
- No fastenings required
- Fully and easily adjustable
- Increases towing safety
- Prevents damage to mast and deck.

PHOTO NO	DESCRIPTION	PART NO
DINGHY MAST SUP	PORT	
1	Dinghy mast support	42300







## Windicator

The Windicator Range is synonymous with the Kiwi Yachting scene. These wind direction indicators have been made in New Zealand for over 30 years and are designed and manufactured by precision engineers and made from the best marine grade materials. Considered the best wind direction indicator by leading sailors and riggers. 100% accurate in two knots of wind.

#### WINDICATOR WP200L -**BARTON MARINE PART NO 84002**


Fits any 63mm (2 1/2") diameter mast. Designed specifically for the Laser, ILCA and Splash class. 100% accurate in two knots of wind and weighs just 34g (1.2oz). Simple and effective clamp eliminates the need for straps.

This model also fits the Byte CI & CII, Fusion, Aero 6 & 7, Hartley H12, RS100, RS Neo, and the SeldonD+ mast section (Solo).

#### WINDICATOR WP200S -**BARTON MARINE PART NO 84001**

Fits any 45-50mm (1 3/4-2") diameter mast. Designed specifically for the Topper, Optimist, Starling and Blokart class. 100% accurate in two knots of wind and weighs just 29g (1oz). Simple and effective clamp eliminates the need for straps.

Also fits Starling, RS Terra, Hartley Streaker, Hartley H10.






#### WINDICATOR WP2000PTI -**BARTON MARINE PART NO 84003**

Fits into the mainsail luff at the top of the mast, 4.8mm diameter shaft. Designed specifically for the Optimist class and applicable to other classes. 100% accurate in two knots of wind and weighs just 22g (0.77oz).

#### **WINDICATOR WP285 -BARTON MARINE PART NO 84004 OFFSHORE RACING MODEL**

Suitable for yachts 4-8m, fits to top of mast. Features reflective film on vane and arms for night sailing. 100% accurate in two knots of wind and weighs just 23g (1oz).



#### WINDICATOR WP400 -**BARTON MARINE PART NO 84005**

Ocean racing model. Suitable for yachts 8m and over, fits to top of mast. Features reflective film on vane and arms for night sailing. 100% accurate in two knots of wind and weighs just 64g (2.26oz).



## **Dinghy Support Parts**





#### ALL PRODUCTS AVAILABLE IN PAIRS OR BULK TRADE PACKS OF 50

РНОТО	DESCRIPTION	PART	OVER	ALL (Ø)	MAX RO	OPE (Ø)	COLOURS)
ID	DESCRIPTION	NO	ММ	INCH	ММ	INCH	COLOUR(S)
1	Carded display of two 4mm rope stoppers		17.5	11/ <sub>16</sub>	4	3/ <sub>16</sub>	Red x 1 & Green x 1
2	Carded display of two 4mm rope stoppers	42811	17.5			3/16	Blue x 1 & Grey x 1
3	Carded display of two 4mm rope stoppers	42812	17.5	11/16	4	3/16	2 x Black
4	Carded display of two 4mm rope stoppers	42813	17.5			3/16	Yellow x1 & White x1
5	Carded display of two 6mm rope stoppers	42814	25	1	6	1/4	Red x 1 & Green x 1
6	Carded display of two 6mm rope stoppers	42815					2 x Blue
7	Carded display of two 6mm rope stoppers	42816	25	1	6	1/4	2 x Black
8	Carded display of two 6mm rope stoppers	42817					Yellow x 1 & White x 1
9	Carded display of two 8mm rope stoppers	42818	33	1 19/64	8	5/16	Red x 1 & White x 1
10	Carded display of two 8mm rope stoppers	42819	33	1 19/64	8	5/16	2 x Black



A. Carrier	
	1
	and the same

••	00

14 42214

13 42213



#### LACING BUTTONS - MAX LINE SIZE 6MM - 1/4"

РНОТО	DESCRIPTION	PART	PROJEC	TS	DIAMETI	ER (Ø)	QUANTITY	FIXINGS
NO	DESCRIPTION	NO	ММ	INCH	ММ	INCH	ON CARD	FIXINGS
11	Black lacing buttons on card	42210	10.6	7/16	12.5	1/2	2	No 8 or M4 Counter Sunk
12	White lacing buttons on card	42211	10.6	<sup>7</sup> / <sub>16</sub>	12.5			No 8 or M4 Counter Sunk

#### LACING HOOKS PLASTIC

РНОТО	DESCRIPTION	PART	PROJEC	TS	WIDTH >	DEPTH	QUANTITY	FIXINGS
NO	DESCRIPTION	NO	ММ	INCH	ММ	INCH	ON CARD	FIXINGS
13	Black lacing hook on card up to 8mm cord	42213	12.5	1/2	28mm x 26mm	1 <sup>1</sup> / <sub>8</sub> x 1 <sup>1</sup> / <sub>32</sub>	2	No 8 or M4 Counter Sunk
14	White lacing hook on card up to 8mm cord	42214	12.5	1/2	28mm x 26mm	1 <sup>1</sup> / <sub>8</sub> x 1 <sup>1</sup> / <sub>32</sub>	2	No 8 or M4 Counter Sunk

#### **50MM TOE STRAP BRIDGES**

РНОТО	DESCRIPTION	PART	PROJEC <sup>-</sup>	TS	WIDTH X	DEPTH	QUANTITY	FIXINGS
NO	DESCRIPTION	NO	ММ	INCH	ММ	INCH	ON CARD	FIAINGS
15	Black 50mm toe strap bridge	42215	9.3	3/8	15mm x 69mm	9/ <sub>16</sub> x 2 <sup>11</sup> / <sub>16</sub>	2	No 8 or M4 Counter Sunk
16	White 50mm toe strap bridge	42216	9.3		15mm x 69mm	9/ <sub>16</sub> x 2 <sup>11/</sup> <sub>16</sub>		No 8 or M4 Counter Sunk

## **Deck Hardware**

#### 60330



#### 60331



#### 60415



#### STAND UP BLOCK BASE

The Small Stand Up Base (1) is manufactured from 316 Stainless Steel with a bolted U bolt for added strength. It is mounted on a plastic deck plate. Designed to work with blocks from size 0 through to size 3 and can be used with stand up springs or rubber boots. It will work with a wide range of Barton blocks to suit multiple applications.

The Large Stand Up Base (2) is manufactured from marine grade aluminium which is Spectro or black anodised with a bolted 316 Stainless Steel U bolt for added strength. The aluminium deck plate is fixed directly to the deck with suitable countersunk fasteners. Designed to work with blocks from size 5 through to size 7 and can be used with stand up springs or rubber boots. It will work with a wide range of Barton blocks to suit multiple applications. All Stand Up Bases have a U bolt that is fixed so if a swivel is needed, this is done by block selection. Ideal for lashing down equipment.

PHOTO NO	DESCRIPTION PART		HEIGHT		BASE Ø	i.	FASTENINGS Ø		MAXIMUM APERTURE SIZE		BASE THICKNESS	
			мм	INCH	ММ	INCH	ММ	INCH	мм	INCH	ММ	INCH
STAND UP BASE												
1	Small Stand Up Base	60330	33	1 <sup>5</sup> / <sub>16</sub>	58	2 5/16	5	3/16	9.5	3/8	4	3/16
2	Large Stand Up Base Spectro	60331							14	9/16	12	1/2
	Large Stand Up Base black	60332	40	1 9/16	69	2 11/16	6	1/4	14	9/16	12	1/2

#### LOW FRICTION RING STRAP EYE

Designed using our smallest Low Friction Ring 60449 to reduce friction on small lead ropes up to 4mm. By incorporating the Low Friction Ring into a stainless steel deck eye, small control lines can be led to where they are needed without using blocks. Low Friction Rings are a great way to change the direction or lead of a line efficiently. Ideal for dinghy racers and cruising boats for lines up to 4mm. Hole aperture is 6mm.

РНОТО	DESCRIPTION	PART	HEIGHT		BASE W	IDTH	FASTEN	INGS Ø	HOLE C	ENTRES	MAXIMU ROPE SI	
NO BESCRIPTION	NO	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	
STAND U	STAND UP BASE											
3	Deck eye - S/S with Low Friction ring	60415	13	1/2	38	1 1/2	4	3/16	30	1 3/16	4	3/16

#### **FLUSH STAINLESS STEEL DECK PLATES**

Turned from solid bar 316 stainless steel with a highly polished finish, these deck plates have a centre anchoring hole in three standard metric thread sizes - M8, M10 and M12, each supplied with a stainless steel blanking plug.

Designed to be mounted flush with the deck using three fixing bolts, the encapsulated internal thread eliminates water ingress. The design prevents trip hazards on board when not in use. The range allows for a multitude of uses, including temporary fixing eyes, boat tie downs, deck mounted boarding ladders, stand up blocks, davit mounts, life raft holders, dive tanks and other endless uses. Supplied with or without an eye bolt.





60361



60363

60364

60365

РНОТО	DESCRIPTION	PART NO WITH EYE	PART NO	OVERAL DIAMET		SPIGOT	DEPTH	SPIGOT DIAMETER		SWL	
NO	NO DESCRIPTION	BOLT	PLATE ONLY	ММ	INCH	ММ	INCH	ММ	INCH	KG	LBS
4	Deck Plate with M8 Fixing & Eye With Blanking Plug	60360	60363	50	1 15/16	22	7/8	17	11/16	2000	4100
5	Deck Plate with M10 Fixing & Eye With Blanking Plug	60361	60364	50	1 <sup>15</sup> / <sub>16</sub>	22		17	11/16	2250	4950
6	Deck Plate with M12 Fixing & Eye With Blanking Plug	60362	60365	50	1 <sup>15</sup> / <sub>16</sub>	22	7/8	17	11/16	2500	5500

## **Ancillary Equipment**

#### THE INNOVATIVE NO KNOT BOATING ACCESSORY

This innovative no-knot marine accessory is a fast and easy way to secure lines up to 10mm. This safe, low profile spring loaded locking cleat is easy to install. Locks the line in one direction, allows tensioning of line in the



other direction. High density Zytel nylon composite and stainless-steel construction provides a working load of up to 540kg. Quick Cleat is ideal for leisure craft, work boats and marinas.

O Kayaks O Canoes O Paddleboards O Water Toys O Painters O Fenders O Boat Gear O Covers O Buckets & Fishing Gear



PHOTO NO	DESCRIPTION	PART NO	MAXIMUM ROF	PE SIZE	WWT
			мм	INCH	KG
1	Quick CleatTM – Reinforced black nylon Size 1	60020	6	1/4	30
2	Quick CleatTM – Size 1 on a PVC backing pad for inflatables	60021		1/4	30
3	Quick CleatTM – Reinforced black nylon Size 2	60030	10	3/8	70
4	Quick CleatTM – Reinforced white nylon Size 1	60031		3/8	70
5	Quick CleatTM – Polished stainless steel body Size 2	60040	10	3/8	540

#### **TUBULAR CLEATS**

Available in two sizes, these handy cleats have many uses where light loads are expected.

12 52121



PHOTO NO	DESCRIPTION	PART NO	LENGTH		FASTENING Ø		WEIGHT		BORE Ø	
	DESCRIPTION	PARTINO	мм	INCH	ММ	INCH	G	oz	ММ	INCH
TUBULAR CLEAT										
11	Tubular cleat	52120	55	2 3/16	4	3/16	4	0.1	8	5/16
12	Tubular cleat	52121		3 1/8			13	0.5	13	1/2

#### STAINLESS STEEL RUBBING STRAKES

Stainless steel rubbing strakes, designed to help prevent rope wear to deck edges and coamings. Available in three lengths, these attractive strakes are easy to fit and will last a lifetime.

РНОТО NO	DESCRIPTION	PART NO	DIMENSIONS						
PHOTONO	DESCRIPTION	PARTINO	ММ	IN					
STAINLESS STEEL RUBBING STRAKES									
13	Rubbing strake	67100	203 x 19	8 x <sup>3</sup> / <sub>4</sub>					
14	Rubbing strake	67101	305 x 19	12 x 3/ <sub>4</sub>					
15	Rubbing strake	67102	457 x 19	18 x <sup>3</sup> / <sub>4</sub>					



## **Kevlar Cam Cleats**

Manufactured from a Kevlar composite and available in three sizes to accept lines up to 14mm in diameter. This Kevlar moulded material offers performance advantages over carbon fibre and conventional glass-reinforced resins. K Cams are very strong, lightweight and have excellent wear resistance. A progressive tooth design ensures maximum holding power on all types of line, while maintaining minimum wear to both cam and line.

K Cam bases feature a stainless steel wear bar for prolonged life. The cams utilise stainless steel leaf springs which give a smooth but positive action. They are also stronger and have a longer life than conventional wire springs.

K Cam cleats are supplied as a cleat only plus separate accessories in grey, green, red or yellow where appropriate, to allow colour coordination for port, starboard and other purposes.

#### Wire Front Fairleads

Made from stainless steel.

#### Pillar Fairleads

Stainless steel pillars add strength and wear resistance. These add-ons enable the cam cleat to be engaged from a variety of angles. Cams can be fitted either way around to achieve a lead from in front or behind. Available in several colours to aid identification.

#### Top Fairleads

Top fairleads allow easy colour coding of K Cams with their bright moulded colours and stainless steel reinforcing for added strength and wear resistance.


#### Wedge Mounts

Angled wedge mounts allow you to angle the cam to give a better lead for lines. Available to suit the three sizes of K Cam cleat.

#### **Cam Top Caps**

Supplied in packs containing two each of red, green and yellow cam top caps. These offer a low profile solution to aid identification.

PART NO	PART NO			70200		70330		
SPECIFICATI	SPECIFICATIONS		K CAM MINI			K CAM MAXI		
2.2	Max line Ø	3-10mm	1/8-3/8"	6-12mm	1/4-1/2"	10-14mm	3/8-9/16"	
	Fastenings Ø	4mm			3/ <sub>16</sub> "		3/16"	
1-1	Fastening centres	30mm	1 <sup>3</sup> / <sub>16</sub> "	40m	1 9/16	50mm	2"	
	Holding power	190kg	418lbs	230kg	506lbs	260kg	572lbs	
<b>₽</b> w₽	Weight	17g	0.6oz	34g	1.2oz	50g	1.8oz	
	Overall length	51mm		68mm	2 11/16"	81mm	3 3/16"	
	Overall width	21mm	13/ <sub>16</sub> "	28mm	1 1/8"	31mm	1 1/4"	





#### K CAM CLEAT ONLY




#### K CAM CLEAT SUPPLIED WITH WIRE FRONT FAIRLEAD



#### K CAM CLEAT FITTED WITH PILLAR FAIRLEAD



#### **CLEAT TOP FAIRLEADS**




#### **PILLAR FAIRLEADS**

#### WIRE FRONT FAIRLEADS



#### **WEDGE MOUNTS**



#### CAM TOP CAPS



PHOTO NO	DESCRIPTION	K CAM MINI	K CAM MIDI	K CAM MAXI
	K CAM CLEAT ONLY			
1	K Cam cleat only	70100	70200	70300
K CAM CLEAT WI	TH WIRE FRONT FAIRLEAD			
2	K Cam cleat with wire front fairlead	70101	70201	70301
WIRE FRONT FAIR	RLEAD ONLY			
3	Stainless steel wire front fairlead only	70104	70204	70304
PILLAR FAIRLEAD	ONLY			
4	Pillar fairlead – dark grey	70105	70205	70305
TOP FAIRLEAD OI	NLY			
5	Top fairlead – grey	70106	70206	70306
6	Top fairlead – green	70116	70216	70316
7	Top fairlead – red	70126	70226	70326
8	Top fairlead – yellow	70136	70236	70336
WEDGE MOUNT				
9	Wedge mount	70140	70240	70340
CAM TOP CAPS				
10	Pack of top caps, 2 x red, green, yellow	70141	70241	70341

## **Cleats**

A wide range of specialised glass filled nylon cleats designed for a variety of uses onboard.

#### STANCHION CLEAT

Designed to fit stanchions or pushpit/pullpit tubes - fits in seconds and features soft nylon jaws that will not damage the tube. The Stanchion Bullseye is suitable for line up to 12mm and fits to stanchions or pushpit/pullpit tubes.

Full range of Stanchion fittings on p84

#### **SHROUD CLEATS**

Two handy cleats that simply clamp onto shroud wire (maximum  $8mm \varnothing$ ) without causing damage.

**52110** is a plain cleat for flag halyards etc.

**52111** features a wide eye opening for stowage of halyard shackles.



1 52100

2 60142

Stanchion Bullseye









DUCTO NO	DESCRIPTION	PART NO	CLEAT			HOLE CEN	ITRES	WEIGHT		FASTENING Ø	
PHOTO NO	DESCRIPTION	PART NO	MATERIAL	ММ	INCH	ММ	INCH	G	oz	мм	INCH
STANCHION	CLEAT										
1	Stanchion cleat	52100	Nylon	111	4 3/8	_	-	90	3.2	-	-
STANCHION	BULLSEYE										
2	Stanchion bullseye	60142	Nylon	Bullseye internal Ø 17mm for lines up to 12mm							
SHROUD CLE	AT										
3	Shroud cleat	52110	Nylon	100	3 15/16	_	-	26	0.9	-	-
4	Shroud cleat with eye	52111	Nylon	100	3 15/16	-	-	26	0.9	-	-
SHROUD CLE	AT										
5	Open cleat	52140	Nylon	75	2 <sup>15</sup> / <sub>16</sub>	26	1 1/32	6	0.2	3	1/8
6	Open cleat	52141	Nylon	100				12	0.4	4	3/16
7	Open cleat	52142	Nylon	125	4 15/16	36	1 7/16	26	0.9	4	3/16
8	Open cleat	52143	Nylon	170		42				5	3/16
9	Open cleat	52144	Nylon	205	8 1/16	50	1 15/16	84	3	6	1/4
10	Open cleat	52145	Nylon	245	9 5/8			157	5.5	8	5/16

## Wingnuts

#### PLASTIC WINGNUTS WITH STAINLESS STEEL THREADS

Barton Marine provides solutions for boat owners and boat builders. When equipment needs to be bolted in place for functionality but also needs to be removed easily when required.

These plastic Wingnuts can be fitted over standard M5, M6 or M8 nuts and bolts. This allows for easy removal without the need for tools.

The extended wings provide additional purchase by hand compared to that offered by a standard fixing. Supplied with stainless steel nut and durable plastic moulded cover.



PART NO	DESCRIPTION	THREAD SIZE	SPANNER SIZE	TOTAL WINGNUT WIDTH
52160	Pack of 2 Wingnuts for M5 Thread (carded)	M5	8mm	30mm
52161	Pack of 2 Wingnuts for M6 Thread (carded	M6	10mm	40mm
52162	Pack of 2 Wingnuts for M8 Thread (carded)	M8	13mm	50mm
52160B	Pack of 50 Wingnuts for M5 Thread (Bulk Pack)	M5	8mm	30mm
52161B	Pack of 50 Wingnuts for M6 Thread (Bulk Pack)	M6	10mm	40mm
52162B	Pack of 50 Wingnuts for M8 Thread (Bulk Pack)	M8	13mm	50mm



# Clevis Pins, Split Rings & Springs

#### **STAND-UP SPRINGS**

Stainless steel springs are ideal for mounting blocks on decks to prevent tumbling of blocks. Flexible plastic versions also stop rope snags and deck damage.



РНОТО	DESCRIPTION	PART	DIA Ø 'I	D'	HEIG	HT 'H'
NO	DESCRIPTION	NO	мм	INCH	ММ	INCH
STAND-UP	SPRINGS					
1	Spring – stainless steel (tapered)	60119	16-24	5/8-15/16	20	13/16
2	Spring – stainless steel	60120	20	13/16	35	1 3/8
3	Spring – tempered stainless steel	60121	30	1 3/16	30	1 3/16
4		60122	40	1 9/16	50	1 <sup>15</sup> / <sub>16</sub>
5	Spring – plastic	60123	48	1 7/8	50	1 15/16

#### **SPLIT RINGS**

Easy-fit stainless steel split rings for use with our clevis pins. Supplied in two sizes and in packs of 10.

РНОТО NO	DESCRIPTION	PART NO
SPLIT RINGS		
6	Split ring – 10mm Ø - pack of 10	60190
7	Split ring – 14mm Ø - pack of 10	60191
	Bulk pack – 10mm – pack of 50	50191



60207

#### **CLEVIS PINS**

Barton clevis Pins are manufactured from 316 stainless steel – as used throughout the Barton range of blocks. Supplied in packs of two with stainless steel split rings.

60203

PHOTO NO	DESCRIPTION	PART NO	DIA Ø 'E	) <sup>'</sup>	HEIGHT 'H'	
PHOTONO	DESCRIPTION	PARTINO	ММ	INCH	ММ	INCH
CLEVIS PINS						
8	Clevis pins (pack of 2)	60203	5	3/16	15	9/16
	Clevis pins (pack of 2)	60204	5			11/ <sub>16</sub>
9	Clevis pins (pack of 2)	60207	5	3/16	24	15/16
	Clevis pins (pack of 2)	60208		3/ <sub>16</sub>	33	1 <sup>5</sup> / <sub>16</sub>
	Clevis pins (pack of 2)	60209	5	3/16	51	2
10	Clevis pins (pack of 2)	60210				3/8
	Clevis pins (pack of 2) - plastic	60212	6	1/4	23	7/8



### Shackles, 'S' Hooks & Swivels

#### **SHACKLES**

A range of screw pin strip and forged bar shackles in stainless steel – as used throughout the Barton range. Pin diameters up to 8mm available.









#### **SWIVELS**

Stainless steel swivels as used throughout the Barton block range. Four sizes available.







#### 'S' HOOKS

A handy fitting with a multitude of uses. Manufactured from stainless steel. Supplied as either a plain hook or with spring latch fitted.

13 60355



#### **RIGGING LINKS & SHACKLE KEY**

Pressed stainless steel rigging links with clevis pin and captive pin. Sizes up to 6mm pin diameter.













РНОТО	DESCRIPTION	DART NO.	PIN Ø 'D		LENGTH	H 'L'	WIDTH	'W'	
NO	DESCRIPTION	PART NO	ММ	INCH	ММ	INCH	ММ	INCH	
SCREW PI	N SHACKLES (STRIP)								
	Strip shackle	60310	5	3/16	27	1 1/16	10	3/8	
1	Strip shackle	60311	6	1/4	38	1 1/2	13	1/2	
2	Strip shackle	60312	8	5/16	50	1 15/16	16	5/8	
SCREW PI	N SHACKLES (BAR)							·	
3	Forged D shackle 6mm	60320	6	1/4	38	1 1/2	13	1/2	╽╬══╬╷
	Forged Bow shackle 6mm	60321	6	1/4	44	1 3/4	16	5/8	`w ´
	Forged D shackle 8mm	60322	8	5/16	49	1 15/16	13	1/2	
4	Forged Bow shackle 8mm	60323	8	5/16	55	2 3/16	16	5/8	
SWIVELS									w
	Swivel	60700	5	3/16	33	1 <sup>5</sup> / <sub>16</sub>	8	5/16	
5	Swivel	60701	5	3/16	33	1 <sup>5</sup> / <sub>16</sub>	9	3/8	
6	Swivel	60702	5	3/16	33	1 <sup>5</sup> / <sub>16</sub>	11	7/16	╟┷╟
7	Swivel	60703	6	1/4	45	1 3/4	14	9/16	Pin Dia
'S' HOOK	S								
8	'S' hook plain	60708	6	1/4	73	2 3/4	19	3/4	/w P
9	'S' hook with latch	60709	6	1/4	73	2 3/4	19	3/4	( <i>`` </i>   /∟
RIGGING	LINKS								• •
10	Rigging link	60343	5	3/16	30	1 3/16	14	9/16	
11	Rigging link	60344	6	1/4	37	1 7/16	18	11/16	
12	Captive Pin 6mm Shackle with locking pin	60350	6	1/4	50	1 15/16	19	3/4	
13	Stainless Steel Shackle Key	60355				three spannand bottle op		, 10 and	


### **Deck Plates & Eyes**

#### **PAD EYES**

A wide range of attachment eyes/fairleads manufactured from 316 stainless steel. All featuring a solid stainless steel bar welded for extra security. Folding pad eye - stainless steel pad eye with anti-vibration rubber pad. Folds flat to deck when not in use. Double folding pad eye – with anti-vibration rubber pads and two fixing eyes which fold flat when not in use.



DUIGTO NO	PHOTO NO DESCRIPTION	DADT NO	DIA Ø '	DIA Ø 'A'		HEIGHT 'A'		HOLE CENTRE 'C'		WIDTH 'D'		FASTENINGS Ø	
PHOTONO	DESCRIPTION	PART NO	мм	INCH	мм	INCH	мм	INCH	ММ	INCH	ММ	INCH	
PAD EYES													
1	Pad eye – double folding	60304	6	1/4	42	1 <sup>5</sup> / <sub>8</sub>	-	-	52	2 1/16	6	1/4	
2	Pad eye – fixed	60305	4	3/16	16	5/8	30		40	1 9/16	5		
3	Pad eye – fixed	60306	6	1/4	24	15/16	44	1 3/4	60	2 3/8	5	3/16	
4	Pad eye – fixed	60307	8	5/16	28	1 1/8	55	2 3/16	80	3 1/8			
5	Pad eye – fixed	60308	10	3/8	35	1 3/8	60	2 3/8	95	3 3/4	8	5/16	
6	Forged pad eye – folding	60309	6	1/4	42	1 5/8	36	1 <sup>7</sup> / <sub>16</sub>	54	2 1/8	6	1/4	



#### STAINLESS STEEL DECK EYES




Made from 316 marine grade stainless steel, these eyes can be used for a number of applications, from fairleads to lashing points. Low friction ring version is embedded in stainless steel for low friction performance.

Supplied on cards to hang on euro hooks in shops. Can be bought bulk packed.

РНОТО	DESCRIPTION	PART	HEIGHT		BASE WIDTH		FASTENINGS Ø		HOLE CENTRES		MAXIMUM ROPE SIZE	
NO		NO	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	мм	INCH
LOW FRIG	CTION RING DECK	EYE										
7	Deck eye – s/s	60410	14	9/16	14	9/16	5	3/16	34	1 <sup>5</sup> / <sub>16</sub>	10	9/16
8	Deck eye – s/s	60411	18		16	5/8	6	1/4	49		14	3/8
9	P Clip – s/s	60410P	12	1/2	12	1/2	5	3/16	-	-	-	-
10	Deck eye – s/s with low friction ring	60415	13		38	1 <sup>1</sup> / <sub>2</sub>	4	3/16	30		4	3/16

#### **BULLSEYES**

A range of four bullseyes for through-deck or on-deck screw mounting. All feature a strong, moulded plastic eye, reinforced with a stainless steel bar. Two models also feature a stainless steel eye insert to limit wear to the line. All accept lines up to 16mm (5/8") Ø.





### **Sheaves**

#### **SHEAVES**

A comprehensive range of plain and ball bearing sheaves as used throughout the complete Barton block range. Moulded from Acetal resin, our unique, super-low friction ball race system features Delrin balls running on a large diameter centre boss, ensuring extremely low friction performance.

РНОТО	DESCRIPTION.	PART	DIA !	Ø 'D'	THIC	KNESS 'T'	BOR	E
NO	DESCRIPTION	NO	ММ	INCH	ММ	INCH	ММ	INCH
SHEAVES	– PLAIN BEARING	1						
1	Plain bearing sheave	N64800	25	1	12	1/2	8	5/16
	Plain bearing sheave	N64801	30	1 3/ <sub>16</sub>	12	1/2	8	5/16
	Plain bearing sheave	N64802	32	1 1/4	14	9/ <sub>16</sub>	8	5/ <sub>16</sub>
	Plain bearing sheave	N64803	32	1 1/4	17	11/ <sub>16</sub>	11	<sup>7</sup> / <sub>16</sub>
	Plain bearing sheave	N64804	35	1 3/8	12	1/2	8	5/16
	Plain bearing sheave	N64805	34	1 <sup>5</sup> / <sub>16</sub>	18	11/16	13	1/2
	Plain bearing sheave	N64806	38	1 1/2	17	11/ <sub>16</sub>	13	1/2
	Plain bearing sheave	N64807	44	1 3/4	18	11/16	13	1/2
	Plain bearing sheave*	N64808	44	1 3/4	20	13/ <sub>16</sub>	13	1/2
	Plain bearing sheave	N64809	45	1 3/4	11	<sup>7</sup> / <sub>16</sub>	8	5/16
	Plain bearing sheave	N64810	44	1 3/4	13	1/2	8	5/16
	Plain bearing sheave	N64811	46	1 <sup>13</sup> / <sub>16</sub>	20	<sup>13</sup> / <sub>16</sub>	13	1/2
	Plain bearing sheave	N64812	58	2 5/16	14	9/16	8	5/16
	Plain bearing sheave	N64813	57				13	
	Plain bearing sheave	N64814	63	2 1/2	18	11/ <sub>16</sub>	12	1/2
	Plain bearing sheave	N64815	71	2 <sup>13</sup> / <sub>16</sub>	17	11/16	13	1/2
	Plain bearing sheave	N64816	71	2 13/16	19	3/4	13	1/2
	Plain bearing sheave	N64817	54	2 1/8	17	11/16	13	1/2

<sup>\*</sup> This sheave fits the Barton Deck Organisers

#### **SPARE GENOA SHEAVES IN WHITE ERTALYTE**

The former Barton Genoa Car has white sheaves manufactured from Ertalyte, for strength and durability. Supplied with aluminium bearings, Genoa sheaves stand up to the shock loads that head sails transfer to the blocks.



Sheaves also available in white to order.

РНОТО	DESCRIPTION.	PART	DIA	Ø 'D'	THIC	KNESS 'T'	BOR	E
NO	NO DESCRIPTION		ММ	INCH	мм	INCH	мм	INCH
SHEAVES	– BALL BEARING							
2	Ball bearing sheave	N64901	30	1 <sup>3</sup> / <sub>16</sub>	13	1/2	5	3/16
	Ball bearing sheave	N64902	32	1 <sup>1</sup> / <sub>4</sub>	14	9/16		3/16
	Ball bearing sheave	N64904	35	1 3/8	13	1/2	5	3/16
	Ball bearing sheave	N64906		1 1/2		11/ <sub>16</sub>		1/4
	Ball bearing sheave	N64907	44	1 3/4	19	3/4	6	1/4
	Ball bearing sheave	N64908	44	1 3/4	20	13/ <sub>16</sub>		1/4
	Ball bearing sheave	N64909	45	1 3/4	12	1/2	5	3/ <sub>16</sub>
	Ball bearing sheave	N64910	45	1 3/4	14	9/16		3/ <sub>16</sub>
	Ball bearing sheave	N64912	58	2 5/16	14	9/16	5	3/ <sub>16</sub>
	Ball bearing sheave	N64913		2 5/16	17	11/ <sub>16</sub>		1/4
	Ball bearing sheave	N64914	64	2 1/2	18	11/16	6	1/4
	Ball bearing sheave	N64915	72	2 <sup>13/</sup> 16	18	11/ <sub>16</sub>	6	1/4
	Ball bearing sheave	N64916	72	2 13/16	21	13/16	6	1/4
	Ball bearing sheave	N64917	58	2 <sup>5/</sup> 16	17	11/ <sub>16</sub>	6	1/4






PHOTO NO	DESCRIPTION	PART NO	DIA Ø 'D'		THICKNESS 'T'		BEARING BORE		SHEAVE BORE	
			ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH
FORMER DESIGN GI	ENOA CAR SHEAVES – SUPPLIED WITH ALUMINIUM BEA	ARING								
3	Genoa car sheave for 32100	32997	50	1 <sup>15</sup> / <sub>16</sub>	37	1 7/16	8	5/16	13	1/2
	Genoa car sheave for 32101HD	32995	60	2 3/8		1 <sup>7</sup> /16	10	3/8		3/4
	Genoa car sheave for 25100	25997	39	1 9/16	31	1 1/4	6	1/4	10	3/8
	Genoa car sheave for 22100	22997	30	1 <sup>3</sup> / <sub>16</sub>	22	7/8	6	1/4	10	3/8

### **Wear Pads & Line Tamers**

#### **WEAR PADS IN CLEAR POLYURETHANE**

Designed to help sailors and power boaters protect key areas of a boat's deck and superstructure from abrasion, chips, scuffs and wear, our wear pads can be applied wherever there is a need to protect a boat's finish without compromising its appearance. Non-yellowing, durable film.

#### **HOW TO FIT WEAR PADS**

Ensure that the surface is smooth and perfectly clean; remove all traces of dirt, salt, moisture and grease. For rough surfaces, such as non-slip deck surfaces, lightly sand the surface with sandpaper for better adhesion.

Align the pad and trim to size with scissors if necessary. Press down firmly with a hard edged plastic tool which is the full width of the pad to provide the necessary pressure at the point of lamination.

РНОТО NO	DESCRIPTION	PART NO
WEAR PADS		
1	Polyurethane clear wear pads (pack of 2)	67170





#### THE BARTON LINE TAMER



### Fuel Whistle & EasySplice

#### **FUEL WHISTLE**

### A simple device to prevent accidental spillages when refuelling.

This unique patented product has been designed to give an audible warning to prevent fuel spills during the refuelling of boats. This helps prevent marine pollution and ensures that your topsides and decks are kept free from spills.

- Eco friendly
- Simple to fit
- Protects the environment and your deck
- Suitable for sail and power boats
- Fitting instructions included
- Cost effective
- More information bartonmarine.com

#### **EASYSPLICE**

### Sailors and boat owners are rediscovering the timeless art and skill of rope splicing.

Splicing is the ability to terminate a rope or join two ends of a rope without using a knot. Barton's EasySplice is designed specifically to make this action simple, fast and precise.

A balanced and lightweight tool that enables faster and easier rope splicing.

- Simple to use No experience required
- Lightweight design
- Balanced needle and head construction
- Hand tool and four needles included
- Splicing tool for up to 5mm line
- Different needle lengths available on request








PHOTO NO	DESCRIPTION	PART NO
1	Fuel whistle	60010

#### **BABYSPLICE**

This is a small version of the EasySplice, but provided with three shorter needles.

- Hand tool and three needles included
- Splicing tool for up to 4mm line
- Includes instructions







### **ClamSeal**<sup>TM</sup>



### The award winning, patented ClamSeal™ repairs inflatables fast – even when wet

The ClamSeal™ can instantly repair splits and tears up to 90mm (3½") in length without the use of any hand tools or adhesive.

ClamSeal<sup>™</sup> is a patented glue-less repair system that instantly repairs small tears or splits in inflatables above or below the waterline – regardless of the fact that the material may be wet.


The system works by using two half 'shells' that screw together tightly, using the inflatable material itself as a water and air-tight seal. It is quick and easy to fit and effects an immediate repair which can keep you afloat until a more permanent repair can be made.

- Quick and easy to fit
- Requires no adhesive or tape
- Can be used above or below the waterline
- Can be used on wet materials
- Provides an instant repair
- Re-useable again and again.

The ClamSeal™ can be carried as part of your emergency equipment onboard. It can be used at sea, on shore; even underwater as no adhesive or tape is involved. The clever mechanics of the ClamSeal™ design mean this simple product can keep you afloat safely.

The ClamSeal™ is now a permanent part of the safety kit on RIBs globally and continues to amaze those who have used it – an effective, low cost solution to an otherwise complicated problem.





Open the ClamSeal<sup>™</sup> and insert the base plate into the split



Pull the plates of the ClamSeal™ together, across the split, using the lanyard



#### **DAME Design Award category winner**

Winner of National Marine Manufacturer's Association Product Innovation Award

#### ClamSeal™ is suitable for use on:

- RIBs
- Dinghies
- Liferafts

- Buoyancy bags
- Most inflatable products

РНОТО NO	DESCRIPTION	PART NO
CLAM SEAL™		
1	Barton ClamSeal™	60001





With the two plates pulled together, simply hand tighten the nut for a Clam-tight seal



Reinflate and you're safe to continue on your way

### SkyDock

Barton's solution to create hidden storage space - all in one kit. The ideal garage storage solution for dinghies, paddle boards, kayaks, roof box, camping equipment, or anything else that can be lifted off the ground to save on storage space.



The clever configuration of ropes and blocks means one person can raise and lower loads up to 80kg single handed and then lock off with Barton Marine's unique SkyLock block when finished.

All SkyDock components are provided in a single box kit - this includes rope and beam fittings/eyes, and all lifting straps.

Comprehensive hassle free fitting instructions included. Ideal to transform unused areas in your garage, loft, barn or shed into valuable storage space.



View installation quide here





РНОТО	DESCRIPTION	PART	MAX LI LOAD	FT	MAX CEILING HEIGHT			
NO		NO	KG	LBS	М	FT		
SKYDOCK								
2	SkyDock 4:1 purchase system	41201	80	175	4	13		

### **Inspection Covers**

equipment manufacturers to new models due to their quality and performance.

#### **SCREW INSPECTION COVERS**

#### Barton offers a wide range of inspection covers.

Manufactured from high impact polycarbonate, these covers feature an easy start thread and a built in silicone 'O' ring seal. Available in four diameters and two colours – white and black.



APERTURE Ø CUTTING Ø OVERALL Ø FASTENINGS Ø WEIGHT PART NO WHITE PART NO BLACK DESCRIPTION INCH ММ INCH мм INCH INCH SCREW INSPECTION COVERS - ROUND Screw inspection covers - round 40040 40041 4 1/16 114 4 1/2 145 5 11/16 3/16 3.0 8 1/16 172 Screw inspection covers - round 40060 40061 6 1/8 165 6 1/2 3/16 6.1 **Outboard Motor Sling** 

Barton Marine's Outboard Motor Sling - British Yachting Awards 2024 Equipment Innovation of the Year nominee – was designed after months of research and customer feedback into the practicalities of lifting outboard motors.


Barton's Outboard Motor Sling makes it easy to securely lift and hold your valuable engines during maintenance and changeovers. It outperforms other slings that slip, fail and are difficult to use as they leave the motor unbalanced during lifting.

The Barton Sling is designed to balance and maximise the centre of gravity of the motor to create a stable central elevation point regardless of the motor lifted. Holding most outboard engine brands up to 20hp and 50kg (110 lbs), the Barton Sling has extra lifting capacity to work with two-stroke and modern four-stroke engines.

Installes in seconds and the straps self-tighten on all motors giving the user full confidence when lifting. The Sling is designed with a short strap that stays attached to the front toggle assembly of the engine even when in use. The top sling strap hooks around the back of the engine and clips to the stainless steel D-rings on the toggle strap. The Sling can be removed quickly once the engine is in place by simply unclipping the two stainless steel carabiners at the front.

Quick, safe and easy to use and manufactured in the UK from strong durable webbing with heavy duty buckles and clips, the Outboard Motor Sling is designed to perform in harsh marine environments. Retail hanging display pack includes complete illustrated instructions.








For technical support, instructional videos and products go to bartonmarine.com





88000









# Index – content

Description	Pages	Description	Pages	Description	Pages
20mm Blocks	10-11	Furling Line Blocks/Leads	84-85	Sheet Fairleads	110
20mm T track	62-63	Glands	45	Shroud Cleats	106
25mm T rack	64-65	Genoa Cars	58, 60-67	Single Line reefing kits	89
30mm Blocks	12-13	Goose neck Fitting	89	SkyDock	115
32mm T Track	66-68	Gudgeons	98	SkyLock	41
35mm Blocks	14-15	Handy Billy	90	Slab Reefing Kits	89
45mm Blocks	16-17	High Load Blocks	38-40	Snatch Blocks	41, 46
54 & 58mm Blocks	18-19	High Load Eyes	42-43	Snubbing Winch	81
64mm Blocks	20-21	Hooks	89, 101,	Spinnakers Fairlead	98
70mm Blocks	22-23	I Beam Track	70-72	Spinnakers Pole Attachmen	
Aluminium Tiller Extensions	96	Industrial Blocks	36, 46, 47	Splicing Fids	113
Back Stay Tensioner	38	Inflatable Repairs	114	Split Rings	108
Beam Track	48, 70-72	Inspection Hatch	88	Springs	81-82, 108
Block & Tackle Sets	90	·	40, 78-79, 103-105	Springs For Winches	81-82
Boat Size Guide	6-7	Lacing Hooks & Buttons	101	Stainless Steel Blocks	38-40
Boom Fittings	89	Laser Kits	94	StainlessSteel Rubbing Stral	ke 103
Boom Out Haul Kits	89	Lazy Jack Sets	88	Stanchion Bulls Eyes	84-85
Boomstruts	92-93	Line Tamers	112	Stanchion Cleats	85
Boom Vangs	92-93	Low Friction Rings	42-43	Stanchion Lead Blocks	84-85
Boom Vangs With Rope	90	Main Sheet Track Systems	48-56, 59, 62-67,	Stand Up Block	10-12, 14-20, 22
Bulls Eyes	102, 110	,	70-72	Stand Up Springs	108
Bulkhead Pipe Glands	45	Mast Base Organiser	79	Stay Adjusters	98
Cam Cleats	104-105	Mast Slugs	89	Steering Block	38
Carbon Tiller Extensions	97	Mast Step	88	Strap Shackles	109
Cascade Lazy Jacks	88	Mast Support	99	Strop Blocks	22
CE Approved Blocks	46	Outboard Lift Sling	116	Swivel	109
Cheek Blocks 10, 12, 14, 1	16, 18, 36, 39-40	Outhaul Traveler Kits	89	T Track & Accessories	62-68
ClamSeals	114	Pad Eyes	102, 110	Tie Block	22, 43
Cleats	103-106	Parrel Beads	101	Tiller Clips	97
Clevis Pins	108	Pico Kits	94	Tiller extensions	96-97
Clutches	78-79	Pipe Glands & Seals (Bulkh	nead) 45	Toe Strap Bridges	101
Cringle Hook	89	Pintles	98	Top Swivel	87
Cruising Blocks	18-25	Plastic Cleats	106	Topper Kits	94
Day Boat Blocks	14-19, 24	Plastic Lacing Hooks	101	Track Systems	48-72
Deck Eyes	102, 110	Quick cleat	103	T-track cleats	65, 67
Deck Organisers	79-80	Ratchet Blocks	26	T-Track Conversion Kits	67
Deck Plates	102	Recirculating Ball Bearing	Traveller Systems	Tubular Cleats	103
Deck Staples	110		48-59	Tufnol Blocks	32-37
Dinghy Blocks	10-17, 24-26	Reefing Handle	83	Turning Blocks	40
Dinghy Race Packs	94	Reefing kits	89	Universal Joints	97
Dinghy Track Systems	59	Removable Track Systems	50-51	Upright Blocks	10-18, 39
Double Folding Eyes	110	Rigging Adjusters	38, 98	Vangs	90, 92-93
Drain Bungs	98	Rigging Configurations	8-9	Victory Blocks	29-31
Easy Splice	113	Rigging Links	98	Watertight Glands	45
Emergency Repair	114	Roof Systems	74-77	Wear Pads	103, 112,
Eye Bolts	102, 110	Rope Clutches	78-79	Webbing Bridges	101
Fiddle Blocks	24-25	Rope Stoppers	101	Winch Handle Pockets	83
Fids	113	Rubbing Strakes	103	Winch Handles	83
Flexible Tiller Joint	97	Rudder Fittings	98	Winchers	82
Flush Deck Plates	102	S Hooks	109	Winches	81
Folding Pad Eyes	110	Service Kits Tracks	56	Windicator	100
Foot Blocks	40	Shackle Pins	109	Wire Rope Blocks	36, 38-39
Fuel Whistle	113	Shackles	109	Wooden Blocks	29-31
Furler	86, 87	Sheaves	111	Yacht Blocks	18-25

# Index – part number

Part no	Page	Part no	Page	Part no	Page								
18000	48	20110	54	24032	48	26101	71	30902	49	42422	98	50260	31
18000	59	20112	54	24033	48	26102	71	30910	50	42435	98	50330	31
18001	48	20113	54	24033	50	26110	71	32000	66	42450	98	50345	31
18001	59	20114	54	24040	48	26111	71	32010	66	42500	98	50360	31
18010	48	20117	54	24042	48	26900	71	32020	66	42519	98	50430	31
18010	59	20200	54	24043	48	26901	71	32030	66	42522	98	50445	31
18020	48	20201	54	24050	48	26902	71	32040	66	42535	98	50460	31
18020	59	20202	54	24052	48	28000	72	32050	66	42550	98	51223	67
18030	48	20210	56	24053	48	28010	72	32060	66	42601	98	51253	65
18030	59	20300	58	24060	48	28020	72	32300	67	42700	98	51254	65
18040	48	20310	55	24062	48	28030	72	32301	67	42810	101	52000	112
18040	59	20900	49	24063	48	28040	72	32302	68	42811	101	52001	112
18050	48	20901	49	24090	50	28050	72	32303	67	42812	101	52030	31
18050	59	20902	49	24100	48	28060	72	32304	68	42813	101	52045	31
18060	48	20910	50	24101	52	28101	72	32310	67	42814	101	52060	31
18060	59	21001	83	24103	52	28102	72	32311	67	42815	101	52100	85
18101	59 50	21002	83	24105 24107	53 53	28110	72 72	32312 32900	67 7	42816 42817	101	52100	106
18105 18110	59 59	21033 21034	83 83	24107	53	28112 28900	72 72	32900	67	42817 42818	101	52110 52111	106
18111	59 59	21034	83	24106	56 54	28900	72 72	32901	66 111	42819	101 101	52111	106 103
18112	59	21050	83	24110	54 54	28902	72 72	32996	67	43101	96	52120	103
18210	56	21055	83	24112	54	30000	48	32997	111	43101	96	52140	106
19000	70	21101	81	24114	54	30001	48	32998	67	43103	96	52141	106
19010	70	21200	81	24117	54	30001	48	32999	67	43104	96	52142	106
19020	70	21201	81	24200	54	30003	48	40040	115	43105	96	52143	106
19030	70	21202	81	24201	54	30003	50	40041	115	43106	96	52144	106
19040	70	21210	81	24202	54	30012	48	40050	115	43201	96	52145	106
19050	70	21211	81	24210	56	30013	48	40051	115	43202	96	52160	107
19060	70	21212	81	24300	58	30013	50	40060	115	43203	96	52161	107
19100	70	21323	83	24310	55	30020	48	40061	115	43204	96	52162	107
19103	70	21641	82	24400	89	30022	48	40080	115	43205	96	52230	31
19105	70	21642	82	24401	89	30023	48	40081	115	43206	96	52245	31
19900	70	21643	82	24402	89	30023	50	41130	89	43500	97	52260	31
19901	70	21644	82	24900	49	30030	48	41140	88	43501	97	52330	31
19902	70	22000	63	24901	49	30032	48	41143	88	43502	97	52345	31
20000	48	22010	63	24902	49	30033	48	41160	88	43503	97	52360	31
20001	48	22020	63	24905	89	30033	50	41161	88	43504	97	52430	31
20002	48	22030	63	24906	89	30040	48	41162	88	43506	97	52445	31
20003	48	22040	63	24907	89	30042	48	41201	115	43509	97	52460	31
20003	50	22050	63	24910	50	30043	48	41483	89	43514	97 07	53030	31
20010 20012	48	22060	63	25000 25010	64	30050	48	41484	89 89	43515	97 07	53045	31
20012	48 48	22100 22200	62 62	25010	64 64	30052 30053	48 48	41496 41497	69 89	43600 43601	97 97	53060 53230	31 31
20013	50	22220	62	25030	64	30060	48	41477	89	43605	97	53245	31
20013	48	22221	62	25040	64	30062	48	41517	89	44001	93	53243	31
20020	48	22300	63	25050	64	30063	48	42102	63	44001	93	53330	31
20023	48	22301	63	25060	64	30090	50	42102	98	44007	93	53345	31
20023	50	22310	63	25300	65	30100	48	42200	98	44008	93	53360	31
20030	48	22311	63	25301	65	30100	48	42201	98	44009	93	53430	31
20032	48	22312	63	25302	68	30101	52	42210	101	44010	93	53445	31
20033	48	22900	63	25303	65	30103	52	42211	101	44011	93	53460	31
20033	50	22901	63	25304	68	30105	53	42213	101	44020	93	60001	114
20040	48	22997	111	25310	65	30107	53	42214	101	44021	93	60010	48
20042	48	24000	48	25311	65	30108	56	42215	101	44030	93	60010	113
20043	48	24001	48	25312	65	30110	54	42216	101	44031	93	60020	103
20050	48	24002	48	25900	64	30112	54	42300	99	44035	93	60021	103
20052	48	24003	48	25901	64	30113	54	42334	87	44036	93	60030	103
20053	48	24003	50	25997	111	30114	54	42335	87	44040	93	60031	103
20060	48	24010	48	25998	65	30117	54	42336	87	44041	93	60040	103
20062	48	24012	48	25999	65	30200	54	42340	86	50010	29	60119	108
20063	48	24013	48	26000	71	30201	54	42354	98	50030	31	60120	108
20090	50	24013	50	26010	71	30202	54	42356	98	50045	31	60121	108
20101	52	24020	48	26020	71	30210	56	42357	98	50060	31	60122	108
20103	52	24022	48	26030	71	30300	58	42358	98	50080	29	60123	108
20105	53 53	24023	48	26040	71 71	30310	55 40	42359	98	50191	108	60124	82
20107	53 54	24023	50 48	26050	71 71	30900	49 49	42400	98 98	50230	31 31	60125	82 85
20108	56	24030	48	26060	71	30901	49	42419	98	50245	31	60142	85

Part no	Page	Part no	Page	Part no	Page	Part no Page	Part no	Page	Part no	Page	Part no	Page
60142	106	62054	113	82998	40	24910B 50	BPI-16	45	N02211	15	N03811	17
60150	42	62056	113	82999	40	25100GT 64	BPI-25	45	N02230	15	N04150	18
60150	85 26	67100 67101	103 103	84001 84002	100 100	25100GTB 64 25220GT 64	BPI-32	45 45	N02231 N02250	15 15	N04151 N04160	18 18
60160 60160	26 85	67101	103	84002	100	25220GT 64 25220GTB 64	BPI-50 BPI-75	45 45	N02250 N02260	15	N04160 N04250	18
60190	108	67170	112	84004	100	25220GTB 64 25221GT 64	BPI-90	45	N02280	15	N05090	19
60191	108	70100	105	84005	100	25221GTB 64	N00110	10	N02290	84	N05091	19
60203	108	70101	105	88000	116	25300B 65	N00111	10	N02290R	84	N05110	19
60204	108	70104	105	88001	116	25301B 65	N00130	10	N02310	15	N05111	19
60207	108	70105	105	90301	41	25302B 68	N00131	10	N02311	15	N05120	19
60208	108	70106	105	90401	41	25303B 65	N00150	10	N02330	15	N05121	19
60209	108	70116	105	90402	41	25304B 68	N00160	10	N02331	15	N05130	19
60210 60212	108 108	70126 70136	105 105	90500 91020	26 38	25310B 65 25311B 65	N00170 N00190	10 10	N02410 N02411	24 24	N05131 N05140	19 19
60304	110	70136	105	91020	38	25311B 65 25312B 65	N00190	10	N02411	24	N05140	19
60305	110	70140	105	91200	38	30900B 50	N00210	10	N02431	24	N05171	19
60306	110	70200	105	91300	38	30910B 50	N00211	10	N02440	24	N05171	19
60307	110	70201	105	91301	38	32100GT 67	N00230	11	N02441	24	N05190	84
60308	110	70204	105	91302	38	32100GTB 67	N00231	11	N02531	15	N05210	19
60308	110	70205	105	91303	38	32101HD 67	N00250	11	N02541	15	N05211	19
60310	109	70206	105	91400	39	32101HDB 67	N00310	11	N02571	15	N05220	19
60311	109	70226	105	91500	39	32210GT 67	N00311	11	N02591	85	N05221	19
60312 60320	109 109	70236 70240	105 105	91600 91650	39 39	32210GTB 67 32211HD 67	N00330 N00331	11 11	N02631 N02641	24 24	N05230 N05231	19 19
60320	109	70240	105	91700	39	322111D 67 32211HDB 67	N00531	11	N02041	38	N05291	84
60321	109	70300	105	91750	39	32221GT 67	N00930	11	N02740	15	N05270	84
60323	109	70301	105	92030	46	32221GTB 67	N00931	11	N03090	16	N05320	19
60330	102	70304	105	92050	46	32300B 67	N00932	11	N03091	16	N05321	19
60331	102	70305	105	92075	46	32301B 67	N01090	12	N03110	16	N05330	19
60332	102	70306	105	92100	46	32302B 68	N01091	12	N03111	16	N05331	19
60343	109	70316	105	92135	46	32303B 67	N01110	12	N03130	16	N05410	25
60344	109	70326	105	98075	94	32304B 68	N01111	12	N03131	16	N05411	25
60350 60355	109 109	70336 70340	105 105	98076 98077	94 94	32310B 67 32311B 67	N01130 N01131	12 12	N03140 N03141	16 16	N05420 N05421	25 25
60360	107	70340	105	98078	94	32311B 67	N01150	12	N03141	16	N05421	25
60361	102	80500	79	98079	94	32900B 67	N01151	12	N03151	16	N05431	25
60362	102	80501	79	98080	94	32996M 67	N01160	12	N03160	16	N05440	25
60363	102	80502	79	98095	94	32998M 67	N01170	12	N03161	16	N05441	25
60364	102	81500	78	98096	95	32999M 67	N01180	12	N03170	16	N05461	25
60365	102	81501	78	98098	95	42102B 63	N01190	13	N03171	16	N05531	19
60410	110	81502	78	98099	95	51253B 65	N01210	13	N03190	84	N05541	19
60411	110 102	81540 81541	78 78	99701 99766	76	51254B 65 52160B 107	N01211 N01230	13 13	N03210 N03211	17 17	N05571 N05591	19 85
60415 60415	1102	81545	78 78	99767	76 76	52160B 107 52161B 107	N01230	13	N03211	17	N05631	o5 25
60420	110	81546	78	99789	77	52161B 107	N01251	13	N03230	17	N05930	19
60421	110	81547	78	99790	77	60410P 110	N01280	13	N03250	17	N05931	19
60422	110	81548	78	702016	105	81546S 78	N01310	13	N03290	84	N06090	20
60423	110	81549	78	02900	90	81550B 79	N01311	13	N03290R	84	N06110	20
60449	42	81550	79	03900	90	97701-01 76	N01330	13	N03310	17	N06111	20
60450	42	81565	78	03901	90	99701-02 76	N01331	13	N03311	17	N06120	20
60451	42	81581	80	05900 20090B	90	99701-03 76	N02090	14	N03330	17 17	N06121 N06130	20
60452 60453	42 42	81582 81583	80 80	20090B 20910B	50 50	99767-01 76 99767-02 76	N02091 N02110	14 14	N03331 N03410	17 24	N06130 N06131	20 20
60454	42	81584	80	21200-03		99790-01 77	N02110	14	N03410	24	N06140	20
60460	42	81585	80	21200-03		99790-02 77	N02111	14	N03430	24	N06141	20
60461	42	81586	80	22100B	62	99790-03 77	N02131	14	N03431	24	N06170	20
60462	42	81682	80	22200B	62	99790-04 77	N02140	14	N03440	24	N06171	20
60463	42	81683	80	22220B	62	BPB-110 45	N02141	14	N03441	24	N06210	20
60700	109	81684	80	22221B	62	BPB-180 45	N02150	14	N03511	17	N06211	20
60701	109	81685	80	22300B	63	BPB-50 45	N02151	14	N03531	17	N06220	20
60702	109	81686	80	22301B	63	BPB-63 45	N02160	14	N03541	17 17	N06221	21
60703 60708	109 109	82100 82200	40 40	22310B 22311B	63 63	BPG-110 45 BPG-180 45	N02161 N02170	14 1 <i>4</i>	N03571 N03591	17 85	N06230 N06231	21 21
60708	109	82200	40 40	22311B 22312B	63 63	BPG-180 45 BPG-50 45	N02170 N02171	14 14	N03591 N03630	85 24	N06231 N06310	21
60750	88	82995	40	22900B	63	BPG-63 45	N02171	14	N03631	24	N06310	21
62050	113	82996	40	24090B	50	BPI-125 45	N02190	84	N03641	24	N06320	21
62053	113	82997	40	24905SK	89	BPI-140 45	N02210	15	N03810	17	N06321	21

### Index - part number (cont'd)

Part no	Page	Part no	Page	Part no	Page	Part no	Page	Part no	Page	Part no	Page	Part no	Page
			_		_		-		•		•		J
N06330 N06331	21 21	N10931 N10932	11 11	N13111 N13130	16 16	N15411 N15420	25 25	N17321 N17330	23 23	T01330 T01331	34 34	T04310 T04311	34 34
N06420	25	N110732	12	N13130	16	N15420	25	N17331	23	T01331	34	T04311	34
N06421	25	N11070	12	N13140	16	N15430	25	N17420	25	T01410	34	T04331	34
N06430	25	N11110	12	N13141	16	N15431	25	N17421	25	T01430	34	T06110	33
N06431	25	N11111	12	N13150	16	N15440	25	N17430	25	T01431	34	T06111	33
N06440	25	N11130	12	N13151	16	N15441	25	N17431	25	T01610	34	T06130	33
N06441	25	N11131	12	N13160	16	N15461	25	N17440	25	T01611	34	T06131	33
N06510	21	N11150	12	N13170	16	N15531	19	N17441	25	T01630	35	T06180	33
N06511	21	N11151	12	N13171	16	N15541	19	N17631	25	T01631	35	T06181	33
N06631	25	N11160	12	N13190	84	N15571	19	N17641	25	T02110	33	T06210	33
N06641	25	N11170	12	N13210	17	N15631	25	N17930	23	T02111	33	T06211	33
N06690 N06931	21 21	N11180 N11190	12 13	N13211 N13230	17 17	N15930 N15931	19 19	N17931 N25997	23 65	T02130 T02131	33 33	T06230 T06231	33 33
N07090	22	N11170	13	N13230	17	N16090	20	N32995	67	T02131	36	T06231	33 34
N07110	22	N11211	13	N13250	17	N16110	20	N32997	67	T02180	33	T06310	34
N07111	22	N11230	13	N13290	84	N16111	20	N64800	111	T02181	33	T06330	34
N07120	22	N11231	13	N13290R		N16120	20	N64801	111	T02210	33	T06331	34
N07121	22	N11250	13	N13310	17	N16121	20	N64802	111	T02211	33	T46110	36
N07130	22	N11280	13	N13311	17	N16130	20	N64803	80	T02230	33	T47110	36
N07131	22	N11310	13	N13330	17	N16131	20	N64803	111	T02231	33	T47111	36
N07140	22	N11311	13	N13331	17	N16140	20	N64804	111	T02310	34	T47230	36
N07141	22	N11330	13	N13410	24	N16141	20	N64805	111	T02311	34	T47231	36
N07170	22	N11331	13	N13411	24	N16170	20	N64806	111	T02330	34	T64030	35
N07171 N07191	22 22	N12090 N12091	14 14	N13430 N13431	24 24	N16171 N16210	20 20	N64807 N64808	111 80	T02331 T02410	34	T64040 T64050	35 35
N07191	22 46	N12091	14	N13431 N13440	24 24	N16210	20	N64808	111	T02410	34 34	T64060	35 35
N07171	23	N12110	14	N13440	24	N16220	20	N64809	111	T02411	34	T64080	35
N07221	23	N12130	14	N13511	17	N16221	21	N64810	111	T02431	34	T64100	35
N07230	23	N12131	14	N13531	17	N16230	21	N64811	111	T02610	34	T65030	35
N07231	23	N12140	14	N13541	17	N16231	21	N64812	111	T02611	34	T65040	35
N07320	23	N12141	14	N13571	17	N16310	21	N64813	111	T02630	35	T65050	35
N07321	23	N12150	14	N13630	24	N16311	21	N64814	111	T02631	35	T65060	35
N07330	23	N12151	14	N13631	24	N16320	21	N64815	111	T03110	33	T65080	35
N07331	23	N12160	14	N13641	24	N16321	21	N64816	111	T03111	33	T65100	35
N07420 N07421	25 25	N12170 N12171	14 14	N13810 N13811	17 17	N16330 N16331	21 21	N64817 N64901	111 111	T03130 T03131	33 33	T70200 T70201	35 35
N07421	25 25	N12171	14	N14150	17	N16420	25	N64901	111	T03131	36	T70201	35 35
N07430	25	N12190	84	N14151	18	N16421	25	N64904	111	T03180	33	T70300	35
N07440	25	N12210	15	N14160	18	N16430	25	N64906	111	T03181	33	T91304	36
N07441	25	N12211	15	N14250	18	N16431	25	N64907	111	T03210	33	T91305	36
N07631	25	N12230	15	N15090	19	N16440	25	N64908	111	T03211	33	T91306	36
N07641	25	N12231	15	N15091	19	N16441	25	N64909	111	T03230	33	T91307	36
N07930	23	N12250	15	N15110	19	N16510	21	N64910	111	T03231	33	T92304	36
N07931	23	N12260	15	N15111	19	N16511	21	N64912	111	T03310	34	T92305	36
N09411	41	N12280	15	N15120	19	N16631	25	N64913	111	T03311	34	T92306	36
N09421 N10110	41 10	N12290 N12290R	84 84	N15121 N15130	19 19	N16641 N16690	25 21	N64914 N64915	111 111	T03330 T03331	34 34	T92308	36
N10110	10	N12310	15	N15130	19	N16931	21	N64916	111	T03331	34		
N10111	10	N12311	15	N15140	19	N17090	22	N64917	111	T03411	34		
N10131	10	N12330	15	N15141	19	N17110	22	T00110	33	T03430	34		
N10150	10	N12331	15	N15170	19	N17111	22	T00111	33	T03431	34		
N10160	10	N12410	24	N15171	19	N17120	22	T00130	33	T03610	34		
N10170	10	N12411	24	N15190	84	N17121	22	T00131	33	T03611	34		
N10190	10	N12430	24	N15210	19	N17130	22	T01110	33	T03630	35		
N10191	10	N12431	24	N15211	19	N17131	22	T01111	33	T03631	35		
N10210	10 10	N12440	24	N15220	19 10	N17140	22	T01130	33	T04110	33		
N10211 N10230	10 11	N12441 N12531	24 15	N15221 N15230	19 19	N17141 N17170	22 22	T01131 T01160	33 36	T04111 T04130	33 33		
N10230	11	N12531	15 15	N15230 N15231	19	N17170	22	T01180	36 33	T04130	33		
N10251	11	N12571	15	N15231	84	N17171	22	T01180	33	T04131	36		
N10310	11	N12631	24	N15290R		N17191	46	T01210	33	T04180	33		
N10311	11	N12641	24	N15320	19	N17220	23	T01211	33	T04181	33		
N10330	11	N12931	15	N15321	19	N17221	23	T01230	33	T04210	33		
N10331	11	N13090	16	N15330	19	N17230	23	T01231	33	T04211	33		
N10511	11	N13091	16	N15331	19	N17231	23	T01310	34	T04230	33		
N10930	11	N13110	16	N15410	25	N17320	23	T01311	34	T04231	33		















Barton Marine Equipment Limited Marine House Tyler Way Whitstable Kent CT5 2RS UK

t: +44 (0) 1227 792979 e: sales@bartonmarine.com

w: www.bartonmarine.com

Front cover photo from The International Dragon Association
Inside back page photo from Ralston Gallery, Maine, USA – www.ralstongallery.com

Barton US LLC Warehouse and Logistics 4304 Kecoughtan Road Hampton Virgina 23669 USA

t: +1 732 902 0400 e: info@bartonUS.com w: www.bartonUS.com